BERTAZZONI PROFESSIONAL SERIES

24" UNDERMOUNT CANOPY HOOD KU24 PRO 1 X



The single-motor canopy hoods deliver extraction power up to 600 CFM with three different power settings. They come equipped with aluminum mesh filters or optional baffle filters, all easily removable and dishwasher safe. They can be installed under a cabinet or on the wall with an optional narrow or wide duct cover. The design matches Bertazzoni Professional Series ranges and cooktops while also complementing other Bertazzoni Series.

SINGLE MOTOR CANOPY



Single motor canopy hood shown with optional narrow duct cover.





BERTAZZONI PROFESSIONAL SERIES


24" UNDERMOUNT CANOPY HOOD KU24 PRO 1 X

FEATURES

Motor	3 speeds
Halogen lights	2
Filters	aluminium mesh
Motor power	600 cfm







TECHNICAL SPECIFICATIONS

Electrical Requirements	120V 60Hz			
Max. Amp Usage	3.3 Amp			
Certification	CSA			
Warranty	2 years parts a	2 years parts and labor		
Electronic control	1			
Product weight	28.7 lbs			
Box weight	30 lbs			
ACCESSORIES				
Recirculation kit		code 901154		
Duct cover		code 901262		
Duct cover for ceiling height 8-10 ft		code 901281		
European Baffle Filter - 3 filters (optional)		code 901253		

This model is not suited for recirculation

DIMENSIONS

Ref.	Description	Dimensions	
Rei.	Description	Inches	mm
D	Hood max depth	19 ⁵ / ₁₆	490
D1	Hood min depth	12	305
L	Duct cover depth	3 11/16	93
S	Max body hood height	10 ¹/ ₈	275
S1	Hood control panel height	1 ⁵ / ₈	40
W	Hood width	23 7/8	595
W1	Narrow duct cover width	97/16	240
D2	Narrow duct cover depth	6 11/16	170
H1	Narrow duct cover min height	36 ¹ / ₄	920
H2	Narrow duct cover max height	72 ¹ / ₂	1842

INSTALLATION INSTRUCTIONS

Bertazzoni recomends to operate the appliance after it has been properly installed. Please refer to the installation manual for further details.