

Ventilation

HCP36651UC 36" Pyramid Canopy Chimney Hood 500 Series - Stainless Steel





Wall Mounted Chimney Hoods Add Style and Sophistication to the Kitchen and Gives You Greater Freedom in Your Kitchen Planning

- Touch Controls with LCD Display
- 600 CFM Centrifugal Integrated Blower Included
- Four Speed Touch Controls with LCD Display
- Dishwasher Safe Aluminum Mesh Filters
- Converts to Recirculation Mode with Accessory Kit (Separate Purchase Required)

Technical Data

Operating Mode : Conv Number of speed settings :	vertable: Ducted / Recirculating 4-stage
Optional accessories : HCIFI	LTUC, HCPEXT5UC, HCREC5UC
Number of lights :	2
Type of lamps used :	Halogen
Total power of the lamps (W) :	40
Grease filter material :	Washable aluminium
Grease filter type :	Multilayer cassette
UPC code :	825225909033
Material :	Stainless steel 530
Watts (W) : Volts (V) :	110
Frequency (Hz) :	60
Approval certificates :	CUL, UL
Power cord length (cm) :	0
Plug type :	no plug
Overall appliance dimensions (HxWxD) (in) :	
24 9/16" - 38 7/8" / 28 1/4" - 42 9/16" x 36 " x 19 11/16 '	
Overall appliance dimensions (HxWxD) (mm) :	
	718-1081 x 914 x 500
Product packaging dimensions (HxWxD) (in) :	
	26.25 x 39.99 x 17.75
Height of the chimney (in) :	
19 9/16" - 33 7/8"/2	23 1/4" - 42 9/16"
Height of the chimney (mm) :	498-861
Required distance above cooktop	/ranges : 24"/27 "
Net weight (lbs) :	53
Net weight (kg) :	24.0
Gross weight (lbs) :	59
Gross weight (kg) :	27.0
Motor location : Integrated motor in hood chimney	
Diameter of air duct (in) top :	8
No-return airflow flap :	Yes

Optional accessories

HCIFILTUC : Wall/Island Chimney Charcoal Filter HCPEXT5UC : Pyramid Chimney Extension HCREC5UC : Wall Chimney Recirc. Kit



Ventilation

HCP36651UC

36" Pyramid Canopy Chimney Hood 500 Series - Stainless Steel

Wall Mounted Chimney Hoods Add Style and Sophistication to the Kitchen and Gives You Greater Freedom in Your Kitchen Planning

Design

- Duct Extension Accessory Kit Available for 9' to 11.5' Ceilings

Performance

- 2 Halogen Lights 12 Volt, 20 Watt Max., G-4 Base
- 8" round duct at discharge.

Efficiency

- Blower will automatically turn on at high speed if excessive heat is sensed in the control area.
- Absorb odors with charcoal replacement filters.


Convenience

- Convenient timer built into control from 1-60 minutes.
- Signal on LCD display will illuminate as a reminder to check filters for cleaning.
- Audible tone when select controls are pressed.



Ventilation

HCP36651UC 36" Pyramid Canopy Chimney Hood 500 Series - Stainless Steel



* Recirculating installation ** Ducted installation

Installation height above cocking surface. 24"-34" (610 mm-864 mm) to Electric 27"-34" (686 mm-864 mm) to Gas

measurements in inches (mm)