ELECTRIC OVENS

CRVSOE330 – 30" WIDE SINGLE OVEN CRVDOE330 – 30" WIDE DOUBLE OVEN



Features and Functions

- Extra large oven cavity provides for all your cooking needs
- 4.3 cu. ft. overall
- 3.8 cu. ft. measured to AHAM standard
 (See specifications chart for oven interior dimensions)
- Ten high performance cooking modes include Two Element Bake, Convection Bake, TruConvec[™] Convection Cooking, Convection Roast, Convection Broil, Hi Broil, Medium Broil, Low Broil, Convection Dehydrate, and Convection Defrost
- Two-speed convection system circulates air throughout entire oven cavity for maximum airflow and excellent cooking results (both ovens in double oven)
- 10-pass broiler with heat reflector provides excellent results for a variety of broiling applications
- Concealed six-pass element provides excellent temperature control while allowing oven cavity to be easily cleaned
- Meat probe ensures perfect baking/roasting of meats (upper oven only in double oven)
- Each oven has five porcelain-coated rack supports and comes standard with three heavy-duty oven racks, including two TruGlide™ Full Extension Oven Racks
- Digital clock/timer
- 100-minute timer allows you to set cooking time for up to
 12 hours
- Tone and digital display indicate when pre-set cooking time is finished
- Custom oven settings offer options including degree format and clock format
- Two halogen oven lights provide plenty of light throughout the oven cavity
- Star-K certified with dedicated Sabbath mode

Easy Operation and Cleanup

- Extra large self-clean convection oven
- Concealed six-pass bake element makes cleaning bottom of oven easy
- Durable metal die-cast knobs with child-proof, push-to-turn safety feature

Multiple Design Options

- Standard or flush mount installation
- Oven can be installed flush to cabinet with accessory flush mount installation kit

Installation Accessories

- Flush mount installation kit for single oven (D30FTS)
- Flush mount installation kit for double oven (P30FTD)

Finishes

• Available in Stainless Steel (SS), Black (BK), and White (WH)



Warranty Highlights

- Three-year full complete product
- Ninety-day full cosmetic parts such as glass, painted items, and decorative items
- Lifetime limited stainless steel exterior
- Ten-year limited porcelain oven(s) and porcelain inner door panel(s)
- Five-year limited electric heating elements









30" Wide Electric Double Oven

| DESCRIPTION | ELECTRIC 30" WIDE OVENS | |
|--------------------------------|---|--|
| | CRVSOE330 | CRVDOE330 |
| Overall Width | 29 3/4" (75.6 cm) | |
| Overall Height | 29 3/8" (74.6 cm) | 51 3/8" (130.5 cm) |
| Overall Depth | To front of door – 25 3/16" (64.3 cm) | |
| Cutout Width | Standard – 28 1/2" (72.4 cm) Flush mount* – 29 5/8" (75.2 cm) | |
| Cutout Height | Standard – 28 1/4" (71.8 cm) Flush mount* – 29 1/2" (74.9 cm) | Standard – 50 5/8" (128.6 cm) Flush mount* – 51 1/2" (130.8 cm) |
| Cutout Depth | Standard – 24" (61.0 cm) Flush mount* – 25 1/4" (64.1 cm) | |
| Electrical Requirements | 4-wire ground, 240VAC, 30-amp electrical connection for single oven/50-amp for double oven. Unit is equipped with No. 10 ground wire conduit. Should be fused separately. | |
| Maximum Amp Usage | 240V – 23.3 amps 208V – 20.2 amps | 240V – 46.7 amps 208V – 40.5 amps |
| Oven Interior Width | 25" (63.5 cm) | |
| Oven Interior Height | 16" (40.6 cm) | |
| Oven Interior Depth | 18 1/2" (50.0 cm) | |
| Oven Volume | Overall – 4.3 cu. ft. AHAM** – 3.8 cu. ft. | |
| Approximate Shipping Weight | 259 lb. (117.6 kg) | 374 lb. (174.2 kg) |

^{*} To install the oven in a flush mount application, the flush mount accessory kit (D30FTS for single oven and D30FTD for double ovens) is required.





^{**}The AHAM standard for measuring oven capacity subtracts the doorplug and convection baffle dimension from the total oven volume.