



PERFORMANCE DATA NO LOAD & NO DRAWER OPENINGS AT MID-POINT CONTROL SETTINGS		
Type A with Run/Start Capacitor	65° (18°C) Ambient	90° (32°C) Ambient
Operating Time	15 to 35%	35 to 55%
Temperature	34°F to 42°F	34°F to 42°F
Low Side Pressure (cut-in)	25 to 50 psig 172 to 345 kPa	25 to 50 psig 172 to 345 kPa
Low Side Pressure (cut-out)	0 to 10 psig 0 to 69 kPa	0 to 10 psig 0 to 69 kPa
High Side Pressure (last 1/3 cycle)	95 to 125 psig 655 to 862 kPa	130 to 175 psig 896 to 1207 kPa
Wattage (last 1/3 cycle)	55 to 80	55 to 80
Amps (running)	.45 to .85	.45 to .85
Base voltage	115 vac (127 vac max)	
CONDENSER FAN MOTOR		
Watts	RPM	Amps
4.1	1280	0.06
EVAPORATOR FAN MOTOR		
1.08	2550	0.09

SERVICE DATA SHEET
41013618
REFRIGERATOR DRAWERS - R134a

IMPORTANT SAFETY NOTE

The information provided herein is designed to assist qualified repair personnel only. Untrained persons should not attempt to make repairs due to the possibility of electrical shock. Disconnect power cord before servicing this appliance.

IMPORTANT

If any green grounding wires are removed during servicing, they must be returned to their original position and properly secured.

CAUTION

All electrical parts and wiring must be shielded from torch flame. DO NOT allow torch to touch insulation; it will char at 200°F and flash ignite (burn) at 500°F. Excessive heat will distort the plastic liner.

WARNING

Double drawer refrigerator drawers are designed to be built-in only. They cannot be used for free-standing.

The screw supplied with the Anti-Tip Kit are for mounting the bracket to a wood floor. This screw will not work if used with sheetrock (dry wall) or anything other than wood.

IMPORTANT: PLEASE RETURN THIS SHEET TO IT'S ORIGINAL LOCATION.

NOTE

Your Electrolux refrigerator drawers has been designed for built-in installation. When built-in, your refrigerator drawers do not require additional air space for top, sides or rear. In either case, the front grille must **NOT** be obstructed.

To ease unit installation and removal, it is recommended that the cabinet rough opening dimensions be increased by at least ¼ inch over the dimensions given for the unit.

Unit Dimensions

Width	Height	Depth
23 ⁷ / ₈ inch	33 ³ / ₄ to 34 ³ / ₄ inch	26 ¹¹ / ₃₂ inch



