

# Front Load Washers EIFLS60L SS, EIFLS60L T, EIFLS60J IW

## IQ-Touch<sup>™</sup> Electronic Controls Featuring Perfect Steam<sup>™</sup>





Island White

Optional Luxury-Glide® Touch-2-Open™ Pedestals Shown in

Available Colours.

Most Efficient

Silver Sands EIFLS60L SS



# ExpertCare<sup>™</sup> Wash System

State-of-the-art wash technology includes varied wash motions and bottom-vent steam options to deliver the best front-load cleaning performance.

ipeed So	bil		tions
	max G	a stal	n treat
•	heavy		y start
	0	pret	wash
		2	u I steam♀
6	e la construction de la construc	and a	k guard
E	9	2	h rinse
			trol lock
	um o	• max • heavy um • normal • light	max m

Perfect Steam<sup>™</sup> Washer

Add steam to select wash cycles to gently deep clean clothes for better stain removal.



**Fastest Wash Time**<sup>1</sup> Fifteen minutes to wash.



Sure-2-Fit<sup>®</sup> Capacity Washer

Wash more in one load with our large capacity washer.

### 27" ELECTRIC FRONT LOAD WASHERS

Capacity O.E.E./I.E.C.	4.30/5.0 Cu. Ft.
Features	
Door Design	Signature Soft-Arc
Electronic Controls	IQ-Touch <sup>™</sup> with LCD Display
Perfect Steam <sup>™</sup> Wash System	Yes
Balance System	Perfect Balance®
Sound System	Luxury-Quiet™
Lighting	Luxury-Design®
Touch-2-Open™/(Close) Door	Yes
Touch-2-Open <sup>™</sup> /(Close) Dispenser Drawer	Luxury-Glide®
Wash System	ExpertCare™
Integral Water Heater	Yes
Wash Drum	Stainless Steel
Automatic Temperature Control	Yes
Automatic Water Level Adjustment	Yes
Auto Prewash Detergent Dispenser (Liquid/Powder)	Yes
Auto Bleach Dispenser (Liquid Only)	Yes
Auto Detergent Dispenser (Liquid/Powder)	Yes
Auto Fabric Softener Dispenser (Liquid Only)	Yes
Tumble Speed (RPM)	Variable
Spin Speed (RPM)	1,300
Reversible Door	Yes
	Yes
Adjustable Leveling Legs	Most Efficient <sup>2</sup>
NSF® Certified	
INSF® Certified	Sanitize/Allergen
Cycles	
Fast Wash*, My Favourite (1), Deep Clean Sanitize*, Heavy Duty*, Whitest Whites*, Colours*, Normal*, Casual*, Delicates, Allergen*, Rinse & Spin (*Can be used with Add Steam option)	11
Specialty Cycles – Jeans, Fast Sanitize, Stuffed Animals, Pet Beds, Clean Washer, Active Wear, Fast Steam	7
Options	
Wash/Rinse Temperature Combinations	9
Temperature Selections	5
Add Steam	7
Spin Speed Selections	5
Soil Level Selections	5
Delay Start (Hours)	22
End-of-Cycle Chime	Adjustable
Installation Options	
Freestanding, Under Counter*, Stacked (Under Dryer), Pedestal, Hidden (In Closet), Second Floor	Yes
Accessories	
Luxury-Glide® Touch-2-Open <sup>™</sup> /(Close) Pedestal – Silver Sands – PN # EPWD15SS Titanium – PN# EPWD15T Island White – PN# EPWD15IW	Optional
Dryer Stacking Kit – PN# STACKIT4X	Optional
Drain Hose Extension Kit – PN# 137098000	Optional
Mobile Home Installation Kit - PN# 137067200	Optional
	•
Specifications	
Colour –	
Silver Sands	SS
Titanium	Т
Island White	IW
Product Dimensions –	
Height Without 15" Pedestal)	38"
(With 15" Pedestal)	53"
Width	27"
Depth (to Centre of Arc Not Including Hose)	31-1/2"
(with 90° Door Open)	50-5/8"
Power Supply/	Top Right Rear/
Water Inlet Location	Top Left Rear
	120V/60 Hz/15A
Voltage Rating	1.2
	1.2
Connected Load (kW Rating) @ 120 Volts <sup>‡</sup>	1200
Voltage Rating Connected Load (kW Rating) @ 120 Volts <sup>‡</sup> Watts @ 120 Volts Amps @ 120 Volts	
Connected Load (kW Rating) @ 120 Volts <sup>±</sup> Watts @ 120 Volts	1200


NOTE: Always consult local and national electric & plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at electroluxappliances.ca. Specifications subject to change.



# Front Load Washers

EIFLS60L SS, EIFLS60L T, EIFLS60J IW





Elevates washer height to 53". For detailed pedestal installation, refer to instructions included with pedestal or on web. **Note:** Pedestal Installation requires modified utility hookup locations. For details, refer to Product Installation Guide on web.

Side-by-Side Units in Under-Counter Installation Requires custom-built countertop and/or cabinetry.

Washer

A - 311/2" (with non-steam dryer) / 321/4" (with steam dryer)

\* To achieve minimal depth dimensions or clearances, dryer MUST be vented straight back or with quick-turn 90° elbow.

Dryer



### Front Load Washer Specifications

- Product Weight 237 Lbs.
- An electrical supply with grounded three-prong receptacle is required. The power supply circuit must be installed in accordance with national and local codes & ordinances. (*Do not use same circuit as dryer.*)
- Voltage Rating 120V/60 Hz/15 Amps
- Amps @ 120 Volts = 12 Amps
- Connected Load (kW Rating) @ 120 Volts = 1.2 kW
- Equipped with 120V 3-wire power supply cord, approx. 60" long.
- Always consult local and national electric & plumbing codes.
- To maximize detergent effectiveness, ambient temperature should never be below 60° F.
- Can be installed alone, with or without optional 15" pedestal drawer, or stacked beneath matching Electrolux Dryer, which requires installation of optional dryer stacking kit. (For installation details, refer to instructions included with optional pedestal or stacking kit or on web.)
- Can be built in with matching Electrolux Dryer in under-counter, recessed or closet installation. Installations requiring countertop and/or cabinetry will require custom building. (Refer to Built-In Installations on this page for cutout dimensions. For additional installation details, refer to Product Installation Guide on web.)
- Closet installation requires vented door with 2 unobstructed louvered openings, minimum 60 sq. in. each, located 3" from top and bottom of door. Full-length 120 sq. in. opening also acceptable. Allow 1" clearance between door and fronts of units.

- Do NOT install in area exposed to dripping water or outdoor weather conditions, or where gasoline or other flammables, including automobiles, are kept or stored.
- Floor MUST be solid with 1" maximum slope. To ensure vibration or movement does not occur, reinforcement of floor may be necessary. Do NOT install on carpeted surface.

Installation Guide on web

- Leveling legs supplied to level washer properly and reduce excessive noise and vibration.
- H/C water faucets MUST be installed within 42" of washer's water inlet and MUST be 3/4" garden hose type, to connect to 48-1/2" inlet hoses.
- Water pressure MUST be between 30 and 120 psi with NOT more than 10 psi pressure difference between hot and cold.
- Drain required with standpipe diameter of 1-1/4" min. and height of 24" min./96" max. above floor, capable of eliminating 17 gallons per minute. Attached 59" drain hose can reach 79"-high standpipe.

#### Note: For planning purposes only. Refer to Product Installation Guide on the web at electroluxappliances.ca for detailed instructions.

### **Optional Accessories**

- Pedestal Drawers Silver Sands (PN# EPWD15SS), Titanium (PN# EPWD15T), Island White (PN# EPWD15IW).
- Dryer Stacking Kit (PN # STACKIT4X).
- Drain Hose Extension Kit (PN# 137098000).
- Mobile Home Installation Kit (PN# 137067200).



### **Electrolux Major Appliances, N.A.**

CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • electroluxappliances.ca

EIFLS60L 10/13

High standards of quality at Electrolux Home Products, Inc. mean we are constantly working to improve our products. We reserve the right to change specifications or discontinue models without notice.