

### ASPIRE SERIES



Designed for ducted installation, Salice can also be intalled as a recirculating system using the Recirculating Kit, available as an accessory.



# **MODELS**

ESL636S2 Salice 36" Stainless ESL642S2 Salice 42" Stainless

## **DIMENSIONS**

(36"W x 27"D x 5"H) (42"W x 27"D x 5"H)



Halogen Lamps



Multi-function electronic controls with LCD display



Stainless Steel Micro Hole Filters











Size (in) & Type 36" or 42" Wide Island Finish Stainless Steel

Controls Multi-function electronic controls with LCD display

Illumination 4, 40 Watt Halogen Lamps, 2 Light Intensities (bulbs included)

Installation Type Ducted or Recirculating Installation

Recirculating Kit Sold Separately

**Blower Type** 600 CFM, 4-Speed Internal

Blower Performance Speed 1, 180 CFM, 1.6 Sones

> Speed 2, 300 CFM, 3.5 Sones Speed 3, 470 CFM, 6.5 Sones Speed 4, 600 CFM, 8.7 Sones

3, Dishwasher-Safe, Stainless Steel Microhole Filters Filter Type

**Telescopic Chimney Extension** For heights 7'9" - 9'8" (ducted)

For heights 8'0" - 10'0" (recirculating)

**Duct Transition** 6" Round with Back Draft Damper (top)

Electrical 120V-60Hz

530 Watts at 4.4 Amps

Warranty 2 Year Parts & Labor, In-Home Service



Optional Recirculating Kit for 36" and 42" Units

CODE: KIT02665 MODEL: KIT02665



Optional Long Chimney Extension Kit Reaches 9'0" - 12'0" (ducted) Reaches 9'4" - 12'4" (recirculating)

CODE: KIT0100317 MODEL: EXXRCK06

Replacement Grease Filter (1) CODE: GF04YB

Replacement Carbon Filter (1) Replacement Light Bulb (1)

CODE: 2006BH

CODE: KIT02667

Consumable parts are sold in units of one (1). Order accordingly.



Elica Heat Guard: A technology that protects the hood and cabinetry from excessive heat, by sensing extreme temperatures and automatically adjusting blower speeds accordingly.



Elica CRS: CFM Reduction System (CRS), is an exclusive feature to Elica hoods, which enables the installer to reduce the maximum blower CFM, to meet local code requirements.

