ASPIRE SERIES

When the view out your kitchen window is too spectacular to disrupt with a range hood, Elica's Rise is the perfect solution. Rise recesses completely out-of-sight into the countertop (when not in use), but when it's time to cook, Rise elevates a full 14" above the countertop (almost twice the height of competitors), for added ventilating efficiency. On top of that, Elica added Perimeter Aspiration Technology, which increases suction 35% and actually draws air from the front burner effectively, to create the best functioning downdraft on the market.

Rise comes equipped with a powerful 600 CFM internal blower, which is operated by an electronic rotating control that's flush mounted into the countertop or cabinet face.

For maximum flexibility, the blower can be rotated to the opposite side to make room for a floor mounted range.

Electronic Rotating
Disc Controls

Anodized Aluminum Mesh
Grease Filters plus
Perimeter Aspiration Plate

MODELS

ERS630SS   Rise 30" Stainless
ERS636SS   Rise 36" Stainless

DIMENSIONS

(30"W x 12$^{1/2}$"D x 14"H)
(36"W x 12$^{1/2}$"D x 14"H)

FEATURES

Size (in) & Type	30" or 36" Wide Downdraft
Finish	Stainless Steel
Controls	Electronic Rotating Disc
Installation Type	Ducted Installation Only
Blower Type	600 CFM, 4-Speeds Internal
Blower Performance	Speed 1, 205 CFM, 1.9 Sones
	Speed 2, 350 CFM, 3.4 Sones
	Speed 3, 510 CFM, 6.0 Sones
	Speed 4, 600 CFM, 8.0 Sones
Filter Type	Perimeter Aspiration (Aluminium Mesh Filter Behind)
	Plus Perimeter Aspiration Plate
Duct Transition	6" Round with Back Draft Damper (side)
Electrical	120V-60Hz
	410 Watts at 3.4 Amps
Warranty	2 Year Parts & Labor, In-Home Service

CONSUMABLE PARTS

Replacement Grease Filter (1)
CODE: GRI0107245A

Consumable parts are sold in units of one (1). Order accordingly.

SPECIAL FEATURES

PERIMETER ASPIRATION

Perimeter Aspiration: First developed by Elica, this tech nology literally turned the market 45 degrees and opened the door to hoods that could be mounted on the wall like pic ture frames. The technology draws air through a narrowed channel around a face plate, which increases suction, without increasing blower speed or energy consumption.

LINE DRAWING

Top trim widths:
30"
36"

$19\frac{9}{32}$"

13½" retractable vent height

1½"

27"
33"

28½"

13⅛"

5¼" for 30" models
8¼" for 36" models

16½"

10"

2⅛"