

Dishwashers

FGID2476S F/W/B



Signature Features



A Complete Clean

Clean dishes in one cycle with OrbitClean® Wash System, which uses four times more water coverage¹ for a complete clean.



Best 30-Minute Clean

Don't wait when dishes can be cleaned with the best 30-Minute Quick Clean3.



Remarkable Dry

Dishes come out remarkably dry every time with EvenDry $^{\text{TM} 2}$.



Automatically Adjusts Cycles

DishSense™ Technology automatically adjusts the cycle time based on the level of clean that your dishes need for an efficient clean.

24" Built-In

Product Dimensions

33-3/4"-35-3/4" Height (Adjustable) Width Depth (Including Door) 24-1/4"

More Easy-To-Use Features

Smudge-Proof™ Stainless Steel4 Resists fingerprints and cleans easily.

Clean Dishes of All Sizes

Loading your dishwasher is no longer a puzzle with our SpaceWise® Adjustable Rack, which adjusts to fit oversized dishes and kitchen tools of all shapes and sizes.

Ready-to-Use Dish Alert

Know when your dishes are clean with LED Floor Beam Indicator, which beams a green light alerting you that your dishes are mealtime-ready.

Stay-In-Place Door

The door stays put at whatever angle you open it for easy loading and unloading.

24-Hour Delay Start Set your dishwasher in advance to run on your schedule. It can be set to run 1-24 hours in advance.

Cleans 14 Place Settings

Clean up to 14 place settings in one cycle.

Efficient Water Usage

Cleans a full load of dishes using 15% less water5.

Stainless Steel Interior and Filtration

Durable, stainless steel interior with removable, stainless steel filter, which prevents re-depositing of food particles.

ENERGY STAR® NSF® International Certification





Available in:







¹Than a traditional spray arm.

²When used with rinse aid.


³Tested against competing models with comparable quick cycle times according to ANSI/AHAM DW-1-2010 with only 6 place settings.


⁴Select model only.

⁵Over a year when using normal cycle in our stainless tub compared to our plastic tub.

FRIGIDAIRE GALLERY.

Features	
Control Design	Fully-Integrated Express-Select*
Digital Display	Yes
Door Latch/Stay-Put Door Hinge Design	Yes/Yes
Low Rinse-Aid Indicator Light	
Interior Colour/Interior Design	Stainless Steel/Tall Tu
Wash System	Direct Feed
Wash Arm	OrbitClean®
Wash Levels/Wash Speeds	5/5
DishSense™ Technology	Yes
AquaSurge™ Technology	Yes
Sound Package	SilentDesign™
Filter/Filter Trap	S. Steel/Removable
Soft Food Disposer	
dB Level	51
Drying System	EvenDry™
Cycles	
Number of Cycles	8
PowerPlus™ (Heavy)	Yes
Normal	Yes
Light	
Quick Wash (30-Min.)	Yes
Favourite	Yes
China Crystal	Yes
Rinse Only	Yes
Energy Saver Plus	Yes
Upper Rack Wash Only	Yes
Cycle Indicator Light/Control Lock	No/Yes
Cycle Complete Floor Beam Indicator	LED
Options	
<u> </u>	\\ \\\
Heat/No Heat Dry	Yes / Yes
Hi-Temp Wash NSF® Certified Sanitize Rinse	Yes
	Yes 1-24 Hour
Delay Start	I-24 Hour
Rack System	
Rack Design	Deluxe
Rack Coating	Nylon TufRacks™
Upper Rack -	
Rack Handles	
Stemware/Champagne Glass Holders	Yes
Fold-Down Tines	Yes
Cup Shelves/Stemware Grips	2/No
Versa-Tray™	
Adjustable Rack	Yes
Lower Rack -	
SpaceWise* Silverware Basket	3-Piece Split
Fold-Down Tines	2 Full Rows
Small Items Cover	2
Third-Level Rack (Single Tray)	
Certifications	
ENERGY STAR*	Yes
NSF® International Certification	Yes
Specifications	
Specifications Water Inlet Location	Left Bottom Front
<u> </u>	Left Bottom Front 4.0 - 8.0
Water Inlet Location	
Water Inlet Location Water Usage (Gallons)	4.0 - 8.0
Water Inlet Location Water Usage (Gallons) Water Pressure (PSI)	4.0 - 8.0 20 - 120
Water Inlet Location Water Usage (Gallons) Water Pressure (PSI) Integral Air Gap on Supply	4.0 - 8.0 20 - 120 Yes
Water Inlet Location Water Usage (Gallons) Water Pressure (PSI) Integral Air Gap on Supply Leveling Legs	4.0 - 8.0 20 - 120 Yes Yes
Water Inlet Location Water Usage (Gallons) Water Pressure (PSI) Integral Air Gap on Supply Leveling Legs Power Supply Connection Location	4.0 - 8.0 20 - 120 Yes Yes Right Bottom Front







Product Dimensions	
A - Height (Adjustable)	33-3/4" - 35-3/4"
B-Width	23-3/4"
C-Depth (Including Door)	24-1/4"
D-Depth (To Tub Flange)	22-1/2"
Depth with Door Open 90°	50-1/4"

¹For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.

Cutout Dimensions	
Height (Min.)	34"
Height (Max.)	35-3/4"
Width (Min.)	24"
Depth (Min.)	24"

Accessories information available on the web at **frigidaire.ca**