

GALLERY.



Double Wall Oven

FGET3065PF



Signature Features



Quick Preheat

Preheat in less than six minutes.1



Added power means you can broil food faster.



True Convection

Single convection fan circulates hot air throughout the oven for faster and more even multi-rack baking



Effortless™ Convection

Takes the guesswork out of convection cooking - our ovens automatically adjust standard baking temperatures to convection temperatures for consistent results.

30" Electric

Product Dimensions

Height 50-7/16" Width 30" Depth 24-3/4"

More Easy-To-Use Features

Even Baking Technology

Our Even Baking Technology ensures even baking every time.

Effortless™ Temperature Probe

Take the guesswork out of cooking with the Effortless Temperature Probe that shows you the internal cooking temperature of your food. You can set the desired finished temperatire and the oven alerts you when that temperature has been reached.

Steam Cleaning

A light oven cleaning that's chemical-free, odour-free, and fast.

Smudge-Proof™ Stainless Steel

Reduces fingerprints and smudges so it's easy to clean.

Express-Select® Controls

Easily set cooking temperature or choose one-touch cooking options.

One-Touch Keep Warm Setting

Just one touch of a button keeps food warm until everything - and everyone is ready.

Auto Oven Shut-Off

As an extra safety measure, the oven will automatically shut off after six hours.

Sabbath Mode (Star-K® Certified)

Available in:




¹Based on single rack cooking performance, not set temperature, using Quick Preheat.

FGET3065PF **30" Electric**

GALLERY

Features	
Oven Control/Timing System	Express-Select®
Windows	Extra-Large
Exterior Door Finish	Smudge-Proof™ Stainless Steel
Handle Design	Stainless Steel
Oven Cleaning System	Self-Clean w/ Steam Clean Option
Oven Controls	
Bake/Broil	Yes/Variable (400 - 550 °
Effortless™ Convection Conversion	Yes
Convection Bake/Broil/Roast	Yes/Yes/Yes
Oven Preheat	Quick
My Favourite	
Slow Cook	
Effortless™ Temperature Probe	Yes (Upper Oven)
Chicken Nugget Button	
Pizza Button	
Keep Warm	Yes
Add-a-Minute	
Delay Start	Yes
Self-Clean / Clean Options	Yes/2, 3, 4 Hours
Steam Clean	Yes
Delay Clean	Yes
Kitchen Timer/Timed Cook Option	Yes/Yes
Control Lock	Yes
Auto Oven Shut-Off	6 Hours
Oven Lock-Out	Yes
Upper Oven Features	
Capacity (Cu.Ft.)	4.6
Convection System	True Convection
Oven Light	2 Halogen
Hidden Bake Element	Yes
Rack Configuration	2 Heavy Duty, 1 Offset Rac
Baking System	Even Baking Technology
Broiling System	Power Broil
Bake/Broil Element (Watts)	2,000/3,400
Lower Oven Features	
Capacity (Cu.Ft.)	4.6
Convection System	True Convection
Oven Light	2 Halogen
Hidden Bake Element	Yes
Rack Configuration	2 Heavy Duty, 1 Offset Rac
Baking System	Even Baking Technology
Broiling System	Power Broil
Bake/Broil Element (Watts)	2,000/3,400
Optional Accessories	
3"-High Bottom Trim-Stainless Steel	(S) PN# 318259707
10'-Long Armoured Power Cable	PN# 903056-9010
Certifications	
A.D.A. Compliant	
Sabbath Mode (Star-K® Certified)	Yes
Specifications	17-1/2" x 24-1/8" x 18-3/4"
·	17 1/2 X21 1/0 X 10 0/ 1
Oven Interior (H x W x D)	Left Bottom Rear
Oven Interior (H x W x D) Power Supply Connection Location	
Oven Interior (H x W x D) Power Supply Connection Location Voltage Rating Connected Load	Left Bottom Rear
Oven Interior (H x W x D) Power Supply Connection Location Voltage Rating Connected Load	Left Bottom Rear 240V/208V/60Hz
Specifications Oven Interior (H x W x D) Power Supply Connection Location Voltage Rating Connected Load (kW Rating) @ 240/208 Volts¹ Amps @ 240/208 Volts Minimum Circuit Required (Amps) Shipping Weight (Approx.)	Left Bottom Rear 240V/208V/60Hz 7.4/5.6

Single phase 3- or 4-wire cable, 120 / 240 or 120 / 208 Volt, 60 Hertz AC only electrical supply with ground required on separate circuit fused on both sides of line.



NOTE: For planning purposes only. Always consult local and national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.ca.



Product Dimensions	
A-Height	50-7/16"
B-Width	30"
C-Depth	24-3/4"
D-Height (Wrapper)	48-5/8"
E-Width (Wrapper)	28-1/4"
Depth with Door Open 90°	45-3/4"

Cutout Dimensions	
Height (Min.)/(Max.)	48-7/8" / 49-7/8"
Width (Min.)/(Max.)	28-1/2"/29"
Depth (Min.)	23-1/2"

Accessories information available on the web at **frigidaire.ca**