

FRIGIDAIRE

GALLERY



Freestanding Ranges

CGGF3032K W/B

30" Gas



Signature Features



Quick Boil

Boil water faster with our 17,000-BTU burner.



Express-Select™ Controls

Easily go from warm to boil.



Effortless™ Oven Rack

Bottom rack extends when you open the door for easy access.



Quick Bake Convection

Bake faster and more evenly with Quick Bake Convection.

Effortless Performance

Quick Bake Convection (Fan Only)
Auto Shut-Off
One-Touch Self Clean Option
Quick Clean Option
Broil Option

Performance-Driven Style

Low-Simmer Burner (5,000 - 500 BTU)
Continuous Cast Iron Grates with Black Matte Finish
Even Baking Technology
Centre Burner (9,500 BTU)

SpaceWise™ Design

Fits-More™ Cooktop

More Easy-To-Use Features

Delay Start
Extra-Large Window
Storage Drawer

Capacities

5.0 Cu. Ft. Oven Capacity

Overall Exterior Dimensions

Height	47"
Width	29-7/8"
Depth	28-1/4"

Available in:



White
(W)



Black
(B)



Based on Largest Burner Output Rating on Cooking Surface	Minimum Clearance Required
9,500 BTU or less	2"
12,000-17,000 BTU	3"
18,000 BTU or greater	5"

- Product Shipping Weight (approx.) – 215 Lbs.
- Voltage Rating – 120V/60 Hz/15 Amps
- Connected Load (kW Rating) @ 120 Volts = 1.8kW
(For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.)
- Amps @ 120 Volts = 15 Amps
- Always consult local and national electric and gas codes.
- Range ships with 3/4" factory regulator.
- Range is LP Gas convertible. (*Optional LP Gas conversion kit available.*)
- Floor beneath range MUST be solid and level.
- Overhead cabinetry should not exceed a 13" maximum depth.
- Absolute minimum horizontal distance between overhead cabinets installed to either side of appliance must be no less than maximum width of appliance.

- Range can be installed flush to wall with 0" minimum rear clearance.
- Minimum clearance required (*from edge of rangetop to nearest combustible wall on either side of range above 36" height*) is based on largest burner output rating on cooking surface.
- To reduce risk of fire when using overhead cabinetry, install range hood that projects horizontally a recommended minimum of 5" beyond bottom of cabinets.
- Follow all dimension requirements provided to prevent property damage, potential fire hazard, and incorrect countertop and cabinet cuts.

- LP Gas Conversion Kit - PN# GRLP3