



## PRODUCT DIMENSIONS

	INCHES	CENTIMETERS
Α	30	76.2
В	30	76.2
C	13	33.0
D	15 7/16	39.2
Е	29 7/8	75.9
F	16 15/16	43.0

**MODEL SKUs** 

JMV8166BAW JMV8166BAB JMV8166BAS

**NOTES:** 

- 1. Range backguard to bottom of the microwave is to be a minimum of 2" apart.
- 2. Mount the oven against a flat, vertical wall, so it is supported by the wall. The wall should be constructed of minimum 2" x 4" wood studding and 3/8" thick drywall or plaster/lath.

Style of product may vary from picture

- 3. ATTACH AT LEAST ONE of the two lag screws supporting the oven to a vertical, 2" x 4" wall stud.
- 4. DO NOT mount the microwave oven to an island or peninsula cabinet.
- 5. BE SURE the upper cabinet and rear wall structures are able to support 150 lbs., plus the weight of any items you place inside the oven or upper cabinet.
- 7. Locate the oven away from strong draft areas, such as windows, doors, and strong heating vents.
- 8. This microwave oven can be installed over gas or electric cooking products.
- 9. Use the optional filler kit UXA3036ADW/Q/B/S when installing an over-the-range microwave in a 36" opening.

Electrical requirements: Adequately wired individual 120V A/C, 60Hz approved electrical circuit. Use required fuse (15 amp) or comparable circuit breaker.