

HPIN42HS

Professional Series

42" Island Hood



HPIN42HS Stainless steel

Performance

- Three fan speeds
- Filter systems are highly efficient at capturing grease
- Powerfully quiet ventilation systems

Design

- Brushed stainless steel finish
- Chiseled design for a seamless integration into any kitchen
- Stainless steel control buttons
- All-in-one low profile solution with the flexibility of having an integrated blower

Convenience

- Halogen lighting spotlights your best recipes
- Dishwasher safe frameless filters with stainless steel covers
- Dimmer lighting - for a soft lighting effect
- Delayed shut off tackles lingering odors for up to 10 minutes
- Built-in 'Clean Filter' reminder light illuminates after 40 hours of operation
- Blowers sold separately

Capacity


- Inline Blowers: VTI610D (600 CFM) or VTI1010D (1000 CFM)
- Remote Blowers: VTR630D (600 CFM) or VTR1030D (1000 CFM) or VTR1330E (1300 CFM)
- Remote Blower requires Roof Plate RFPLT600 for roof installations (600 CFM)
- Remote Blowers require Roof Plate RFPLT1000 for roof installations (1000/1300 CFM)
- 6" Round duct size
- Vertical ducting direction

825225885832

HPIN42HS

Professional Series

42" Island Hood



Product Features

Operating Mode: Ducted
Number of speed settings: 3-stage
Delay Shut off modes: 10
Number of lights: 4
Type of lamps used: Halogen
Total power of the lamps (W): 80
Grease filter material: Washable stainless steel
Grease filter type: Multilayer cassette
Clean filter reminders: Electronic

Consumption and connection features

UPC code: 825225885832
Material: Alu, Stainless steel
Watts (W): 80
Current (A): 10
Volts (V): 120
Frequency (Hz): 60
Approval certificates: ETL
Power cord length (in): 51 2/16 "
Power cord length (cm): 130.0
Plug type: 120V-3 prong
Overall appliance dimensions (HxWxD) (in): 30 3/8" - 41 3/8" / x 41 1/3" x 27 1/2"
Overall appliance dimensions (HxWxD) (mm): 772-1052 x 1050 x 700
Product packaging dimensions (HxWxD) (in): 31.49 x 26.77 x 44.09
Adjustable feet:
Height of the chimney (in): 28 3/8" - 39 7/16"
Height of the chimney (mm): 722-1002
Vertical rise height:
Required distance above cooktop/ranges: 30"/30
Net weight (lbs): 87
Net weight (kg): 39.000
Gross weight (lbs): 107
Gross weight (kg): 49.000
Motor location:
Maximum CFM:
Diameter of air duct (in) top: 6
Diameter of air duct (in) back:
Discharge direction:
No-return airflow flap: Yes

2013-07-12