


Updated with dual-level BriteStrip™ LED lighting the Breeze II's modern, clean lines provide a perfect complement to any interior. Equipped with 3-speed electronic controls, 400-CFM blower, convenient dishwasher-safe

aluminum filters and an auto delay-off feature that clears the air and powers down after 5 minutes. Available in black, white, stainless steel and black stainless finishes.



Stainless Steel




Black Stainless




Black




White



Front



Side



Top

MODEL

Black	AK1200BB	AK1236BB
White	AK1200BW	AK1236BW
Black Stainless	AK1200BBS	AK1236BBS
Stainless Steel	AK1200BS	AK1236BS

Size	30" (29-15/16")	36" (35-15/16")
Blower CFM (Min. - Max.)	175 - 400	175 - 400
Sones (Min. - Max.)	1.9 - 4.5	1.9 - 4.5

FEATURES

Controls	Electronic Touch	Electronic Touch
Speed Levels	3	3
Auto Delay-Off	Yes	Yes
Lighting	BriteStrip™ LED x1	BriteStrip™ LED x1
Dual-Level Lighting	Yes	Yes
Filters	Aluminum Mesh x2	Aluminum Mesh x2
Recirculating Option	Yes	Yes

DUCT SPECIFICATIONS

Vertical Internal Blower	3-1/4" x 10"	3-1/4" x 10"
Horizontal Internal Blower	3-1/4" x 10"	3-1/4" x 10"
AC POWER	120V, 60Hz at Max. 0.8A	120V, 60Hz at Max. 0.8A

OPTIONAL ACCESSORIES

Recirculating Kit	0AK11-21001	0AK11-21001
--------------------------	-------------	-------------

MOUNTING HEIGHT RANGE*	24" - 32"	24" - 32"
-------------------------------	-----------	-----------

WARRANTY	3 years parts, 1 year labor	3 years parts, 1 year labor
-----------------	-----------------------------	-----------------------------

*Mounting height refers to distance between top of a 36" tall cooking surface and bottom of hood.