ARC COLLECTION



SURFACEISLAND

No angles here. Just clean, straight lines bisected by a slim plane of transparent gray glass. For minimalism with depth and contrast, dark glass always lends drama to the contemporary stainless steel kitchen. Four halogen lights and a remote control put this island range hood's reflective play of power and light right in your hands.



)		SIZE	NET WIDTH	COLOR
	ASL-E42ASX	42"	42"	Stainless Steel/ Transparent Gray Glass
	ASL-E48ASX	48"	48"	Stainless Steel/ Transparent Gray Glass







ZEP_DS_ARC_Surface_Island_R7.indd 1 10/28/08 7:26:11 PM

ARC COLLECTION

SURFACE ISLAND

MODEL

ASL-E42ASX 42" ASL-E48ASX 48"

FEATURES

Controls Memory Touch Glass
Speed Levels 3
Auto Delay-Off Yes
CleanAir Function Yes
Remote Control Yes, RF
Lighting Halogen, 20W x 4

Tri-Level Lighting Yes
Filters Decorative Mesh x 2

Recirculating Yes
Duct Cover Extension No

*PERFORMANCE

Internal Blower - CBI-290A 290 CFM, 3.2 Sones Max.
Internal Blower - CBI-600A 600 CFM, 6 Sones Max.
In-Line Blower - PBN-1000A 1000 CFM, Sones NA
External Blower - CBE-1000 1000 CFM, Sones NA

AC INPUT 120V - 60Hz

**AC POWER

Hood Only Max. 80W, 0.66 Amps

MOUNTING HEIGHTS

Height from the cooking surface Min. 24" - Max. 36"

HOOD HEIGHTS

Standard

Minimum Ducted 31" Minimum Recirculating 31" Maximum 48"

Extension Kit - Z1C-00SL

Minimum Ducted 46" Minimum Recirculating 46" Maximum 80"

DUCT SPECIFICATIONS

Vertical - Internal 6"


Vertical - In-Line/External 10" to 8"***

Horizontal NA


OPTIONAL ACCESSORIES

Recirculating Kit ZRC-00SL Duct Cover Extension Kit Z1C-00SL

(12' ceiling)



Top (blower housing and ceiling bracket)



24 7//16"

42" or 48" Front

24 7/16"

Zephyr Corporation 2277 Harbor Bay Parkway Alameda, CA 94502

13 1/2'

1.888.880.VENT

www.zephyronline.com nov08.0101

2 11/16"





^{*}Requires purchase of Zephyr blower, sold separately. **AC power listed above is for hood with lights only. See blower specs on our website for more AC power details. ***10" round duct connects to external and in-line blower. Must transition from 10" to 8" before duct passes through ceiling. A 10" to 8" adapter is included with the external and in-line blowers.