

# best Cattura Downdraft Installation Parts Guide

## Accessories for all Applications

ACRD: Remote Up/Down control (optional)

ATTD1: End Cap trim extension to expand width 1". Includes Left & Right trim caps (optional)

AVDKD219: 1-7/8" x 19" rectangular adaptor. Allows connection of rectangular duct to side or rear outlets. This can extend narrow duct as far as necessary until it is possible to connect to AVDKD8 or 10 transitions.

AEDD2: 1-7/8" x 19" x 2' Rectangular duct section to use in conjunction with AVDKD219

643 or 441: 8" or 10" Wall vent

MD6T, MD8T, and MD10T: 6", 8" and 10" make-up air damper.

641FA, 643FA, and 610FA; 6", 8" and 10" Fresh Air inlets for use with make-up air damper

### Note:

- For Range Top applications that are 48" or with grill, recommend Option 3 with EB15.
- For Slide-in Range applications with grill, recommend Option 9 using dual outlet with EB15.

Option	Installation	Parts needed
1	Front / Internal / In Cabinet	D49M (30-36-48)
		PF6 - Internal blower
		ATSKD30,36,48 Gas cooktop seal kit- (If gas cooktop)
		408 – 8" Rd Duct / 432 - 8" Elbow (as required)
		ANKD – Recirculation kit (optional)
2	Front / Internal / Under Floor	D49M (30-36-48)
		PF6 - Internal blower
		ATSKD30,36,48 Gas cooktop seal kit- (If gas cooktop)
		ACVPD8 – Front panel rough-in plate 8" round
		408 – 8" Rd Duct / 432 - 8" Elbow (as required)
		AEWD5 – 5' Ext. cable for electrical panel (use up to two if PF6 blower is mounted more than 4 feet away from downdraft)
3	Front / External or In-Line	D49M (30-36-48)
		EB9, 12, 15, ILB11 – External or in-line blower
		ATSKD30,36,48 Gas cooktop seal kit- (If gas cooktop)
		ACVPD10 - Front panel rough-in plate 10" round
		410 – 10" Rd Duct / 418 - 10" Elbow (as required)
4	Rear / Internal / In Cabinet For Clear Front  For 48" Pro slide in range or applications with grills recommend using Option 9 with dual outlet and EB15.	D49M (30-36-48)
		PF6 - Internal blower
		ATSKD30,36,48 Gas cooktop seal kit- (If gas cooktop)
		ATKD30,36SB – Range trim kit (If slide-in range)
		AVDKD8 – Transition to 8" round
		408 – 8" Rd Duct / 432 - 8" Elbow (as required)
		ANKD – Recirculation kit (optional)

# best Cattura Downdraft Installation Parts Guide

5	Rear / Internal / Under Floor For Clear Front  For 48" Pro slide in range or applications with grills recommend using Option 9 with dual outlet and EB15.	D49M (30-36-48)
		PF6 - Internal blower
		ATSKD30,36,48 Gas cooktop seal kit- (If gas cooktop)
		ATKD30,36SB – Range trim kit (If slide-in range)
		408 – 8" Rd Duct / 432 - 8" Elbow (as required)
		AEWD5 – 5' Ext. cable for electrical panel (use up to two if PF6 blower is mounted more than 4 feet away from downdraft)
6	Rear / External For Clear Front  For 48" Pro slide in range or applications with grills recommend using Option 9 with dual outlet and EB15.	D49M (30-36-48)
		EB15 or ILB11 – External or in-line blower
		ATSKD30,36,48 Gas cooktop seal kit- (If gas cooktop)
		ATKD30,36SB – Range trim kit (If slide-in range)
		AVDKD10 – Transition to 10" round
		410 – 10" Rd Duct / 418 - 10" Elbow (as required)
AEWD5 – 5' Ext. cable for electrical panel (use up to two if panel is mounted more than 2 feet away from downdraft)		
7	Lft or Rht / Internal / In Cabinet For Clear Front  For 48" Pro slide in range or applications with grills recommend using Option 9 with dual outlet and EB15.	D49M (30-36-48)
		PF6 - Internal blower
		ATSKD30,36,48 Gas cooktop seal kit- (If gas cooktop)
		ATKD30,36SB – Range trim kit (If slide-in range)
		AVDKD8 – Transition to 8" round
		408 – 8" Rd Duct / 432 - 8" Elbow (as required)
AEWD5 – 5' Ext. cable for electrical panel (use up to two if: blower is mounted more than 2 feet away from downdraft on the right - if going left you will need to order a minimum of one)		
ANKD – Recirculation kit (optional)		
8	Lft or Rht / Internal / Under Floor For Clear Front  For 48" Pro slide in range or applications with grills recommend using Option 9 with dual outlet and EB15.	D49M (30-36-48)
		PF6 - Internal blower
		ATSKD30,36,48 Gas cooktop seal kit- (If gas cooktop)
		ATKD30,36SB – Range trim kit (If slide-in range)
		AVDKD8 – Transition to 8" round
		408 – 8" Rd Duct / 432 - 8" Elbow (as required)
AEWD5 – 5' Ext. cable for electrical panel (use up to two if PF6 blower is mounted more than 4 feet away from downdraft)		
9	Lft or Rht / External or In-Line For Clear Front  For 48" Pro slide in range or applications with grills recommend using dual outlet and EB15.	D49M (30-36-48)
		EB12, 15, ILB11 – External or in-line blower
		ATSKD30,36,48 Gas cooktop seal kit- (If gas cooktop)
		ATKD30,36,48SB – Range trim kit (If slide-in range)
		AVDKD10 – Transition to 10" round (for single outlet)
		2 X AVDKD8 – Transition to 8" round (for dual outlet)
ATKD8810 – "Y" Transition Two 8" in to one 10" (for dual outlet)		
AEWD5 – 5' Ext. cable for electrical panel (use up to two if panel is mounted more than 2 feet away from downdraft)		