



**Accessories for all Applications**

- ACRD/ACRDBLS: **Remote Up/Down control** Stainless Steel/ Black Stainless (optional).
- AEWD5: **5’ Ext. cable for electrical panel**. Only required if electrical panel is more than two feet away from downdraft. Use up to 2 extension cables connected together.
- ATTD1/ATTD1BLS: **End Cap trim extension to expand 1” overall trim width**. Includes Left & Right trim caps Stainless Steel/ Black Stainless (optional).
- ATSKD30, 36, 48: **Gas cooktop seal kit**. Use if a gas cooktop is installed.
- MD6T, MD8T, and MD10T: **6”, 8” and 10” make-up air damper**.
- 641FA, 643FA, and 610FA; **6”, 8” and 10” Fresh Air inlets** for use with make-up air damper  
**Note:**
  - For Range Top applications that are 48” or with grill, recommend Option 3 with EB15.
  - For Slide-in Range applications with grill, recommend Option 9 using dual outlet with EB15.

Option	FRONT Installation	Parts needed
1	Front / Internal / In Cabinet Ref. Page 8 spec sheet	D49M (30-36-48)
		PF6 - Internal blower
		408 – 8” Rd Duct / 432 - 8” Elbow (as required) /643 - 8” Rd wall cap
		ANKD – Recirculation kit (optional)
2	Front / Internal / Under Floor Ref. Page 9 spec sheet	D49M (30-36-48)
		PF6 - Internal blower
		ACVPD8 – Front panel rough-in plate 8” round
		408 – 8” Rd Duct / 432 - 8” Elbow (as required) /643 8” Rd wall cap
3	Front / Exterior or In-Line Ref. Page 13 spec sheet	D49M (30-36-48)
		EB9, EB12, EB15, ILB11 – Exterior or in-line blower
		ACVPD10 - Front panel rough-in plate 10” round
		410 – 10” Rd Duct / 418 - 10” Elbow (as required) / 441 - 10” Rd wall cap (if ILB11 in-line blower is used)

Option	REAR Installation	Parts needed
4	Rear / Internal / In Cabinet For Clear Front Ref. Page 11 spec sheet	D49M (30-36-48)
		PF6 - Internal blower
		ATKD30SB/30BLS, ATKD36SB/36BLS, ATKD48SB – Range trim kit SS or Blk SS (If slide-in range)
		AVDKD219 (1-7/8" x 19" rectangular adaptor) AEED2 (optional rectangular duct) AVDKD8 – Transition to 8" round
		408 – 8" Rd Duct / 432 - 8" Elbow (as required)
		ANKD – Recirculation kit (optional)
5	Rear / Internal / Under Floor For Clear Front Ref. Page 11 spec sheet	D49M (30-36-48)
		PF6 - Internal blower
		ATKD30SB/30BLS, ATKD36SB/36BLS, ATKD48SB – Range trim kit SS or Blk SS (If slide-in range)
		AVDKD219 (1-7/8" x 19" rectangular adaptor) AEED2 (optional rectangular duct) AVDKD8 – Transition to 8" round
		408 – 8" Rd Duct / 432 - 8" Elbow (as required) / 643 - 8" Rd. wall cap
6	Rear / exterior or in-line for Clear Front Ref. Page 14 spec sheet  For 48" slide in range or applications with grill recommend using Option 9 with dual outlet and EB15.	D49M (30-36-48)
		EB9, EB12, EB15, ILB11 – Exterior or in-line blower
		ATKD30SB/30BLS, ATKD36SB/36BLS, ATKD48SB – Range trim kit SS or Blk SS (If slide-in range)
		AVDKD219 (1-7/8" x 19" rectangular adaptor) AEED2 (optional rectangular duct) AVDKD10 – Transition to 10" round
		410 – 10" Rd Duct / 418 - 10" Elbow (as required) / 441 - 10" Rd wall cap
Option	LEFT -RIGHT Installation	Parts needed
7	Left or Right / Internal / In Cabinet for Clear Front Ref. Page 10 spec sheet	D49M (30-36-48)
		PF6 - Internal blower
		ATKD30SB/30BLS, ATKD36SB/36BLS, ATKD48SB – Range trim kit SS or Blk SS (If slide-in range)
		AVDKD219 (1-7/8" x 19" rectangular adaptor) AEED2 (optional rectangular duct) AVDKD8 – Transition to 8" round
		408 – 8" Rd Duct / 432 - 8" Elbow (as required) 643 - 8" Rd. wall cap
		ANKD – Recirculation kit (optional)



# Cattura Downdraft Installation Parts Guide (Revision February 2020)

8	<b>Left or Right</b> / Internal / Under Floor For Clear Front Ref. Page 10 spec sheet	D49M (30-36-48)
		PF6 - Internal blower
		ATKD30SB/30BLS, ATKD36SB/36BLS, ATKD48SB – Range trim kit SS or Blk SS (If slide-in range)
		AVDKD219 (1-7/8" x 19" rectangular adaptor) AEED2 (optional rectangular duct) AVDKD8 – Transition to 8" round
		408 – 8" Rd Duct / 432 - 8" Elbow (as required) 643 8" Rd. wall cap
9	<b>Left or Right</b> / Exterior or In-Line For Clear Front Ref. Page 14 spec sheet  For 48" Pro slide in range or applications with grills recommend using dual outlet and EB15.	D49M (30-36-48)
		EB9, EB12, EB15, ILB11 – Exterior or in-line blower
		ATKD30SB/30BLS, ATKD36SB/36BLS, ATKD48SB – Range trim kit SS or Blk SS (If slide-in range)
		AVDKD219 (1-7/8" x 19" rectangular adaptor) AEED2 (optional rectangular duct) AVDKD10 – Transition to 10" round (for single outlet)
		2 X AVDKD8 – Transition to 8" round (for dual outlet)
		ATKD8810 – "Y" Transition Two 8" in to one 10" (for dual outlet), 441 10" Rd wall cap
<b>Option</b>	<b>BELOW Installation</b>	<b>Parts needed</b>
10	<b>Below vent</b> / Internal / Under Floor Ref. Page 12 spec sheet	D49M (30-36-48)
		PF6 - Internal blower
		ATKD30SB/30BLS, ATKD36SB/36BLS, ATKD48SB – Range trim kit SS or Blk SS (If slide-in range)
		AVDKD8 – Transition to 8" round
		408 – 8" Rd Duct / 432 - 8" Elbow (as required) 643 8" Rd. wall cap
		ANKD – Recirculation kit (optional)
11	<b>Below vent</b> / Exterior or In-Line Ref. Page 15 spec sheet  For 48" Pro slide in range or applications with grills recommend using dual outlet and EB15.	D49M (30-36-48)
		EB9, EB12, EB15, ILB11 – Exterior or in-line blower
		ATKD30SB/30BLS, ATKD36SB/36BLS, ATKD48SB – Range trim kit SS or Blk SS (If slide-in range)
		AVDKD10 – Transition to 10" round
		410 – 10" Rd Duct / 418 - 10" Elbow (as required) / 441 10" Rd wall cap