



# **Features and Benefits**

## **Key Features**

- 600 CFM Blower Included
- 2 Halogen Lights
- · Seven-segment Digital Display
- Recirculation Option Available
- · Adjustable Chimney

#### Design

- · Slim Silhouette Canopy
- 2 Halogen Lights
- · Seven-segment Digital Display
- · Brushed Stainless Steel Finish

#### **Performance**

- 600 CFM Blower Included
- Four Power Levels
- Whisper-quiet at 53 dBA
- Quickly and Quietly Clears the Air of Smoke and Odor

### Convenience

- Dishwasher-safe Mesh Filters
- Recirculation Option Available
- · Adjustable Chimney

Notes: All height, width and depth dimensions are shown in inches. \*Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be foundin a ccompanying product literature or you may contact your account manager for further details.

For more information on our entire line of products, go to boschappliances.com or call 1-800-944-2904.

Copyright ©2013 BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.

Litho Date: 04/2013



Features	
Operating Mode	Convertable: Ducted /
	Recirculating
Number of speed settings	3-stage
Delay Shut off modes	
Silence level (dBA)	
Required accessories	Recirc Kit
Optional accessories	DHZ9400UC, DRZ94UC
Number of lights	2
Type of lamps used	Halogen
Total power of the lamps (W)	40
Grease filter material	aluminium
Grease filter type	Multilayer cassette
Clean filter reminders	
Technical Specification	
UPC code	825225854142
Material	Stainless steel
Watts (W)	580
Current (A)	
Volts (V)	110
Frequency (Hz)	60
Approval certificates	ETL
Power cord length (in)	51 2/16 "
Plug type	120V-3 prong
Overall appliance dimensions (HxWxD) (in)	26 7/8 " - 42 5/8 " / x 35
	3/8 " x 19 5/8 "
Product packaging dimensions (HxWxD) (in)	28.34 x 39.76 x 25.98
Height of the chimney (in)	24 1/8 " - 43 5/8 "
Vertical rise height	
Required distance above cooktop/ranges	30 "/30 "
Net weight (lbs)	49
Gross weight (lbs)	66
Adjustable feet	
Motor location	
Maximum CFM	600
Diameter of air duct (in) top	6
Diameter of air duct (in) back	
Discharge direction	
No-return airflow flap	No

Notes: All height, width and depth dimensions are shown in inches. \*Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be foundin a ccompanying product literature or you may contact your account manager for further details.