

Ventilation

HCB50651UC 30" Box Canopy Chimney Hood 500 Series - Stainless Steel



Wall Mounted Chimney Hoods Add Style and Sophistication to the Kitchen and Gives You Greater Freedom in Your Kitchen Planning

- Touch Controls with LCD Display
- 600 CFM Centrifugal Integrated Blower Included
- Four Speed Touch Controls with LCD Display
- Dishwasher Safe Filters with Stainless Steel Covers
- Converts to Recirculation Mode with Accessory Kit (Separate Purchase Required)

Technical Data

Operating Mode :	Convertible: Ducted / Recirculating
Number of speed settings :	4-stage
Optional accessories :	HCBEXT5UC, HCIFILTUC, HCREC5UC
Number of lights :	2
Type of lamps used :	Halogen
Total power of the lamps (W) :	40
Grease filter material :	Washable stainless steel
Grease filter type :	Multilayer cassette
UPC code :	825225909040
Material :	Stainless steel
Watts (W) :	530
Volts (V) :	110
Frequency (Hz) :	60
Approval certificates :	CUL, UL
Power cord length (cm) :	0
Plug type :	no plug
Overall appliance dimensions (HxWxD) (in) :	27 1/16" - 42 1/8 " / 27 1/16" - 45 13/16" x 30 " x 19 11/16 "
Overall appliance dimensions (HxWxD) (mm) :	687-1164 x 762 x 500
Product packaging dimensions (HxWxD) (in) :	26.37 x 34.49 x 17.99
Height of the chimney (in) :	25 1/2" - 40 9/16"/25 3/8" - 44 1/4"
Height of the chimney (mm) :	647-1031/647-1124
Required distance above cooktop/ranges :	24 "/27 "
Net weight (lbs) :	52
Net weight (kg) :	24.0
Gross weight (lbs) :	58
Gross weight (kg) :	26.0
Motor location :	Integrated motor in hood chimney
Diameter of air duct (in) top :	8
Discharge direction :	vertical
No-return airflow flap :	Yes

Optional accessories

HCBEXT5UC : Box Chimney Extension
 HCIFILTUC : Wall/Island Chimney Charcoal Filter
 HCREC5UC : Wall Chimney Recirc. Kit

Ventilation

HCB50651UC

30" Box Canopy Chimney Hood 500 Series - Stainless Steel

Wall Mounted Chimney Hoods Add Style and Sophistication to the Kitchen and Gives You Greater Freedom in Your Kitchen Planning

Design

- Duct Extension Accessory Kit Available for 9' to 12' Ceilings

Performance

- 2 Halogen Lights - 12 Volt, 20 Watt max., G-4 Base
- 8" round duct at discharge.

Efficiency

- Blower will automatically turn on at high speed if excessive heat is sensed in the control area.
- Absorb odors with charcoal replacement filters.

Convenience

- Convenient timer built into control from 1-60 minutes.
- Signal on LCD display will illuminate as a reminder to check filters for cleaning.
- Audible tone when select controls are pressed.

Ventilation

HCB50651UC

30" Box Canopy Chimney Hood 500 Series - Stainless Steel

