

## Ventilation

### HIB82651UC 42" Box Canopy Island Hood Benchmark™ Series - Stainless Steel



### Stylish Island Hoods Perfectly Complement Island Cooking Installations

- Touch Controls with LCD Display
- 600 CFM Centrifugal Integrated Blower Included
- Four Speed Touch Controls with LCD Display
- Dishwasher Safe Filters with Stainless Steel Covers
- Converts to Recirculation Mode with Accessory Kit (Separate Purchase Required)

---

#### Technical Data

Operating Mode :	Convertible: Ducted / Recirculating
Number of speed settings :	4-stage
Optional accessories :	HCIEXT5UC, HCIFILTUC, HIREC5UC
Number of lights :	4
Type of lamps used :	Halogen
Total power of the lamps (W) :	40
Grease filter material :	Washable stainless steel
Grease filter type :	Multilayer cassette
UPC code :	825225909071
Material :	Stainless steel
Watts (W) :	610
Volts (V) :	120
Frequency (Hz) :	60
Approval certificates :	CUL, UL
Power cord length (cm) :	0
Plug type :	no plug
Overall appliance dimensions (HxWxD) (in) :	
	29 13/16" - 45 5/16" / 29 13/16" - 50 5/16" x 42 1/16" x 27"
Overall appliance dimensions (HxWxD) (mm) :	
	757 - 1277 x 1069 x 685
Product packaging dimensions (HxWxD) (in) :	
	23.25 x 46.99 x 33.49
Height of the chimney (in) :	
	27 7/16" - 42 7/8"/27 7/16" - 47 7/8"
Height of the chimney (mm) :	697-1090/697-1217
Required distance above cooktop/ranges :	24"/27"
Net weight (lbs) :	101
Net weight (kg) :	46.0
Gross weight (lbs) :	113
Gross weight (kg) :	51.0
Motor location :	Integrated motor in hood chimney
Diameter of air duct (in) top :	8
No-return airflow flap :	Yes

---

#### Optional accessories

- HCIEXT5UC : Island Chimney Extension
- HCIFILTUC : Wall/Island Chimney Charcoal Filter
- HIREC5UC : Island Chimney Recirc. Kit

## Ventilation

### HIB82651UC

#### 42" Box Canopy Island Hood Benchmark™ Series - Stainless Steel

#### Stylish Island Hoods Perfectly Complement Island Cooking Installations

---

##### Design

- Duct Extension Accessory Kit Available for 9' to 12' Ceilings

##### Performance

- 4 Halogen Lights - 12 Volt, 20 Watt max., G-4 Base
- 8" round duct at discharge.

##### Efficiency

- Blower will automatically turn on at high speed if excessive heat is sensed in the control area.
- Absorb odors with charcoal replacement filters.

##### Convenience

- Convenient timer built into control from 1-60 minutes.
- Signal on LCD display will illuminate as a reminder to check filters for cleaning.
- Audible tone when select controls are pressed.

# Ventilation

## HIB82651UC 42" Box Canopy Island Hood Benchmark™ Series - Stainless Steel

