BRSAN

SPECIFICATION SHEET

CENTRAL VACUUM POWER UNIT MODEL VX12000C



Designed for larger homes up to 12,000 square feet (1,114.8 m2) or consumers looking for the ultimate in features and air performance. This power unit has two specially designed 2-stage motors that delivers a whopping 1040 air watts of power. It's the most powerful in its class. The unique oval shape offers space saving advantages and efficient cyclonic filtration.

FEATURES

- Internal sound suppression system makes it the quietest
 power unit in its class
- Progressive full lights let the homeowner know when it is time to empty the debris pail
- · Easy access door for cyclonic filter maintenance
- Oversized debris pail handles made for quick and easy pail removal
- Large 7 U.S. gallons (26.5 litres) debris pail. Typically needs emptying only every 6 months!
- Dual vacuum air intakes allowing the connection of the tubing line from the right side, left side or both
- Six foot (1.8 m) power cord
- cULus Listed

Limited Lifetime Warranty

SPECIFICATIONS

Motors	.Two 2-Stage Universal bypass
Horsepower	.4.8 @ Full open orifice
Ampere	.13.5
Voltage	.240 VAC
Airflow at 2" (50.8 mm) opening	230 CFM (108.5 L/s)
Water Lift	.130" (3.3 m)
Air Watts	.1040
Switch on Power Unit	Yes
Utility Valve with Power Unit	Yes
Recommended Circuit	.20 Amps
Primary Filtration	Self-cleaning permanent HEPA filter protected with non-stick coating
Capacity	.7 U.S. Gallons (26.5 Litres)
Secondary Filtration	.Screen
cULus Listed	.Yes
Housing	.Corrosion resistant Engineered thermoplastic
Power Unit Dimensions (292 mm D	.11.5" D x 17.5" W x 39" H x 445 mm W x 991 mm H)



 Broan-NuTone Canada Inc.; Mississauga, Ontario
 www.broan.ca
 877-896-1119

 REFERENCE
 QTY.
 REMARKS
 Project

 Location
 Architect
 Engineer

 Contractor
 Submitted by
 Date

PRODUCT SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

VX12000Cd100602