

# CENTRAL VACUUM POWER UNIT MODEL VX6000C



Designed for homes up to 6,000 square feet (557.4 m<sup>2</sup>) or consumers looking to step up in features. This power unit is specially designed with a 2-stage motor and delivers 550 air watts of power. It's the most powerful power unit in its class. The unique oval shape offers space saving advantages and efficient cyclonic filtration.

### FEATURES

- Internal sound suppression system makes it the quietest power unit in its class
- Progressive full lights let the homeowner know when it is time to empty the debris pail
- Easy access door for cyclonic filter maintenance
- Oversized debris pail handles made for quick and easy pail removal
- Large 7 U.S. gallons (26.5 litres) debris pail. Typically needs emptying only every 6 months!
- Dual vacuum air intakes allowing the connection of the tubing line from the right side, left side or both
- Six foot (1.8 m) power cord
- cULus Listed

Limited Lifetime Warranty

### SPECIFICATIONS

Motor	.2-Stage Universal bypass
Horsepower	.2.4 @ Full open orifice
Ampere	.12.5
Voltage	.120 VAC
Airflow at 2" (50.8 mm) opening	.135 CFM (63.7 L/s)
Water Lift	.130" (3.3 m)
Air Watts	.550
Switch on Power Unit	.Yes
Utility Valve with Power Unit	.Yes
Recommended Circuit	.15 Amps
Primary Filtration	.Self-cleaning permanent HEPA filter protected with non-stick coating
Capacity	.7 U.S. Gallons (26.5 Litres)
Secondary Filtration	.Screen
cULus Listed	.Yes
Housing	.Corrosion resistant Engineered thermoplastic
Power Unit Dimensions	.11.5" D x 17.5" W x 39" H (292 mm D x 445 mm W x 991 mm H)



Broan-NuTone Canada Inc.; Mississauga, Ontario [www.broan.ca](http://www.broan.ca) 877-896-1119

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by Date