

Under-Cabinet

GLACIER

The clean, contemporary shape of Glacier complements any kitchen design. Impressive LED lighting and superior smoke and odor removal are a mere introduction to everything this hood has to offer. The LED modules included with this hood are the latest in LED cooktop illumination technology specially designed to operate in the elevated temperatures of cooking - offering bright lighting and lasting up to 25 times as long as a standard bulb and greater reliability than typical replacement LED bulbs.

SIZE	WHITE BLAC		SLATE	STAINLESS		GREASE FILTERS (replacement)		NON-DUCTED FILTERS
30 in.	BCSEK130W	W BCSEK130E	BL BCSEK1305	L* BCSEK130SS HPFA130 (T) (Type C1)	HPF30 (Type Xc)	
	RMANCE							* Not available in
		· · · · · · · · · · · · · · · · · · ·		Sones		CFM		Canada.
Duct Orientation		Size	Damper	Normal	High	Normal	High	
Vertical - Rectangular		3¼ in. x 10 in.	Included	1.5	5.0	140	230	
Horizontal - Rectangular		r 3¼ in. x 10 in.	Included	1.5	5.0	110	210	
Round -	Vertical	7 in.	Sold Separately	1.5	5.0	150	250	
FEATUR	RES							
Control [·]	1	2-speed Rocker					1 1-	
		סר						
		no						
Heat Se	entry™	no				The line	In the Party of the	0
ADA Ca		yes			-			
Lighting		1-level ENERGY STAR® LED (included)			78.3			
Grease	Filters	Open Mesh (Qty.	2)					
		EZ1 Bracket			al hile			
ENERGY STAR [®] yes (no if installed non-ducted)			-				00	
Recircul	1	Non-ducted filters	sold separately				The state of the s	TUR
AC INP							A DESCRIPTION	
	60 Hz - 0.65 Al							11.11
	NAL ACCESSO	RIES		88	CONSCRIPTION OF	- 64	0	00
		BP87Q						and the second s
		MD6TU, MD8TU	and MD10TU	_			TRACK DATE	
	TING HEIGHT					-		
		oktop to bottom o	hood				Terrer Contractor	
LIMITE	D WARRANTY						2000	
1-year								
	LED modules o	niy) ' for full warranty t	evt)					X om
	DOOR USE OI				~~	Q.	$\langle \rangle$	
	DOOR USE OI				~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		/ Xo	
0.5			 Vertical High Speed, 7-in. round 		₹ ²		\sim	3 32 6
0.4			 Vertical High Speed, 		\langle		$\checkmark \not \parallel$	8
0.2			with 3¼ in. x 10 in. dampe	er 🤇	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	$\langle \mathbf{\hat{k}} \rangle$		
			 Horizontal High Speed, with 3¼ in. x 10 in. damped 					5-
0.2			wian 5/4 m. X 10 m. uampt			101	5 1	/
0.1					195		298	Dimensions
					- <u>8</u> _	$\langle \rangle$		shown in inche
0	50 100	150 200	250 300	350		\checkmark		
-		Airflow (cfm)						
R 🔺		ERTIFIED RATINGS comply			MODE	L BCSEK1	30SL ALI	
210	by the Home	ologies and procedures pre- Ventilating Institute, for off-	the-shelf	ergy				
HV		they are avaialable to consults is rated at 0.1 in. static pre		RGY STAR				c(VL)us
ERTI	FIED on tests conc	lucted in AMCA's state-of- ones are a measure of hum	he-art test					
		ed on laboratory measuren						990457

926 West State Street, Hartford, WI 53027

550 Lemire Blvd., Drummondville, QC Canada J2C 7W9

1 800-558-1711

1 877-896-1119

www.broan.com

www.broan.ca

SPECIFICATION SHEET GLACIER - BCSEK1 SERIES

Broan-NuTone LLC

Venmar Ventilation ULC