Perfect for the light cooking habits, the BU3 range hood models provide the quality you expect and the value you demand.

SIZE	WHITE	WHITE WITH BLACK CONTROL	STAINLESS	GREASE FILTER (replacement)	CHARCOAL FILTER
24 in.	BU324WW	-	BU324SS	BP29	41F
30 in.	BU330WW	BU330WH	BU330SS	BP29	41F

PERFORMANCE						
Duct Orientation	Size	Damper	Sones on high speed	CFM on high speed		
Vertical - Rectangular	3¼ in. x 10 in.	Included	7.5	190		
Horizontal - Rectangular	3¼ in. x 10 in.	Included	7.5	190		

FEATURES				
Control type	Rotary switch, variable speed			
Delay off	no			
Filter Clean Reminder	no			
Heat Sentry™	no			
Lighting	2-level 75-watt bulb (not included)			
Grease Filter	Aluminum (Qty. 1)			
ENERGY STAR®	no			
Recirculation	Charcoal filter sold separately			
AC INPUT				
120 V, 60 Hz - 2.5 AMPS				
OPTIONAL ACCESSORIES				

OPTIONAL ACCESSORIES				
3¼ in. x 10 in. to 6-in. Round Duct Transition	411			
7-in. Round Damper	BP87Q			
7-in. Round Adapter Plate	SR680508			

MOUNTING HEIGHT


18 in. to 24 in. from cooktop to bottom of hood

LIMITED WARRANTY


1-year

(See installation manual for full warranty text.)

FOR INDOOR USE ONLY









SPECIFICATION SHEET



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.