

## SPECIFICATION SHEET VJ71030SS

## **SPECIFICATIONS** -**DIMENSIONS** -MODEL VJ71030SS — 10¾" → 10Å" → 10Å 12"-VOLTS 120 VAC Hz 60 AMPS 3.3 CFM (Low SPEED) 190 CFM (HIGH SPEED) 450 221/2" - 421/2" SONES (LOW SPEED) 2.5 201/3" SONES (HIGH SPEED) 8.5 TOTAL HOOD 400 W POWER CONSUMPTION • • 🗖 ۰. 6" ROUND DUCTING SIZE 291/2" 19%" JC TYPE, 12 V, HK0139A **2 HALOGEN BULBS** 20 W MAX., G-4 BASE WARRANTY 1 YEAR AIR FLOW PERFORMANCE -**REQUIREMENTS & STANDARDS** 2.5 Complies with UL 507 requirements Vertical Discharge Static Pressure (in. of water) 2.0 1.5 HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to 1.0 consumers. Product performance is rated at 0.1 in. (2.54 mm) static pressure, based on tests conducted in a state-of-the-art test CERTIFIED 0.5 laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements. 0 100 150 200 250 300 350 400 450 500 0 50 Fan Flow Rate (CFM) HG0015A www.venmar.ca Venmar Ventilation Inc., 550 Lemire Blvd., Drummondville, Québec, Canada J2C 7W9 - Tel.: 1-800-567-3855 Fax: 1-800-567-1715 PROJECT REMARKS LOCATION MODEL NO. QTY. SUBMITTED BY DATE

PRODUCT SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.