

36-INCHPRO DUAL-FUEL STEAM RANGE

DOP36M86D | MODERNIST COLLECTION



AVAILABLE MODELS

DOP36M86DLS	Stainless Steel, Natural Gas
DOP36M86DPS	Stainless Steel, Liquid Propane
DOP36M86DHS	Stainless Steel, Natural Gas/High Altitude
DOP36M86DAS	Stainless Steel, Liquid Propane/High Altitude
DOP36M86DLM	Graphite Stainless Steel, Natural Gas
DOP36M86DPM	Graphite Stainless Steel, Liquid Propane
DOP36M86DHM	Graphite Stainless Steel, Natural Gas/High Altitude
DOP36M86DAM	Graphite Stainless Steel, Liquid Propane/High Altitude

FEATURES & BENEFITS

- → Exclusive Four-Part Dual Pure Convection heat, air, baffle, and filter to precisely distribute heat for superior cooking results.
- → Steam Assist and Convection Oven the power of steam and convection cooking in one.
- → Large oven capacity 4.8 cu. ft.
- → 6 Sealed Brass Burners.
- Powerful 22K BTU and true simmer burners.
- → Illumina™ Knobs and Ambient Light.
- → 7" LCD Control Panel.
- → Dacor iQ Kitchen app with integrated Wif-Fi to control and monitor remotely.
- → Auto connect to hood.

ACCESSORIES	
ACCESSORIES (INCLUDED)	
GLIDERACK™	2
STANDARD RACKS	1
TEMPERATURE PROBE	1
WOK RING	1
CONVECTION FILTER	2
BRASS/BLACK BURNER CAPS	YES
ACCESSORIES (OPTIONAL)	
COOKIE SHEETS (SET OF 3)	SKU - ACSM303
GRIDDLE	SKU - AMG36
GENERAL PROPERTIES	
OVEN CAPACITY (CUBIC FEET)	4.8
COOKING MODES	BAKE - BROIL - CONVECTION BAKE - CONVECTION ROAST - CONVECTION BROIL - FOUR PART PURE CONVECTION - PURE CONVECTION SEAR - STEAM ASSIST
OVEN PERFORMANCE	
BAKE ELEMENT	3,000W - 8 PASS
BROIL ELEMENT	4,400W - 10 PASS
CONVECTION ELEMENT	1,300W (EACH - 2,600W TOTAL)
STEAM HEATER	500W
BURNER PERFORMANCE	
TOTAL NUMBER OF COOKTOP BURNERS	6
RIGHT FRONT (BTU)	22,000 DUAL (SIMMER)
RIGHT REAR (BTU)	9,000 STACK DUAL (SIMMER)
CENTER FRONT (BTU)	16,000 STACK DUAL (SIMMER)
CENTER REAR (BTU)	16,000 STACK DUAL (SIMMER)
LEFT FRONT (BTU)	18,000 DUAL (SIMMER)
LEFT REAR (BTU)	16,000 DUAL (SIMMER)
SEALED BURNERS	YES
PERMA-FLAME™ (AUTO RE-IGNITION)	YES
CONTROL FEATURES	
INFOCENTER™ DISPLAY	YES
NUMBER OF KNOBS	6+1 LAMP KNOBS
CONTROL METHOD	7" POP-UP LCD
WIFI	YES
BLUETOOTH (HOOD CONNECTION)	
	YES
ILLULMINA™ BURNER KNOBS	YES / WHITE
ILLULMINA™ BURNER KNOBS	YES / WHITE
ILLULMINA™ BURNER KNOBS HIGHLIGHTING COLOR	YES / WHITE WHITE
ILLULMINA™ BURNER KNOBS HIGHLIGHTING COLOR AMBIENTLIGHTING	YES / WHITE WHITE YES (DIMMING)
ILLULMINA™ BURNER KNOBS HIGHLIGHTING COLOR AMBIENTLIGHTING CLOCK	YES / WHITE WHITE YES (DIMMING) YES
ILLULMINA™ BURNER KNOBS HIGHLIGHTING COLOR AMBIENTLIGHTING CLOCK DELAY START	YES / WHITE WHITE YES (DIMMING) YES YES
ILLULMINA™ BURNER KNOBS HIGHLIGHTING COLOR AMBIENTLIGHTING CLOCK DELAY START KITCHEN TIMER	YES / WHITE WHITE YES (DIMMING) YES YES YES
ILLULMINA™ BURNER KNOBS HIGHLIGHTING COLOR AMBIENTLIGHTING CLOCK DELAY START KITCHEN TIMER TIME OF DAY (12 HR/24 HR)	YES / WHITE WHITE YES (DIMMING) YES YES YES YES
ILLULMINA™ BURNER KNOBS HIGHLIGHTING COLOR AMBIENTLIGHTING CLOCK DELAY START KITCHEN TIMER TIME OF DAY (12 HR/24 HR) TEMPERATURE (F / C)	YES / WHITE WHITE YES (DIMMING) YES YES YES YES YES YES




ADDITIONAL FEATURE	S
CLEANING TYPE	SELF CLEAN & GREENCLEAN
TYPE OF GRATE	CONTINUOUS CAST IRON
CAVITY	BLACK ENAMEL COATING
rack positions	6
CONVECTION TYPE	FOUR PART DUAL PURE CONVECTION WITH FILTER
LIGHTING	BRIGHTVUE™ - LED + HALOGEN
ADDITIONAL MODES	
KEEP WARM	YES
PROOF (LOWER TEMP)	YES
PROOF	YES
STONE MODE	YES
DEHYDRATE	YES
GOURMET COOK	YES
SABBATH	YES
OPTIONAL MODES	
TEMPERATURE PROBE	YES
INSTANTHEAT (NO PREHEAT)	YES WITH CONVECTION ROAST / CONVECTION BAKE

TECHNICAL DETAILS	
CIRCUIT BREAKER (A)	40
VOLTS (V)	240 / 208
FREQUENCY (HZ)	60
ENERGY SOURCE	GAS AND ELECTRIC
GAS TYPE	NATURAL GAS NATURAL GAS (HIGH ALTITUDE) LIQUID PROPANE LIQUID PROPANE (HIGH ALTITU
DIMENSIONS & WEIGHT	
APPLIANCE DIMENSIONS (H X W X D) (IN.)	36 1/8" X 35 7/8" X 27 1/2"
REQUIRED CUTOUT SIZE (W X D) (IN.)	36" X 24"
WARRANTY	
LIMITED, PARTS AND LABOR	2 YEAR



36-INCH 6-BURNER DUAL-FUEL STEAM RANGE

APPLIANCE DIMENSIONS



36"	
A (WIDTH)	35 7/8" (121.6CM)
B (DEPTH)	27 1/2" (95.25CM)
C (HEIGHT)	36 1/8" (91.8CM)

INSTALLATION CUTOUT DIMENSIONS

36"	
A (WIDTH)	36" (91.4CM) MINIMUM 42" (106.7CM) RECOMMENDED
B (WIDTH)	36" (91.4CM)

