



42" WALL CHIMNEY HOODS

DHW421



GENERAL PROPERTIES

FINISH: STAINLESS STEEL

OPTIONAL ACCESSORIES

RECIRCULATION KIT: AVDH1

NUMBER OF MOTORS

(1) SINGLE BLOWER: 600 CFM

TECHNICAL INFORMATION

CIRCUIT REQUIREMENTS: 120VAC, 15AMP, GROUNDED DEDICATED, 3-WIRE CIRCUIT

TOTAL CONNECTED LOAD: 120VAC/60HZ

MAX CURRENT DRAW: 3.6 AMPS

SHIPPING WEIGHT: 71 LBS

PRODUCT DIMENSIONS


WALL DIMENSIONS (H X W X D) (IN.): 30 1/4"-42" X 42" X 24"

FEATURES & BENEFITS

- 8" diameter exhaust. Can accommodate up to a 10" duct.
- Squirrel cage style blower. 4 blower speeds.
- Auto off setting after 4 hours.
- Blue illuminated electronic control panel.
- 10 minute Timer (motor runs for 10 minutes and then automatically shuts off).
- 20 watt halogen lights (can be used w/ 10, 20, or 30w bulbs)
- Easy-to-clean Baffle Filter System, dishwasher safe.
- Hood can be installed to exhaust through the ceiling or rear wall

DHW MODEL

Tolerances: -1/16" (-1.6 mm), -0 unless otherwise stated



**Warranty: Limited, parts and labor for one year