















|                           |  |  |  |    |
|---------------------------|---|---|--|---|
| Model Name                | Asti  | Palermo   | Trento   | Arezzo  |
| Model Numbers             | EAS422SS<br>EAS428S1  | EPR628S1  | ETR134S1   | EAR628S4<br>EAR134S4<br>EAR140S4<br>EAR146S4  |
| Dimensions                | 22¼" W x 10¾" D x 9½" H<br>28¼" W x 10¾" D x 9½" H                                | 28¼" W x 10¾" D x 9¼" H   | 34½" W x 18" D x 11½" H  | 28½" W x 22" D x 11½" H<br>34½" W x 22" D x 11½" H<br>40½" W x 22" D x 11½" H<br>46½" W x 22" D x 11½" H  |
| Blower Type               | 400 CFM (3-speed)   | 600 CFM (3-speed)   | 1200 CFM (4-speed)   | 600 CFM (4-speed) - 28"<br>1200 CFM (4-speed) - 34",<br>40" & 46"   |
| Blower Performance        | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 400 CFM                          | Speed 1, 190 CFM<br>Speed 1, 350 CFM<br>Speed 1, 600 CFM                          | Speed 1, 380 CFM<br>Speed 2, 660 CFM<br>Speed 3, 950 CFM<br>Speed 4, 1200 CFM      | (28") - Speed 1, 90 CFM<br>Speed 2, 330 CFM<br>Speed 3, 490 CFM<br>(34", 40", 46") -<br>Speed 1, 380 CFM<br>Speed 2, 660 CFM<br>Speed 3, 950 CFM<br>Speed 4, 1200 CFM |
| CFM Reduction             | Yes / KITO2748  | No  | No   | No  |
| Noise (sones)             | Min: 1.5, Max: 5.9  | Min: 2.1, Max: 6.0  | Min: 2.05, Max: 7.5  | Min: 2.0, Max: 9.6 (28")<br>Min: 2.05, Max: 7.5 (34", 40", 46")   |
| Finish                    | Stainless Steel   | Stainless Steel   | Stainless Steel  | Stainless Steel   |
| Controls                  | Backlit Electronic Push Button  | Stainless Steel Push Button   | Fully Retractable Rotating Knobs w/Blue Backlighting                               | Fully Retractable Rotating Knobs w/Blue Backlighting  |
| Illumination              | 2 LED, 2.1 watts  | 2 Premium LED, 2.5 watts  | 2 Consumer Replaceable LED, 7.5 watts  | 2 LED, 7.5 watts (28", 34")<br>4 LED, 7.5 watts (40", 46")<br><small>*Consumer Replaceable</small>  |
| Filter Type               | Dishwasher-Safe Anodized Aluminum Mesh (1w/22", 2w/28")                           | 2 Dishwasher-Safe, Stainless Steel Baffle Slot Grease Filter                      | Dishwasher-Safe, Professional Stainless Steel                                      | Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter  |
| Duct Transition           | 6" Round with Back Draft Damper (top only)  | 6" Round with Back Draft Damper (top only)  | 10" Round with Back Draft Damper (top only)  | 10" Round with Back Draft Damper (top only)   |
| Installation Type         | Ducted or Recirculating   | Ducted or Recirculating   | Ducted Installation Only   |   |
| Electrical                | 120 V - 60 Hz<br>340 Wattage  | 120 V - 60 Hz<br>260 Wattage  | 120 V - 60 Hz<br>1000 Wattage  | 120 V - 60 Hz<br>1000 Wattage   |
| Stainless Steel Liner Kit | Available in 30" or 36" widths  | Available in 30" or 36" widths  |  |   |
| Optional Blower           | No  | No  | 1200 CFM Inline or 1200 CFM External   | 1200 CFM Inline or 1200 CFM External  |
| Page                      | 120   | 68  | 94   | 92  |





|                    |  |  |  |  |
|--------------------|---|---|--|---|
| Model Name         | Nemi  | TT  | Allasio  | Bellagio  |
| Model Numbers      | ENM230S1<br>ENM236S1<br>ENM230WT<br>ENM230BL                                      | ETT424SS  | EAL330S1<br>EAL336S1<br>EAL330WT<br>EAL330BL                                       | EBL430SS<br>EBL436SS<br>EBL430WT  |
| Dimensions         | 30" W x 18 3/4" D x 5" H<br>36" W x 18 3/4" D x 5" H                              | 23 9/16" W x 17 1/8" D x 1 9/16" H  | 30" W x 20" D x 4 3/4" H<br>36" W x 20" D x 4 3/4" H                               | 30" W x 20" D x 4 3/4" H<br>36" W x 20" D x 4 3/4" H<br>30" W x 20" D x 4 3/4" H    |
| Blower Type        | 280 CFM(3-speed)  | 400 CFM(3-speed)  | 300 CFM(3-speed)   | 430 CFM(4-speed)  |
| Blower Performance | Speed 1, 110 CFM<br>Speed 2, 220 CFM<br>Speed 3, 280 CFM                          | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 400 CFM                          | Speed 1, 120 CFM<br>Speed 2, 210 CFM<br>Speed 3, 300 CFM                           | Speed 1, 160 CFM<br>Speed 2, 240 CFM<br>Speed 3, 310 CFM<br>Speed 4, 430 CFM        |
| CFM Reduction      | No  | Yes/ KIT02748   | No   | Yes   |
| Noise (sones)      | Min: 1.5, Max: 4.7  | Min: 1.5, Max: 5.9  | Min: 1.85, Max: 4.2  | Min: 1.4, Max: 7.1  |
| Finish             | Stainless Steel   | Stainless Steel   | Stainless Steel  | Stainless Steel   |
| Controls           | Backlit Electronic Push Button  | Hidden Electronic Touch Controls  | Backlit Electronic Push Button Controls  | Multi-function Electronic with LCD Display  |
| Illumination       | 2 LED, 2.1 watts  | 2 LED, 2.1 watts  | 2 LED, 2.1 watts   | 2 Halogen, 50 watts   |
| Filter Type        | Dishwasher-Safe, Anodized Aluminum Mesh   | 2 Dishwasher-Safe, Anodized Aluminum Mesh   | 2 Dishwasher-Safe, Anodized Mesh Grease Filter                                     | 2 Dishwasher-Safe, Anodized Aluminum Mesh Grease Filter                             |
| Duct Transition    | 3" x 1/4" x 10" with Back Draft Damper (Top and Rear)                             | 6" Round (Top Only)   | 3 1/4" x 10" with Back Draft Damper (Top and Rear)                                 | 3 1/4" x 10" with Back Draft Damper (Top and Rear)                                  |
| Installation Type  | Ducted or Recirculating   | Ducted or Recirculating   | Ducted or Recirculating  | Ducted or Recirculating   |
| Electrical         | 120 V - 60 Hz<br>210 Wattage  | 120 V - 60 Hz<br>280 Wattage  | 120 V - 60 Hz<br>360 Wattage   | 120 V - 60 Hz<br>445 Wattage  |
| Page               | 116   | 114   | 115  | 64  |





|                    |  |  |  |
|--------------------|---|--|---|
| Model Name         | Aria  | Modena   | Glide   |
| Model Numbers      | EAI430SS<br>EAI436SS  | EMD530S3<br>EMD536S3   | EGL430S1<br>EGL436S1  |
| Dimensions         | 30" W x 20" D x 4 ¾" H<br>36" W x 20" D x 4 ¾" H                                  | 30" W x 20" D x 9" H<br>36" W x 20" D x 9" H                                       | 30"W x 11 ½-19 ¾" D x 2 ¾" H<br>36"W x 11 ½-19 ¾" D x 4 ¾" H                        |
| Blower Type        | 430 CFM (4-speed)   | 520 CFM (4-speed)  | 450 CFM (4-speed)   |
| Blower Performance | Speed 1, 160 CFM<br>Speed 2, 240 CFM<br>Speed 3, 310 CFM<br>Speed 4, 430 CFM      | Speed 1, 170 CFM<br>Speed 2, 280 CFM<br>Speed 3, 430 CFM<br>Speed 4, 520 CFM       | Speed 1, 110 CFM<br>Speed 2, 200 CFM<br>Speed 3, 300 CFM<br>Speed 4, 400 CFM        |
| CFM Reduction      | Yes   | Yes  | No  |
| Noise (sones)      | Min: 1.1, Max: 4.7  | Min: 1.73, Max: 6.0  | Min: 0.7, Max: 5.2  |
| Finish             | Stainless Steel + Black Glass   | Stainless Steel + Black Glass  | Stainless Steel + Glass   |
| Controls           | Touch Control 3 Speed + Booster   | Touch Controls 3 Speed + Booster   | Backlit Electronic Push Button Controls   |
| Illumination       | 2 Premium LED Dimmable Lights, 2.5 watts  | 2 Premium LED Dimmable Lights, 2.5 watts   | 2 LED, 3 watts  |
| Filter Type        | 2 Dishwasher-Safe, Stainless Steel Baffle Slot Filter                             | Dishwasher-Safe, Stainless Steel Microhole Grease Filter                           | 1 Dishwasher-Safe, Stainless Steel Mesh Filter                                      |
| Duct Transition    | 3 ¼" x 10" with Back Draft Damper (Top or Rear)                                   | 3 ¼" x 10" with Back Draft Damper (Top or Rear)                                    | 6" Round (Top only)   |
| Installation Type  | Ducted or Recirculating   | Ducted or Recirculating  | Ducted or Recirculating   |
| Electrical         | 120 V - 60 Hz<br>445 Wattage  | 120 V - 60 Hz<br>550 Wattage   | 120 V - 60 Hz<br>270 Wattage  |
| Page               | 60  | 62   | 111   |





|                    |  |  |   |
|--------------------|---|--|--|
| Model Name         | Sora  | Cervinia   | Calabria   |
| Model Numbers      | ESR430S1<br>ESR436S1  | ECV630S3<br>ECV636S3   | ECL630S4<br>ECL136S4<br>ECL142S4<br>ECL148S4   |
| Dimensions         | 30"W x 23"D x 10"H<br>36"W x 23"D x 10"H  | 30"W x 23"D x 11 1/32"H<br>36"W x 23"D x 11 1/32"H                                 | 30"W x 25"D x 18"H<br>36"W x 25"D x 18"H<br>42"W x 25"D x 18"H<br>48"W x 25"D x 18"H   |
| Blower Type        | 400 CFM(2-speed)  | 600 CFM(4-speed)   | 600 CFM(4-speed) - 30"<br>1200 CFM (4-speed) -<br>(36", 42", 48")  |
| Blower Performance | Speed 1, 160 CFM<br>Speed 2, 400 CFM  | Speed 1, 170 CFM<br>Speed 2, 280 CFM<br>Speed 3, 440 CFM<br>Speed 4, 600 CFM       | (30") - Speed 1, 205 CFM<br>Speed 2, 350 CFM<br>Speed 3, 510 CFM<br>Speed 4, 600 CFM<br>(36", 42", 48") -<br>Speed 1, 375 CFM<br>Speed 2, 640 CFM<br>Speed 3, 940 CFM<br>Speed 4, 1200 CFM |
| CFM Reduction      | Yes / KIT02748  | No   | No   |
| Noise (sones)      | Min: 1.5, Max: 5.9  | Min: 2.34, Max: 7.0  | Min: 2.01, Max: 6.0 (30")<br>Min: 3.1, Max: 7.7 (36", 42", 48")  |
| Finish             | Stainless Steel   | Stainless Steel  | Stainless Steel  |
| Controls           | Rocker Switch Controls  | Fully Retractable Rotating Knobs w/ Blue Backlighting                              | Fully Retractable Rotating Knobs w/ Blue Backlighting  |
| Illumination       | 2 LED Lamps, 2.1 watts  | 2 Consumer Replaceable LED, 7.5 watts  | 2 Consumer Replaceable LED, 7.5 watts  |
| Filter Type        | 2 Dishwasher-Safe, Stainless Steel Baffle Slot Grease Filter                      | 2 Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter               | Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter 2 (30", 36", 42"), 3 (48")  |
| Duct Transition    | 3 1/4" x 10" with Back Draft Damper (Top and Rear)                                | 3 1/4" x 10" with Back Draft Damper (Top and Rear)                                 | 10" Round with Back Draft Damper (Top and Rear)  |
| Installation Type  | Ducted or Recirculating   | Ducted Installation Only   | Ducted Installation Only   |
| Electrical         | 120 V - 60 Hz<br>340 Wattage  | 120 V - 60 Hz<br>550 Wattage   | 120 V - 60 Hz<br>550 Wattage   |
| Page               | 121   | 90   | 88   |





# SPECS

## Chimney Hoods




|                    |       |  |  |  |
|--------------------|--|---|--|---|
| Model Name         | Volterra   | Varna   | Varna Black  | Pilato  |
| Model Numbers      | EVL424SS<br>EVL430SS<br>EVL436SS   | EVR630S2<br>EVR636S2  | EVR630BL<br>EVR636BL   | EPL630S1<br>EPL636S1  |
| Dimensions         | 24"W x 19 5/8"D x 10 1/4"H<br>30"W x 19 5/8"D x 10 1/4"H<br>36"W x 19 5/8"D x 10 1/4"H | 30"W x 19 11/16"D x 10 1/4"H<br>36"W x 19 11/16"D x 10 1/4"H                      | 30"W x 19 11/16"D x 10 1/4"H<br>36"W x 19 11/16"D x 10 1/4"H                       | 30"W x 21 1/2"D x 10 1/4"H<br>36"W x 21 1/2"D x 10 1/4"H                            |
| Blower Type        | 400 CFM (3-speed)  | 600 CFM (4-speed)   | 600 CFM (4-speed)  | 600 CFM (4-speed)   |
| Blower Performance | Speed 1, 160 CFM<br>Speed 2, 285 CFM<br>Speed 3, 400 CFM                               | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 475 CFM<br>Speed 4, 600 CFM      | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 475 CFM<br>Speed 4, 600 CFM       | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 475 CFM<br>Speed 4, 600 CFM        |
| CFM Reduction      | Yes/ KIT02748  | Yes   | Yes  | No  |
| Noise (sones)      | Min: 0.83, Max: 6.0  | Min: 1.93, Max: 6.0   | Min: 1.93, Max: 6.0  | Min: 1.7, Max: 8.2  |
| Finish             | Stainless Steel  | Stainless Steel + Black Glass   | Black Stainless Steel + Black Glass  | Stainless Steel   |
| Controls           | Backlit Electronic Push Button   | Touch Controls 3 Speed + Booster  | Touch Controls 3 Speed + Booster   | Multi-function Electronic with LCD Display  |
| Illumination       | 2 LED lamps, 2,1 watts   | 2 Premium Dimmable Lights, 2.5 watts  | 2 Premium LED Dimmable Lights, 2.5 watts   | 2 Halogen Lamps, 40 watts   |
| Filter Type        | Dishwasher-Safe, Anodized Aluminum Mesh (2w/24", 30" & 3w/36")                         | Dishwasher-Safe, Anodized Aluminum Mesh (2w/30" & 3w/36")                         | Dishwasher-Safe, Anodized Aluminum Mesh (2w/30" & 3w/36")                          | Dishwasher-Safe, Anodized Aluminum Mesh (2w/30" & 3w/36")                           |
| Duct Transition    | 6" Round with Back Draft Damper (Top only)   | 6" Round with Back Draft Damper (Top Only)  | 6" Round with Back Draft Damper (Top Only)   | 6" Round with Back Draft Damper (Top Only)  |
| Installation Type  | Ducted or Recirculating  | Ducted or Recirculating   | Ducted or Recirculating  | Ducted or Recirculating   |
| Electrical         | 120 V - 60 Hz<br>300 Wattage   | 120 V - 60 Hz<br>340 Wattage  | 120 V - 60 Hz<br>490 Wattage   | 120 V - 60 Hz<br>530 Wattage  |
| Page               | 117  | 56  | 54   | 66  |




|                    |  |  |                                       |   |
|--------------------|---|---|---|--|
| Model Name         | Foglia  | Lugano  | Stoney  | Leone  |
| Model Numbers      | EFG630S1<br>EFG636S1  | ELG630S3<br>ELG636S3  | EST630SS<br>EST636SS  | ELN630S2<br>ELN136S2<br>ELN142S2<br>ELN148S2   |
| Dimensions         | 30" W x 20" D x 10" H<br>36" W x 20" D x 10" H                                    | 30" W x 19 1/16" D x 5" H<br>36" W x 19 1/16" D x 5" H                            | 30" W x 19 7/8" D x 5" H<br>36" W x 19 7/8" D x 5" H  | 30" W x 24" D x 12 1/8" H<br>36" W x 24" D x 12 1/8" H<br>42" W x 24" D x 12 1/8" H<br>48" W x 24" D x 12 1/8" H   |
| Blower Type        | 600 CFM (4-speed)   | 600 CFM (4-speed)   | 600 CFM (4-speed)   | 600 CFM (4-speed) - (30")<br>1200 CFM (4-speed) - (36", 42", 48")<br><br>*1200 CFM inline and external blowers available   |
| Blower Performance | Speed 1, 210 CFM<br>Speed 2, 300 CFM<br>Speed 3, 470 CFM<br>Speed 4, 600 CFM      | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 470 CFM<br>Speed 4, 600 CFM      | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 470 CFM<br>Speed 4, 600 CFM<br><br>Black Stainless Steel + Black Glass | (30") - Speed 1, 205 CFM<br>Speed 2, 350 CFM<br>Speed 3, 510 CFM<br>Speed 4, 600 CFM<br><br>(30", 42", 48") -<br>Speed 1, 375 CFM<br>Speed 2, 640 CFM<br>Speed 3, 940 CFM<br>Speed 4, 1200 CFM |
| CFM Reduction      | Yes   | Yes   | Yes   | No   |
| Noise (sones)      | Min: 1.71, Max: 7.5   | Min: 2.03, Max: 8.0   | Min: 1.53, Max: 6.0   | Min: 2.01, Max: 6.0 (30")<br>Min: 3.21, Max: 7.7 (36", 42", 48")   |
| Finish             | Stainless Steel + Black Glass   | Stainless Steel + Black Glass   | Black Stainless Steel + Black Glass   | Stainless Steel  |
| Controls           | Touch Controls 3 Speed + Booster  | Touch Controls 3 Speed + Booster  | Touch Controls 3 Speed + Booster (Sensor)   | Fully Retractable Rotating Knobs w/ Blue Backlighting  |
| Illumination       | 2 Premium LED Dimmable Lights, 2.5 watts  | 2 Premium LED Dimmable Lights, 2.5 watts  | 2 Premium LED Dimmable Lights, 2.5 watts  | 2 Consumer Replaceable LED, 7.5 watts  |
| Filter Type        | Dishwasher-Safe, Stainless Steel Micro Hole Grease Filter                         | Aluminum Mesh Filter + Perimeter Aspiration                                       | Dishwasher-Safe, Aluminum Grease Filter + Perimeter Aspiration  | Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filters 1w/30", 2w/36" & 42", 3w/48"   |
| Duct Transition    | 6" Round with Back Draft Damper (Top only)  | 6" Round with Back Draft Damper (Top only)  | 6" Round with Back Draft Damper (Top only)  | 8" Round with Back Draft Damper (Top only)   |
| Installation Type  | Ducted or Recirculating   | Ducted or Recirculating   | Ducted or Recirculating   | Ducted Installation Only   |
| Electrical         | 120 V - 60 Hz, 490 Wattage  | 120 V - 60 Hz, 530 Wattage  | 120 V - 60 Hz, 530 Wattage  | 120 V - 60 Hz, 800 Wattage   |
| Page               | 58  | 72  | 42  | 80   |

|                    |                |  |  |   |
|--------------------|---|---|--|--|
| Model Name         | Toblino   | Mezzano   | Meteorite  | Vavano   |
| Model Numbers      | ETB424SS<br>ETB430S2<br>ETB436S2  | EMZ630S3<br>EMZ636S3  | EMT636SS   | EVV636S1<br>EVV648S1   |
| Dimensions         | 24" W x 19 5/8" D x 1 9/16" H<br>30" W x 19 5/8" D x 1 9/16" H<br>36" W x 19 5/8" D x 1 9/16" H | 30" W x 19 1/16" D x 1 9/16" H<br>36" W x 19 1/16" D x 1 9/16" H                  | 36" W x 17 1/8" D x 2 3/8" H   | 36" W x 24" D x 5" H<br>48" W x 24" D x 5" H   |
| Blower Type        | 400 CFM (3-speed)   | 600 CFM (4-speed)   | 550 CFM (4-speed)  | 600 CFM (4-speed)<br>(1200 CFM inline and external blowers available)                |
| Blower Performance | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 400 CFM  | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 470 CFM<br>Speed 4, 600 CFM      | Speed 1, 192 CFM<br>Speed 2, 310 CFM<br>Speed 3, 450 CFM<br>Speed 4, 550 CFM       | Speed 1, 205 CFM<br>Speed 2, 350 CFM<br>Speed 3, 510 CFM<br>Speed 4, 600 CFM         |
| CFM Reduction      | Yes/ KIT02748   | Yes   | No   | No   |
| Noise (sones)      | Min: 0.78, Max: 6.0   | Min: 1.73, Max: 6.0   | Min: 1.7 Max: 7.0  | Min: 3.21, Max: 7.7  |
| Finish             | Stainless Steel   | Stainless Steel + Black Glass   | Stainless Steel + Black Glass  | Stainless Steel  |
| Controls           | Backlit Electronic Push Button  | Touch Controls 3 Speed + Booster  | Touch Controls 3 Speed + Booster (Sensor)  | Fully Retractable Rotating Knobs w/ Blue Backlighting                                |
| Illumination       | 2 LED Lamps, 2.1 watts  | 2 Premium LED Dimmable Lights, 2.5 watts  | Strip LED 7 Watts<br>2700-6000K - Tunable White                                    | 2 Consumer Replaceable LED, 7.5 watts  |
| Filter Type        | Dishwasher-Safe, Anodized Aluminum Mesh (2w/24" & 30", 3w/36")                                  | Dishwasher-Safe, Stainless Steel Microhole Grease Filter                          | Dishwasher-Safe, Aluminum Grease Filter + Perimeter Aspiration                     | Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filters 2 w/36", 3 w/48" |
| Duct Transition    | 6" Round with Back Draft Damper (Top only)  | 6" Round with Back Draft Damper (Top only)  | 6" Round with Back Draft Damper (Top Round 6")                                     | 8" Round with Back Draft Damper (Top only)   |
| Installation Type  | Ducted or Recirculating   | Ducted or Recirculating   | Ducted Installation Only   | Ducted Installation Only   |
| Electrical         | 120 V - 60 Hz<br>300 Wattage  | 120 V - 60 H<br>490 Wattage   | 120 V - 60 Hz<br>530 Wattage   | 120 V - 60 Hz<br>480 Wattage   |
| Page               | 118   | 52  | 38   | 84   |




|                    |                |  |  |   |
|--------------------|---|---|--|--|
| Model Name         | Toblino   | Mezzano   | Meteorite  | Vavano   |
| Model Numbers      | ETB424SS<br>ETB430S2<br>ETB436S2  | EMZ630S3<br>EMZ636S3  | EMT636SS   | EVV636S1<br>EVV648S1   |
| Dimensions         | 24" W x 19 5/8" D x 1 9/16" H<br>30" W x 19 5/8" D x 1 9/16" H<br>36" W x 19 5/8" D x 1 9/16" H | 30" W x 19 1/16" D x 1 9/16" H<br>36" W x 19 1/16" D x 1 9/16" H                  | 36" W x 17 1/8" D x 2 3/8" H   | 36" W x 24" D x 5" H<br>48" W x 24" D x 5" H   |
| Blower Type        | 400 CFM (3-speed)   | 600 CFM (4-speed)   | 550 CFM (4-speed)  | 600 CFM (4-speed)<br>(1200 CFM inline and external blowers available)                |
| Blower Performance | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 400 CFM  | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 470 CFM<br>Speed 4, 600 CFM      | Speed 1, 192 CFM<br>Speed 2, 310 CFM<br>Speed 3, 450 CFM<br>Speed 4, 550 CFM       | Speed 1, 205 CFM<br>Speed 2, 350 CFM<br>Speed 3, 510 CFM<br>Speed 4, 600 CFM         |
| CFM Reduction      | Yes/ KIT02748   | Yes   | No   | No   |
| Noise (sones)      | Min: 0.78, Max: 6.0   | Min: 1.73, Max: 6.0   | Min: 1.7 Max: 7.0  | Min: 3.21, Max: 7.7  |
| Finish             | Stainless Steel   | Stainless Steel + Black Glass   | Stainless Steel + Black Glass  | Stainless Steel  |
| Controls           | Backlit Electronic Push Button  | Touch Controls 3 Speed + Booster  | Touch Controls 3 Speed + Booster (Sensor)  | Fully Retractable Rotating Knobs w/ Blue Backlighting                                |
| Illumination       | 2 LED Lamps, 2.1 watts  | 2 Premium LED Dimmable Lights, 2.5 watts  | Strip LED 7 Watts<br>2700-6000K - Tunable White                                    | 2 Consumer Replaceable LED, 7.5 watts  |
| Filter Type        | Dishwasher-Safe, Anodized Aluminum Mesh (2w/24" & 30", 3w/36")                                  | Dishwasher-Safe, Stainless Steel Microhole Grease Filter                          | Dishwasher-Safe, Aluminum Grease Filter + Perimeter Aspiration                     | Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filters 2 w/36", 3 w/48" |
| Duct Transition    | 6" Round with Back Draft Damper (Top only)  | 6" Round with Back Draft Damper (Top only)  | 6" Round with Back Draft Damper (Top Round 6")                                     | 8" Round with Back Draft Damper (Top only)   |
| Installation Type  | Ducted or Recirculating   | Ducted or Recirculating   | Ducted Installation Only   | Ducted Installation Only   |
| Electrical         | 120 V - 60 Hz<br>300 Wattage  | 120 V - 60 H<br>490 Wattage   | 120 V - 60 Hz<br>530 Wattage   | 120 V - 60 Hz<br>480 Wattage   |
| Page               | 118   | 52  | 38   | 84   |



|                    |  |  |  |
|--------------------|---|--|---|
| Model Name         | Salice  | Stoney Island  | Leone Island  |
| Model Numbers      | ESL636S3<br>ESL642S3  | ESI636SS<br>ESI642SS   | ELI136S2<br>ELI142S2  |
| Dimensions         | 36" W x 27" D x 5" H<br>42" W x 27" D x 5" H                                      | 36" W x 27" D x 5" H<br>42" W x 27" D x 5" H                                       | 36" W x 27" D x 12 ¾" H<br>42" W x 27" D x 12 ¾" H                                  |
| Blower Type        | 600 CFM (4-speed)   | 600 CFM (4-speed)  | 1200 CFM (4-speed)<br>(1200 CFM inline and external blowers available)              |
| Blower Performance | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 470 CFM<br>Speed 4, 600 CFM      | Speed 1, 180 CFM<br>Speed 2, 300 CFM<br>Speed 3, 470 CFM<br>Speed 4, 600 CFM       | Speed 1, 375 CFM<br>Speed 2, 640 CFM<br>Speed 3, 940 CFM<br>Speed 4, 1200 CFM       |
| CFM Reduction      | Yes<br>Dimmable Lights, 2.5 watts   | Yes  | No  |
| Noise (sones)      | Min: 1.73, Max: 6.0   | Min: 1.46, Max: 6.0  | Min: 3.21, Max: 7.7   |
| Finish             | Stainless Steel +<br>Black Glass  | Stainless Steel +<br>Black Glass   | Stainless Steel   |
| Controls           | Touch Controls 3 Speed<br>+ Booster   | Touch Controls 3 Speed<br>+ Booster  | Fully Retractable Rotating<br>Knobs w/ Blue Backlighting                            |
| Illumination       | 4 Premium LED Dimmable<br>Lights, 2.5 watts                                       | 4 Premium LED Dimmable<br>Lights, 2.5 watts  | 4 Consumable Replaceable<br>LED, 7.5 watts  |
| Filter Type        | Aluminum Mesh Filter<br>+ Perimeter Aspiration                                    | Dishwasher-Safe,<br>Aluminum Grease Filter<br>+ Perimeter Aspiration               | 2 Dishwasher-Safe,<br>2 Professional Stainless<br>Steel Angled Baffle Filter        |
| Duct Transition    | 6" Round with Back Draft<br>Damper (Top only)                                     | 6" Round with Back Draft<br>Damper (Top only)                                      | 8" Round with Back Draft<br>Damper (Top only)                                       |
| Installation Type  | Ducted or Recirculating   | Ducted or Recirculating  | Ducted Installation Only  |
| Electrical         | 120 V - 60 Hz<br>530 Wattage  | 120 V - 60 Hz<br>530 Wattage   | 120 V - 60 Hz<br>800 Wattage  |
| Page               | 76  | 44   | 82  |

|                    |  |  |  |
|--------------------|---|--|---|
| Model Name         | Maggiore  | Meteorite Island   | Vavano Island   |
| Model Numbers      | EMG636S1<br>EMG642S1  | EMI648SS   | EVI642S1<br>EVI648S1  |
| Dimensions         | 36" W x 19 11/16" D x 1 9/16" H<br>42" W x 19 11/16" D x 1 9/16" H                | 48" W x 24" D x 2 3/8" H   | 42" W x 24" D x 5" H  |
| Blower Type        | 600 CFM (4-speed)   | 550 CFM (4-speed)  | 600 CFM (4-speed)<br>(1200 CFM Inline and External blowers available)               |
| Blower Performance | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 470 CFM<br>Speed 4, 600 CFM      | Speed 1, 192 CFM<br>Speed 2, 310 CFM<br>Speed 3, 450 CFM<br>Speed 4, 550 CFM       | Speed 1, 205 CFM<br>Speed 2, 350 CFM<br>Speed 3, 510 CFM<br>Speed 4, 600 CFM        |
| CFM Reduction      | Yes   | No   | No  |
| Noise (sones)      | Min: 1.73, Max: 6.0   | Min: 1.7, Max: 7.0   | Min: 3.21, Max: 7.7   |
| Finish             | Stainless Steel + Black Glass   | Stainless Steel + Black Glass  | Stainless Steel   |
| Controls           | Touch Controls 3 Speed + Booster  | Touch Controls 3 Speed + Booster (Sensor)  | Fully Retractable Rotating Knobs w/Blue Backlighting                                |
| Illumination       | 4 Premium LED Dimmable Lights, 2.5 watts  | Strip LED 7 watts<br>2700-6000K, Tunable White                                     | 4 Consumer Replaceable LED, 7.5 watts   |
| Filter Type        | 3 Dishwasher-Safe, Stainless Steel Microhole Filter                               | Dishwasher-Safe, Aluminum Grease Filter + Perimeter Aspiration                     | Dishwasher-Safe, 3 Professional Stainless Steel Angled Baffle Filters               |
| Duct Transition    | 6" Round with Back Draft Damper (Top only)  | 6" Round with Back Draft Damper (Top only)   | 8" Round with Back Draft Damper (Top only)  |
| Installation Type  | Ducted or Recirculating   | Ducted or Recirculating  | Ducted Installation Only  |
| Electrical         | 120 V - 60 Hz<br>426.2 Wattage  | 120 V - 60 Hz<br>530 Wattage   | 120 V - 60 Hz<br>480 Wattage  |
| Page               | 74  | 40   | 86  |




Curved Glass Island






|                    |  |  |  |
|--------------------|---|--|---|
| Model Name         | Potenza   | Como   | Cingoli   |
| Model Numbers      | EPT430S2<br>EPT436S2  | ECM630S3<br>ECM636S3   | ECN636S3<br>ECN642S3  |
| Dimensions         | 30" W x 19 5/8" D x 1 15/16" H<br>36" W x 19 5/8" D x 1 15/16" H                  | 30" W x 19 11/16" D x 1 15/16" H<br>36" W x 19 11/16" D x 1 15/16" H               | 36" W x 25 3/16" D x 1 15/16" H<br>42" W x 25 3/16" D x 1 15/16" H                  |
| Blower Type        | 400 CFM (3-speed)   | 600 CFM (4-speed)  | 600 CFM (4-speed)   |
| Blower Performance | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 400 CFM                          | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 470 CFM<br>Speed 4, 600 CFM       | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 470 CFM<br>Speed 4, 600 CFM        |
| CFM Reduction      | Yes/ KIT02748   | Yes  | Yes   |
| Noise (sones)      | Min: 0.91, Max: 5.9   | Min: 2.36, Max: 6.0  | Min: 2.36, Max: 6.0   |
| Finish             | Stainless Steel   | Stainless Steel +<br>Black Glass   | Stainless Steel +<br>Black Glass  |
| Controls           | Backlit Electronic<br>Push Button   | Touch Controls 3 Speed<br>+ Booster  | Touch Controls 3 Speed<br>+ Booster   |
| Illumination       | 2 LED, 2.1 watts  | 2 Premium LED, Dimmable<br>Lights, 2.5 watts                                       | 2 Premium LED, Dimmable<br>Lights, 2.5 watts  |
| Filter Type        | Dishwasher-Safe, Anodized<br>Aluminum Mesh Filter                                 | Dishwasher-Safe, Stainless Steel<br>Microhole Filter                               | 1 Dishwasher-Safe, Stainless<br>Steel Microhole Grease Filter                       |
| Duct Transition    | 6" Round with Back Draft<br>Damper (Top Only)                                     | 6" Round with Back Draft<br>Damper (Top Only)                                      | 6" Round with Back Draft<br>Damper (Top Only)                                       |
| Installation Type  | Ducted or Recirculating   | Ducted or Recirculating  | Ducted or Recirculating   |
| Electrical         | 120 V - 60 Hz<br>300 Wattage  | 120 V - 60 Hz<br>530 Wattage   | 120 V - 60 Hz<br>530 Wattage  |
| Page               | 119   | 48   | 50  |


Ceiling

Down Draft

Outdoor

|                    |  |  |       |
|--------------------|---|--|--|
| Model Name         | Siena   | Rise   | Capri  |
| Model Numbers      | ESNX43S1  | ERS630S1<br>ERS636S1   | ECP136SS<br>ECP148SS   |
| Dimensions         | 43" W x 27" D x 7 ¾" H  | 30" W x 12 ½" D x 14" H<br>36" W x 12 ½" D x 14" H                                 | 36" W x 32" D x 18" H<br>48" W x 32" D x 18" H   |
| Blower Type        | 600 CFM In Line<br>(4-speed)  | 600 CFM (4-speed)  | 1200 CFM (4-speed)<br>Internal or external   |
| Blower Performance | Speed 1, 160 CFM<br>Speed 2, 280 CFM<br>Speed 3, 470 CFM<br>Speed 4, 600 CFM      | Speed 1, 205 CFM<br>Speed 2, 350 CFM<br>Speed 3, 510 CFM<br>Speed 4, 600 CFM       | Speed 1, 375 CFM<br>Speed 2, 640 CFM<br>Speed 3, 940 CFM<br>Speed 4, 1200 CFM            |
| CFM Reduction      | No  | No   | No   |
| Noise (sones)      |   | Min: 1.9, Max: 8.0   | Min: 2.47, Max: 9.04   |
| Finish             | Stainless Steel   | Stainless Steel  | Corrosion Resistant<br>Grade Stainless Steel   |
| Controls           | Remote Control  | Rotative Touch Control   | Fully Retractable Rotating<br>Knobs w/Blue Backlighting                                  |
| Illumination       | 4 LED, 2.5 watts  |  | 2 LED, 7.5 watts (36")<br>4 LED, 7.5 watts (48")<br><small>*Consumer Replaceable</small> |
| Filter Type        | Dishwasher Safe<br>Aluminum Mesh filter<br>+ Perimeter Aspiration                 | Perimeter Aspiration<br>(Aluminum Mesh Filter<br>Behind)                           | Dishwasher-Safe,<br>Professional Stainless Steel<br>4 w/36", 6 w/48"                     |
| Duct Transition    | 5 way, 6" Round   | 6" Round with Back Draft<br>Damper (Side)  | 10" Round with Back Draft<br>Damper (Topn Only)  |
| Installation Type  | Ducted Installation Only  | Ducted Installation Only   | Ducted Installation Only   |
| Electrical         | 120 V - 60 Hz<br>365 Wattage  | 120 V - 60 Hz<br>410 Wattage   | 120 V - 60 Hz<br>913 Wattage   |
| Page               | 108   | 70   | 96   |

|                    |                       |  |  |  |  |
|--------------------|--|---|--|---|---|
| Model Name         | Easy   | Wave  | Chrome   | Twin  | Star  |
| Model Numbers      | EES320SS<br>EES320WT   | EWV320SS  | ECH623S1   | ETP536SS  | EST319GL  |
| Dimensions         | 19 3/4" W x 19 3/4" D<br>x 16 7/8" H   | 19 3/4" W x 19 3/4" D<br>x 16 7/8" H  | 22 7/8" W x 17" D<br>x 22 7/8" H   | 35 7/16" W x 19 11/16" D<br>x 14 3/16" H  | 18 5/16" W x 18 5/16" D<br>x 13 1/2" H  |
| Blower Type        | 355 CFM (4-speed)  | 350 CFM (3-speed)   | 600 CFM (4-speed)  | 550 CFM (4-speed)   | 300 CFM (4-speed)   |
| Blower Performance | Speed 1, 102 CFM<br>Speed 2, 165 CFM<br>Speed 3, 240 CFM<br>Speed 4, 355 CFM                           | Speed 1, 110 CFM<br>Speed 2, 220 CFM<br>Speed 3, 350 CFM                          | Speed 1, 195 CFM<br>Speed 2, 340 CFM<br>Speed 3, 500 CFM<br>Speed 4, 600 CFM       | Speed 1, 200 CFM<br>Speed 2, 325 CFM<br>Speed 3, 450 CFM<br>Speed 4, 450 CFM        | Speed 1, 100 CF<br>Speed 2, 175 CFM<br>Speed 3, 250 CFM<br>Speed 4, 300 CFM         |
| CFM Reduction      | No   | No  | No   | No  | No  |
| Noise (sones)      | Min: 1.65, Max: 5.0  | Min: 0.3, Max: 3.8  | Min: 0.7, Max: 4.8   | Min: 0.31, Max: 4.3   | Min: 0.31, Max: 4.1   |
| Finish             | Stainless Steel /<br>White   | Stainless Steel   | Stainless Steel  | Stainless Steel   | Glass Crystals<br>+ Stainless Steel   |
| Controls           | Touch Control 3S +<br>Booster  | Electronic Backlit<br>Push Button   | Magic Wand   | Magic Wand  | Magic Wand  |
| Illumination       | 3 LED, 5 watts   | 6 LED, 2 watts  | 2 LED, 3 watts   | 8 LED, 2 watts  | 1 LED, 2 watts  |
| Filter Type        | 1 Dishwasher-Safe,<br>Perimeter Aspiration +<br>Aluminum Mesh Filter<br>+ 1 Carbon Long Life<br>Filter | Dishwasher-Safe,<br>Aluminum Mesh Grease<br>Filter, 1 Long Life<br>Carbon Filter  | 1 EDS Dishwasher-Safe,<br>Anodized Aluminum<br>Mesh Grease Filter                  | Dishwasher-Safe,<br>2 Aluminum Mesh<br>Grease Filter, 2 Long<br>Life Carbon Filter  | 1 Dishwasher-Safe,<br>Aluminum Mesh<br>Grease Filter + Long<br>Life Carbon Filter   |
| Installation Type  | Recirculating<br>Installation Only   | Recirculating<br>Installation Only  | Ducted or<br>Recirculating   | Recirculating<br>Installation Only  | Recirculating<br>Installation Only  |
| Electrical         | 120 V - 60 Hz<br>460 Wattage   | 120 V - 60 Hz<br>320 Wattage  | 120 V - 60 Hz<br>490 Wattage   | 120 V - 60 Hz<br>320 Wattage  | 120 V - 60 Hz<br>320 Wattage  |
| Page               | 102  | 106   | 110  | 107   | 104   |

|                      |  |  |
|----------------------|--|--|
|                      |                           |    |
| Model Name           | NikolaTesla  | Golden   |
| Model Numbers        | ENT432BL   | EGL324BL<br>EGL430BL<br>EGL536BL   |
| Dimensions           | 32 1/16" W x 20 1/16" D x 8 1/4" H   | 23 3/4" W x 20 3/4" D x 2 1/4" H<br>29 3/4" W x 20 3/4" D x 2 1/4" H<br>35 3/4" W x 20 3/4" D x 2 1/4" H   |
| Blower Type          | 400 CFM (4-speed)  |  |
| Blower Performance   | Speed 1, 160 CFM<br>Speed 2, 250 CFM<br>Speed 3, 350 CFM<br>Speed 4, 400 CFM (Booster)                     |  |
| Noise (sones)        | Min: 2.2, Max: 5.0   |  |
| Cooking Zones        | 4 (2,1 - 3,7 kW) - 7,1 x 7,9 inches  | 3 Cooking Zones + 1 Bridge Zone (24")<br>4 Cooking Zones + 1 Bridge Zone (30")<br>5 Cooking Zones + 2 Bridge Zones (36")                                     |
| Heating Level        | 9 Levels + Booster   | 9 Levels + Booster   |
| Finish               | Black Glass  | Black Glass  |
| Controls             | Slider Touch Control 3S + Booster Ventilation  | Electronic Glass Touch with Finger Glide Function  |
| Installation Type    | Ducted or Recirculating<br>Self Rimming or Flush Mounted   | Self Rimming or Flush Mounted  |
| Filter Specification | 6 Layer Anodized Aluminum Mesh Grease Filter   |  |
| Electrical           | 208 - 240 V - 60 Hz<br>440 Watts at 3.3 Amps<br>240 V - 7.8 kW at 32.5 Amps<br>208 V - 7.1 kW at 34.1 Amps | (24" & 30") 208 - 240 V - 60 Hz<br>7.7 kW at 32.1 Amps<br>6.7 kW at 32.2 Amps<br><br>(36") 208 - 240 V - 60 Hz<br>11.5 kW at 47.9 Amps<br>10 kW at 48.1 Amps |
| Page                 | 22   | 28   |