



AREZZO Insert

ELICA PRO SERIES



LED lamps



hidden metallic in/out knob controls



professional stainless steel baffle filters

Arezzo provides professional grade performance, while being discreetly mounted inside the cabinetry.

Arezzo is available in 28 1/2" width with a 600 CFM blower, and equipped with a 1200 CFM blower for widths of 34 1/2", 40 1/2" and 46 1/2" for extraordinary ventilating power.

The extra depth (22") is ideal for supporting powerful professional ranges. Plus the All-In-One design avoids the need to purchase a stainless liner. Hidden metallic in/out knob controls operate the 4-speed blower and LED lighting.

Easy maintenance, higher efficiency and a cleaner kitchen are ensured by Elica's Professional Baffle Filters, which capture a higher percentage of contaminants and hold larger volumes of grease than traditional baffle filters. Arezzo is designed for standard ducted installation only.

Dimensions | Models

28 1/2" W x 22" D x 11 1/2" H | EAR628S3
Arezzo 28" Stainless

34 1/2" W x 22" D x 11 1/2" H | EAR134S3
Arezzo 34" Stainless

40 1/2" W x 22" D x 11 1/2" H | EAR140S3
Arezzo 40" Stainless

46 1/2" W x 22" D x 11 1/2" H | EAR146S3
Arezzo 46" Stainless



HUSH



LED LIGHT



PROFESSIONAL PERFORMANCE




HEAT GUARD

FEATURES

Size (in) & Type	28", 34", 40" or 46" Wide Insert
Finish	Stainless steel
Controls	IN/OUT Backlit Knob
Illumination	2 LED (28" & 34") 7.5 watts LED light, replaceable lamps (1 intensity) 4 LED (40" & 46") 7.5 watts LED light, replaceable lamps (1 intensity)
Installation Type	Ducted Installation Only
Blower Type	600 CFM, 4-Speed Internal (28" Unit) 1200 CFM, 4-Speed Internal (34", 40", 46" Units)
Blower Performance	Speed 1 (For 28") 90 CFM, (For 34", 40" & 46") 380 CFM Speed 2 (For 28") 330 CFM, (For 34", 40" & 46") 660 CFM Speed 3 (For 28") 490 CFM, (For 34", 40" & 46") 950 CFM Speed 4 (For 28") 600 CFM, (For 34", 40" & 46") 1200 CFM
Noise (sones):	28" Unit: Min: 2.05, Max: 7.05 Sones 34", 40", 46" Units: Min: 2.05, Max: 7.05 Sones
Filter Type	Dishwasher-Safe, Professional Stainless Steel, Angled Baffle Filters 2 (28", 34", 40" Units) 3 (48" Unit)
Duct Transition	10" Round with Back Draft Damper (top only)
Electrical	120V-60Hz
Warranty	2 Year Parts & Labor, In-Home Service

Line Drawing



	Models				
	EAR628S3	ETR134S5	EAR134S3	EAR140S3	EAR146S3
A	28½" (72.4 cm)	34½" (87.6 cm)	40½" (103 cm)	46½" (118 cm)	
B	22" (55.9 cm)	18" (45.7 cm)	22" (55.9 cm)		
C	5 ½" (13.8 cm)				
D	6 ½" (16.4 cm)				
E	27 ¾" (70 cm)				
F	12 ¼" (31.6 cm)				
G	29 1 ¾" (75.7 cm)				
H	10 ¾" (25.7 cm)				
I	10" (25.4 cm)				
J	¾" (1.9 cm)				

PLUS



HUSH SYSTEM

An exclusive sound deadening technology that effectively reduces sound levels by over 35%, compared to typical range hoods.



LED LIGHT

LED lighting is undoubtedly the smartest solution in terms of energy saving. Expected life time of over 20.000 hours, represents the most remarkable advantage of LED light bulbs.



PROFESSIONAL PERFORMANCE

Special features and very high performances for models with aspiration capacity between 600 and 1200 CFM's, and noise level between 65 and 75 db(A) at maximum speed. The ideal complement of PRO ranges.



HEAT GUARD

A safety feature that protects the hood and cabinetry from excessive heat, by sensing extreme temperatures (>158 degrees) and will automatically adjust the blower speed to HIGH. Blower speed will automatically adjust back once temperatures drop to a safe level.

Accessories

Replacement Grease Filter (1)

CODE: GFO61A

Consumable parts are sold in units of one (1). Order accordingly.