




The ultra slim design of TT hides quietly within cabinetry and extends less than 2" below the edge.

When called to action, the horizontal visor effortlessly pulls out to provide added air capture during cooking. IT design is ideal for smaller kitchens or where under-cabinet space is limited. The 400 CFM blower provides more than adequate power for everyday cooking. The 3 speed blower and alhogen lighting are operated with modern electronic touch controls, which are out of sight and behind the visor when idle. Clean up is literally a snap with dishwasher safe anodized aluminum mesh filters.

Designed for ducted or recirculating installations.





	ETT424SS	ETT430SS
Α	23" ⁹ /16(60.9cm)	30" (76.2 cm)
В	6½" (15.2 cm)	
С	11" (27.9 cm)	
D	1 %16" (3.9 cm)	
Е	10 ½ " (26 cm)	
F	18 ½ " (46 cm)	
G	6" (15.2 cm)	

COMFORT SERIES





SPECIFICATIONS





	24" Unit	30" Unit	
Model:	ETT424\$1	ETT430SS	
Dimensions:	23 9/16"W x 17 1/18"D x 1 9/16"H	30 9/16"W x 17 1/18"D x 1 9/16"H	
Blower Type(internal):	400 CFM(3-speed)		
Blower Performance:			
Speed 1	160 CFM		
Speed 2 Speed 3	280 CFM 400 CFM		
Noise (sones):	Min:1.5, Max:5.9		
Woking Speed	MIII.1.3, Max.3.7		
Finish:	Stainless Steel		
Controls:	Hidden Electronic Touch Controls		
Illumination:	2, 20 W Halogen Lamp (Bulb included)	2 LED, 2.1 watts	
Filter Type:	Dishwasher-Safe, Anodized Aluminum Mesh Filter		
Number of filters:	1	1	
Duct Transition:	6" Round, (Non return valve included)		
Installation Type: Electrical:	Ducted or Recirculating Installation 120 V - 60 Hz 280 Wattage		
	120 V - 60 HZ	280 Wallage	
KITS:			
Recirculating Kit	F00539	XXX	
CFM Reduction Kit	KIT02736	xxx	
CONSUMABLE PARTS:			
Replacement	xxx		
Light Bulb (1):	, ,	V.	

*Consumable parts are sold in units of one (1). Order accordingly

PLUS FEATURES





