

		WC-46DZ	BC-112	WC-28DZ	BC-79	WC-118TZ
CAPACITY						
Volume (ft ³)	Gross	5.40	5.40	3.50	3.50	14.10
	Net	4.70	4.90	3.04	3.20	12.19
750 ml Bottles		46	13	28	3	118
12 oz. Bottles		No	42	No	28	No
12 oz. Cans		No	36	No	48	No
GENERAL FEATURES						
Built-in Installation		Yes	Yes	Yes	Yes	Yes
Dual-Zone		Yes	No	Yes	No	No
Three-Zone		No	No	No	No	Yes
Opening Direction		Right	Right	Right	Right	Right
Reversible left/ right doors		Yes	Yes	Yes	Yes	Yes
LED Light		White	White	White	White	White
Number of Lights		4	2	2	1	6
Number of Shelves		5	3	5	2	13
Material of Shelves		Solid Beech wood	Wood faced wires	Solid Beech wood	Wood faced wires	Solid Beech wood
Shelf Style		Glide Out	Glide Out	Glide Out	Glide Out	Glide Out
Anti-odor filter		Yes	No	Yes	No	Yes
Silent Anti-Vibration Compressor		Yes	Yes	Yes	Yes	Yes
Glass Door		Yes	Yes	Yes	Yes	Yes
Door Lock		Yes	Yes	Yes	Yes	Yes
OPERATION CONTROL						
Electronic Control		Yes	Yes	Yes	Yes	Yes
Open Door Alarm		Yes	Yes	Yes	Yes	Yes
Temperature Alarm		Yes	Yes	Yes	Yes	Yes
Temperature Selection		Blue LED	Blue LED	Blue LED	Blue LED	Blue LED
Temperature Adjustment		Blue LED	Blue LED	Blue LED	Blue LED	Blue LED
Temperature Range		41°F-68°F / 5°C-20°C	36°F-43°F / 2°C-6°C	41°F-68°F / 5°C-20°C	36°F-43°F / 2°C-6°C	41°F-68°F / 5°C-20°C
Dynamic Climate Mode		Yes	Yes	Yes	Yes	Yes
Sabbath Mode		Yes	Yes	Yes	Yes	Yes
TECHNICAL SPECIFICATIONS						
Climate Class		N.A	N.A	N.A	N.A	N.A
Ambient Temperature		60°F-95°F / 16°C-35°C	60°F-95°F / 16°C-35°C	60°F-95°F/16°C-35°C	60°F-95°F/16°C-35°C	60°F-95°F / 16°C-35°C
Energy Consumption (kwh/24h)		0.7	1.2	0.65	1.0	1.4
Annual Energy Consumption (kwh/year)		255	438	238	365	511
Voltage (V)		115	115	115	115	115
Frequency (Hz)		60	60	60	60	60
Current (A)		1	1	1	1	1
Noise Level db(a)		34	34	34	34	37
DIMENSIONS						
Dimensions (inches)	Height	34"	34"	34"	34"	69 ⁵ / ₈ "
	Width	23 1/2"	23 1/2"	14 ³ / ₄ "	14 ³ / ₄ "	23 1/2"
	Depth	23 1/2"	23 1/2"	24 ¹ / ₄ "	24 ¹ / ₄ "	24 1/4"