

MIRA TOP

Version

FFMIR16W5FS-R Wall 16" (40 cm) Fasteel – 500 CFM

Collection

Fasteel

EAN code

8034122202297



Photograph is for information purposes only
May not correspond to the selected version

FEATURES

Scotch brite Fasteel no finger prints
Perimeter suction
Electronic control
LED lighting
Metallic grease filter, removable and washable
Optional charcoal filter
SRS Speed reduction system

Recommended mounting height from cooking surface to hood bottom: 24" - 35"

OPTIONAL ACCESSORIES

FDNUVMTR600

FDNUVMTR600 - Motor 600 CFM

FFCHASQC0BL

FFCHASQC0BL - Square charcoal filter - Type 3

TECHNICAL FEATURES

Installation type

Wall

Dimensions

16 / 40 cm

Finish

Scotch brite Fasteel no finger prints

Motor

500 CFM

Type of control

Electronic control

Speed settings

4

Lighting

Led 2x1,2 W - 3200 K

Filter

Metallic filter "Base" - 277x294 mm

Charcoal filter

FFCHASQC0BL - Square charcoal filter - Type 3 (optional)

Minimum distance

Gas hob: 24 in

Electric hob: 21 in

PACKAGING:WEIGHTS AND VOLUMES

Gross weight

45 lbs

Net weight

36 lbs

Volumes

10 ft³

Packaging size

Length

40 in

Height

19 in

Depth

24 in

CONSUMPTION AND CONNECTION FEATURES

Maximum consumption

280 W

Plug type

Hood comes standard with Nema 5-15P power cord

MOTOR TECHNICAL SHEET

Maximum capacity

590 m³/h

I.E.C. 61591

Maximum noise level

64 dB(A)re1pW


I.E.C.60704-2-13

Maximum pressure (Pa)

500 Pa

Max. motor power

203 W



MIRA TOP

Version

FFMIR16W5FS-R Wall 16" (40 cm) Fasteel – 500 CFM

Collection

Fasteel

EAN code

8034122202297

MOTOR TECHNICAL SHEET

Motor Speed	1	2	3	4
Noise level dB(A) _{re1pW-I.E.C.60704-2-13}	45	50	55	64
Capacity (m ³ /h) I.E.C.61591	230	300	380	590
Maximum pressure (Pa)	390	420	460	500
Motor Power (W)	134	156	180	203
Air outlet	150	150	150	150

CAPACITY / PRESSURE

