

FFAD5033W1

Dehumidifier

Available Colors : White

High Humidity 50 Pint Capacity Dehumidifier

Version : 03/20



Product Specifications

Functions

24-Hour On/Off Timer	Yes
Auto Restart	Yes
Auto Shut-Off	Yes
Continuous Drain Operation	Yes

Dehumidifier

Air CFM (High)	229
Air CFM (Low)	167
Air CFM (Med)	194
Container Capacity (Pints)	16.9
Container Full Indication	Yes
Digital Humidity Readout	Yes
Fan Speeds - Fan	3
Filter Access	Rear of Unit
Filter Check Indicator	Yes
Filter Type	Easy-to-Clean Washable Filter
Low Temperature Operation	Yes
Motor RPM (High)	1160
Motor RPM (Low)	880
Motor RPM (Med)	980
Noise Level dB (High)	51
Noise Level dB (Low)	47
Noise Level dB (Med)	49

Electrical Specifications

Amps	5.2
Plug Type	LCDFI 5-15P
Power Cord Length	6'
Voltage Rating	115
Watts	545

Certifications & Approvals

ENERGY STAR® Certified	Yes
Energy Efficiency Verification	Yes
ISTA 6	Yes
UL Listed	Yes
cUL Listed	Yes

Controls

Control Type	Electronic
--------------	------------

Performance

DOE Rating	Yes
Dehumidification - Pints per Day	50

Dimensions

Depth	12.19"
Height	24.25"
Width	15.96"

General Specifications

Prop 65 Label	Yes
Refrigerant Type	R410a
Stack Height	6
40 HQ Stuffing Quantity	663
Warranty - Labor	1 yr Full
Warranty - Parts	1 yr Full

Note: For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at [frigidaire.com / frigidaire.ca](http://frigidaire.com/frigidaire.ca). Specifications subject to change. Accessories information available on the web at frigidaire.com / frigidaire.ca