



Built-In Cooktop

FPIC3677RF

36" Induction



Product Dimensions

| | |
|--------|---------|
| Width | 36" |
| Depth | 20-1/8" |
| Height | 2-7/8" |

More Easy-To-Use Features

Cool Cooktop, Simple Cleanup
Cool-to-the-touch cooktop generates heat directly to the pan, not the cooktop, so spills can't burn on.

Controlled Cooking
Adjusts from a powerful boil to a gentle simmer instantly — ideal for rice, soups and sauces.

Professional-Grade Controls
Heavy-duty knobs deliver precise temperature control, whether you're simmering, sautéing, searing or boiling.

Efficient Use of Power
The cooktop heats the pan directly so less heat is lost in the cooking process.

Cookware Compatible
Induction-friendly cookware includes most stainless steel or iron-based cookware. If a magnet sticks to the bottom of the cookware, it's compatible.

Available in:



Signature Features



Maximize Your Time
PowerPlus™ Induction Technology boils water in less than 2 minutes so you can shave time off of cooking dinner every day!



Gas Benefits, Without the Remodel
Our PowerPlus™ Induction Cooktop offers the the speed, control and consistency of gas, without requiring the converting of your kitchen from electric to gas.



Flexible Cooking
SpacePro™ Bridge Element allows you to cook two separate dishes at once, or combine elements for large pots or griddle use. The cooktop adapts to the size of the pan whether it's a small pot, a large frying pan or a griddle.



Consistent Results
Even heat eliminates hot spots and delivers consistent results for creating delicious, evenly cooked foods like steaks and omelettes.


| Elements | Size | Watts |
|-------------|------|---------------|
| Right Front | 10" | 2,500 / 3,800 |
| Right Rear | 6" | 1,450 / 2,000 |
| Left Bridge | 7" | 1,800 / 2,600 |
| Left Rear | 7" | 1,800 / 2,600 |
| Centre | 8" | 2,300 / 3,200 |

10" induction right burner, 6 qt./10" diameter pot, 1 qt. tepid water.

| Features | |
|--|----------------------|
| Controls | Pro-Select® Controls |
| Surface Type | Black Ceramic Glass |
| Right Front Element (Watts) | 10" - 2,500/3,800 |
| Right Rear Element (Watts) | 6" - 1,450/2,000 |
| Left Bridge Element (Watts) | 7" - 1,800/2,600 |
| Left Rear Element (Watts) | 7" - 1,800/2,600 |
| Centre (Watts) | 8" - 2,300/3,200 |
| Hot Surface Indicators | Yes |
| Control Location | Centre Front |
| Knob Colour | Stainless |
| Knob Type | Cast Metal |
| Specifications | |
| Power Supply Connection Location | Right Rear |
| Voltage Rating | 240V /208V /60Hz |
| Connected Load (kW Rating) @ 240/208 Volts ¹ | 12.0/10.4 |
| Amps @ 240/208 Volts | 50 / 50 |
| Minimum Circuit Required (Amps) | 40 |
| Approved for Electric Single Wall Oven Combination Installation ² | Yes |
| Shipping Weight (Approx.) | 53 Lbs. |

¹Single phase 3- or 4-wire cable, 120/240 or 120/208 Volt, 60 Hertz AC only electrical supply with ground required on separate circuit fused on both sides of line.

²Cooktops are approved for installation above any of our Electric Single Wall Ovens.



NOTE: For planning purposes only. Always consult local and national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.ca.



| Product Dimensions | |
|--------------------|---------|
| A - Width | 36" |
| B - Depth | 20-1/8" |
| C - Height | 2-7/8" |

| Cutout Dimensions | |
|---------------------|-------------------|
| Width (Min.)/(Max.) | 33-7/8" / 34" |
| Depth (Min.)/(Max.) | 19-1/8" / 19-1/4" |
| Height | 3-5/8" |

Granite Countertop Installation Kit available.

Accessories information available on the web at frigidaire.ca