



Side-by-Side Refrigerator

FPHS2399K F

23 Cu. Ft. Standard-Depth



Signature Features



SpaceWise™ Organization System

Our SpaceWise™ Organization system makes it easy to keep food organized and easy to find when you need it.




Real Stainless Steel

Real stainless steel with a protective coating that reduces fingerprints and smudges so it's easy to clean.



Best-in-Class Ice & Water Filtration¹

PureSource Ultra™ Water Filtration offers best-in-class water filtration so you get cleaner, better-tasting water at your fingertips.



PowerPlus™ Ice²

PowerPlus™ Ice delivers up to 37 percent more ice.

Powerful Performance

- PowerPlus™ Freeze
- PureAir Ultra™ Filters
- Quiet Pack

Performance-Driven Style

- Pro-Select™ Controls
- Temp/Door Ajar/Power Failure Alerts
- Performance Lighting
- Tall, 13-Button Water & Ice Dispenser
- Digital Electronic Temperature Controls
- Stainless Look Cabinet

SpaceWise™ Design

- Refrigerator -
- SpaceWise™ Adjustable Glass Shelf
 - 3 Sliding SpillSafe™ Glass Shelves
 - Chill Drawer
 - 2 Clear Crispers (1 Divided) with 3 Adjustable Humidity Controls
 - Wine Rack/Can Dispenser
 - 3 Adjustable Clear Gallon Door Bins
 - 2 Fixed Clear 2-Liter Door Bins
- Freezer -
- 2 Fixed Glass Shelves
 - Full-Extension Basket
 - Regular Basket
 - Half Basket
 - 2 Fixed Clear Door Bins
 - 3 Tilt-Out Wire Door Shelves

ENERGY STAR®
Sabbath Mode (Star-K® Certified)



Capacities

Total Capacity	22.6 Cu. Ft.
Refrigerator Volume	14.22 Cu. Ft.
Freezer Volume	8.33 Cu. Ft.

Overall Exterior Dimensions

Height (Including Hinges & Rollers)	69-3/8"
Width	32-5/8"
Depth	31-3/4"


Available in:



Stainless
(F)

¹As compared to other consumer refrigeration water filtration systems.

²In a 24-hour period.



Side-by-Side Refrigerator Specifications

- Product Shipping Weight (approx.) - 285 Lbs.
- Voltage Rating - 120V / 60 Hz / 15 or 20 Amps
- Connected Load (kW Rating) @ 120 Volts = 1.02 kW (For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.)
- Amps @ 120 Volts = 8.5 Amps
- Always consult local and national electric & plumbing codes.
- Floor should be level surface of hard material, capable of supporting fully loaded refrigerator.
- When installing refrigerator adjacent to wall, cabinet or other appliance that extends beyond front edge of unit, 20" minimum clearance recommended to allow for optimum 120° to 180° door swing, providing complete drawer / crisper access and removal. (*Absolute 4-1/2" minimum clearance will ONLY allow for 90° door swing which will provide drawer / crisper access with restricted removal.*)
- To ensure optimum performance, avoid installing in direct sunlight or close proximity to range, dishwasher or other heat source.
- For proper ventilation, front grille MUST remain unobstructed.

- Recess electrical outlet when possible.
- Water recess on rear wall recommended to prevent water line damage.
- Water Pressure - Cold water line must provide between 30 and 100 pounds per square inch (psi).
- Copper tubing with 1/4" O.D. recommended for water supply line with length equal to distance from rear of unit to household water supply line plus 7 additional feet. Optional Water Supply Installation Kits available.
- Adjustable front rollers to assist with door alignment.

"Built-In Look" Specifications

- Minimum opening of 70-1/4" H x 33" W x 28-7/8" D required to allow for ease of installation, proper air circulation, and plumbing / electrical connections.
- Remove all wall / floor molding prior to installation.

Note: For planning purposes only. Refer to Product Installation Guide on the web at frigidaire.com for detailed instructions.