30" TOUCH CONTROL DOUBLE OVEN - STAINLESS STEEL

F7MDP30S1





OVENS

Creactive Touch Control System

Dual True Convection

Self-cleaning oven with Multifunction baking

Black Porcelain enamel interior

Cool to the touch

Extra-large baking cavity and viewing area

3 Halogen lights for flawless visibility

Total capacity 123 lt

Total capacity 4,34 cu. ft.

2 chromed racks

1 telescopic rack per oven

Enameled Broiler Pan

Lock Keys

Door Lock Soft Close

OVEN FUNCTIONS

Bake (cooking group)

Broil

Convection (cooking group)

Keep Warm (cooking group)

Recipes

Classic Pizza Function 590°F

Preset default temperature

Preheat (display instantaneous temperature)

Fast Preheat Mode

Sabbath Mode

Setting Temperature °C/°F

Setting Weight Kg/lb

Event Logs (for Service)

Meat Probe (only upper oven) Self-Clean

AirFry

OPTIONAL ACCESSORIES


FMTR630

30" Telesc. Rack

fulgor-milano.us FULGOR MILANO

30" TOUCH CONTROL DOUBLE OVEN





CODE ID	30" TOUCH CONTROL DOUBLE OVEN F7MDP30S1	
Series	700	
Finish	Stainless Steel	
CONTROL PANEL		
Control Type	Creactive Electronic Touch Control	
Display: Clock - Temperature - Function	TFT 3.5"	
Language		ench / Spanish / Italian / German
	Control Interface Full Touch: Functions -	Chime Volume Setting
	Recipes - Settings Menu	Date Format
	Brightness Setting	Demo Mode
OVEN	Dono mode	
Type	Dual True Convection	
Temperature Regulation	Electronic Control (min/max 170/550°F - 75/290°C)	
OVEN FUNCTIONS		
	Pyrolytic Self-Clean	Broil
	True Convection	Dehydrate
	Convection Broil	Thaw (Defrost)
	Convection Roast	Proof (Warm)
	Pizza (Lower Convection)	Keep warm (Warm Plus)
	Bake	Oven Lights
ELECTRIC OVEN FEATURES	AirFry	
ELECTRIC OVEN FEATURES	Preset default temperature	Display instantaneous temperature
	Child Door Lock	Control Display Lock
	Sabbath Mode	12/24 Hour Clock Formats
	Automatic Fast Preheat	Temperature Display °C/°F
	Meat Probe (Upper Oven Only)	Event Logs (for Service)
OVEN DOOR(S)		-
Oven Glass Window	Large See Through Glass	
Door Cooling System	4 Heat Resistant Glasses	
Door Hinges	Soft Closing	
OVEN CAVITY	100	
Total Capacity (lt)	123	
Total Capacity (cu. ft.) Cavity Enamel Colour	4,34 Black	
Rack Positions		
Oven Lights	3x20W Halogen	
HEATING ELEMENTS (@240V)		
Broil Upper Heating Element	3500 W	
Upper Auxiliary Element	1032 W	
Concealed Bake Lower Heating Element	3000 W	
Convection Element	2 x 1300 W	
OVEN ACCESSORIES		
Chromed Racks	2	
Enameled Broiler Pan (basin + anti splash)	1	
Telescopic Chromed Rack		1
DIMENSIONS/WEIGHT	29 - 5/8"	(754 mm)
Overall dim - Width Overall dim - Height	29 - 5/8" 50 - 3/4"	(1290 mm)
Overall dim - Depth	23 - 1/8"	(587 mm)
Cut-out - Width	28 - 3/8"	(722 mm)
Cut-out - Height (min)	50"	(1270 mm)
Cut-out - Depth (min)	24"	(610 mm)
Gross Weight	326 lbs	(148 kg)
POWER / RATINGS (208/240 V, 60 HZ)		
kW / Amps rating at 120-240V, 60Hz	7.50kW - 31.2A	
kW / Amps rating at 120-208V, 60Hz	6.30kW - 30.3A	
Power Cable	Conduit	
INSTRUCTIONS FOR USE		
Use & Care Manual / Installation Manual	EN, SP, FR	

fulgor-milano.us FULGOR MILANO