# 30" COMBI STEAM OVEN

700 SERIES OVEN



4

### F7MSCO30S1

CODE ID

œ	CREACTIVE COOKING SYSTEM
	Steam Cooking
	Steam Limescale Filter
<b>M</b>	Fingerprint-proof Stainless Steel
+++ CLEAN	Automatic Cleaning Programs
É	Meat Probe
	Stainless Steel Racks
	Multi-level Cooking
*	True Convection
цш.	AirFry

#### SPECIFICATIONS

#### FEATURES

3 in 1 Oven: Steam, Convection, and Combi-steam Stainless Interior with broiler Quick Access Menu Automatic Programs Meat Probe 240 Volt Connection Steam Generator

#### PERFORMANCE

12 Functions Automatic Cooking Pre-selected and customizable recipes (weight, temperature, cooking time) Steam System Combined Cooking Functions Steam Recovery Cycle CLEAN, assisted cleaning cycle for oven interior and steam circuit




This product meets ADA (Americans with Disabilities Act) requirements. Please check with your local municipality's codes and stipulations for additional details to ensure compliance.

## MATTEO

30" COMBI STEAM OVEN





CODE ID	30" COMBI STEAM OVEN F7MSCO30S1	
Series	70	00
Finish	Stainless Steel	
CONTROL PANEL		
Programming	MODULAR - Electronic	
Control Type	Dual Full Touch Keyboard	
Automatic Cooking	•	
Auto power off	•	
OVEN		
Туре	Steam Oven	
Interiors	Stainless Steel	
Pull-down Door	•	
MAIN FEATURES		
Total Capacity ( It )	39,9	
Tootal Capacity ( cu. ft. )	1,41	
Tangential cooling ventilation	•	
Total no. of modes	12	
PERFORMANCE Maximum cooking temperature	230°C / 446°F	
Automatic Cooking	230°C / 446°F	
Steam 210°F / 270°F	•	
Steam Injection 210°F	•	
Steam + Fan Assisted	•	
Assisted Cleaning (CLEAN)	•	
Power Output Grill (W)	1500	
Oven Lights	1x20W Halogen	
Broil Upper Heating Element	1500W (240V)	
Steamer	1500W (240V)	
Lower Element Wattage	300W (240V)	
Convection Element Wattage	2300W (240V)	
SAFETY		
Safety Door/ no. Panes of Glass	•/3	
Control Lock	•	
ACCESSORIES		
No. of Lights (20 W halogen)	· · · · · · · · · · · · · · · · · · ·	
Removable tank (liters / fl oz)	1.4 / 45	
No./Type of Gastronorm Trays	2 / Stainless Steel	
Grey Metal Flat/no. of Supports	1/1	
DIMENSIONS / WEIGHT		
Width in/mm	29 - 5/8"	754 mm
Height in/mm	18 - 5/8"	473 mm
Depht in/mm	21 - 3/4"	551 mm
Recess (LxHxP) in/mm	(21 - 3/4" x 17- 3/4" x 22")	(722 x 450 x 560 mm)
POWER / RATINGS	2.01/01 - 10.74	
KW/Amps rating at 120-240V, 60Hz	3.3kW - 13.7A	
KW/Amps rating at 120-208V, 60Hz	2.48kW - 11.9A	
Power Cord INSTRUCTIONS FOR USE	Cable + Conduit	
Use & Care Manual / Installation Manual	EN, SP, FR	