

600 Series 30" Dual Fuel Range

F6PDF304S1



Series	600	
	DUAL FUEL	
Size	30"	
Main Colour	SS	
Logo	•	
Stainless Steel Aestethics	Professional	

^		
Coo	kto	n
	NLU	u

o o o mo p	
Type	GAS
Cooking Surface	Black Enameled
Gas Type	NG (5") or LP (10")
Knobs	•
Gas Cooktop Features	
Electric Flame Ignition and Re-ignition	•
Flame out sensing	•
Top Mount Injectors	•
L.P. Conversion Kit	•
Dual Flame Brass Burner	•
Heavy Duty Cast Iron Grates	2
Pressure Regulator	•
Cooking Zones	4
Front Left	Dual Flame Burner
Power (Max/ Min) Natural Gas	18000 (BTU/h) - 5300W / 750 (BTU/h) - 220W
Power (Max/ Min) Propane	15000 (BTU/h) - 4400W / 750 (BTU/h) - 220W
Rear Left	Dual Flame Burner
Power (Max/ Min) Natural Gas	18000 (BTU/h) - 5300W / 750 (BTU/h) - 220W
Power (Max/ Min) Propane	15000 (BTU/h) - 4400W / 750 (BTU/h) - 220W
Front Middle	
Power (Max/ Min) Natural Gas	
Power (Max/ Min) Propane	
Rear Middle	
Power (Max/ Min) Natural Gas	
Power (Max/ Min) Propane	
Front Right (*)	Dual Flame Burner
Power (Max/ Min) Natural Gas	20000 or 18000 (BTU/h) - 5850 or 5300W / 750 (BTU/h) - 220W
Power (Max/ Min) Propane	15000 (BTU/h) - 4400W / 750 (BTU/h) - 220W
Rear Right	Dual Flame Burner
Power (Max/ Min) Natural Gas	18000 (BTU/h) - 5300W / 750 (BTU/h) - 220W
Power (Max/ Min) Propane	15000 (BTU/h) - 4400W / 750 (BTU/h) - 220W
(*) Maximum Power depends on the model	
()	



MILANO

Oven		
Туре		ELECTRIC PIRO
Oven Type		Multifunction 2 Fans (True Euro Convection)
Temperature Regulation		Electronic (max temp. 550°F/290°C)
Functions		
Pyrolitic Self-Clean with automatic door latch		•
True European Convection Bake (Multi level)		•
Convection Broil	X	•
Convection Roast	X	•
Pizza (Lower Convection)	人	•
Bake		•
Broil	***	•
Dehydrate		•
Thaw (Defrost)		•
Proof (Warm)		•
Keep warm (Warm Plus)	<u></u>	•
Oven Lights	<u></u>	•
Fast Preheat		•
Control Panel		
Control type		HAWK3TC - Electronic
Clock Display		White LED
Temperature Display		White LED
Function Display Commands		White LED 6 Heavy Duty Knobs / 6 Touch Keys
Language		English
Electric Oven Features		English
Preset/Last used temperature memory		•
Preheat bar (25%, 50%, 75%, 100%)		•
Automatic Fast Preheat		•
Child Door Lock		•
Commands Lock		•
Sabbath mode		•
12/24 hour clock format °C/°F		•
Oven Door(s)		
Oven Glass Window		Deep Embossed Window
Door Cooling System		4 Pane Heat Resistant Glass
soft closing system Door Hinges		Heavy Duty Steady Tilt
Handle Style		Stainless Steel Tube d30mm, Metal terminals
Oven Cavity		Ctalinood Ctool Fabb accinin, Motal tollimate
Gross Capacity (cuft)		4.4
Usable Capacity (cuft)		4.1
Cavity Enamel Colour		Black
Rack Positions		6
Oven Lights		3x20W Halogen
Heating Element		
Broil Upper Heating Element		3500 W (240V)
Upper Auxiliary Element Wattage		1032W (240V)
Concealed Bake Lower Heating Element		3000 W (240V)
Convection Element Wattage		2x1300 W (240V)
Oven Accessories		
Chromed racks		2
Enameled Grill set (basin + anti splash)		1
Telescopic chromed rack		1
Meat probe Dimensions		
Overall dim - width		29 3/4" (758mm)
C.SIGH WHITE WINGE		20 0/ 4 (700mm)



Height min/max	36 3/8" (925mm) / 38 1/2" (977mm)
Overall dim - depth	29 3/4" (756mm)
Power / Ratings (208/240 V, 60 Hz)	
KW/Amps rating at 120-240V, 60Hz	3.84kW - 16.9A
KW/Amps rating at 120-208V, 60Hz	3.54kW - 17.5A
Cable + Plug	Nema 14-50P
INSTRUCTIONS FOR USE	
Use & Care Manual	EN, SP, FR
Installation Manual	EN, SP, FR