

600 Series 30" Induction Range

F6PIR304S1



Series	600 FULL ELECTRIC
Size Main Colour	30" SS
Logo	•
Stainless Steel Aestethics	Professional

Cooktop

e e e mel	
Туре	INDUCTION
Cooking Surface	Ceramic Glass
Knobs	•
Induction Special Features	
Pot Detection System	•
Child lock function	•
Cooling fan system	•
Failure Codes indication	•
Induction Control Features	
Knob for power setting (illuminated)	
Power levels	1 to 9
Digital display for power level indication Molting Function 142° F (45° C (incide the net 108° F (42° C)	•
Melting Function 113°F / 45°C (inside the pot 108°F / 42°C) Warming Function 158°F / 70°C (inside the pot 149°F / 65°C)	•
Booster/Fast boil function for each zone	
Heat up time automatic	•
Residual heat indication	•
Cooking Zones	4
Front Left	Inductor 9" (230mm)
Power L9	2300W
Booster	3700W
Rear Left	Inductor 6" ½ (165mm)
Power L9	1400W
Booster	2200W
Front Middle	220011
Power L9	
Booster	
Rear Middle	
Power L9	
Booster	
Front Right	Inductor 7" 3/4 (200mm)
Power L9	1850W
Booster	3000W
Rear Right	Inductor 7" 3/4 (200mm)
Power L9	1850W
Booster	3000W

FULGOR MILANO

Oven		
Туре		ELECTRIC PIRO
Oven Type		Multifunction 2 Fans (True Euro Convection)
Temperature Regulation Functions		Electronic
Pyrolitic Self-Clean with automatic door latch		•
True European Convection Bake (Multi level)		•
		·
Convection Broil	X	•
Convection Roast	X	•
Pizza (Lower Convection)	7	•
Bake		•
Broil		•
Dehydrate	$\overline{}$	•
Thaw (Defrost)		•
Proof (Warm)		•
Keep warm (Warm Plus)	<u> </u>	•
Oven Lights	`? -	•
Fast Preheat		•
Control Panel		
Control type Clock Display		HAWK3TC - Electronic White LED
Temperature Display		White LED
Function Display		White LED
Commands		6 Heavy Duty Knobs / 6 Touch Keys
Language Electric Oven Features		English / Frensh / Spanish
Preset/Last used temperature memory		•
Preheat bar (25%, 50%, 75%, 100%)		•
Automatic Fast Preheat		•
Child Door Lock		•
Commands Lock		•
Sabbath mode		•
12/24 hour clock format °C/°F		•
Oven Door(s)		
Oven Glass Window		Deep Embossed Window
Door Cooling System		4 Pane Heat Resistant Glass
soft closing system Door Hinges		● Heavy Duty Steady Tilt
Handle Style		Stainless Steel Tube d30mm, Pro Style
Oven Cavity		
Gross Capacity (cuft)		4.4
Usable Capacity (cuft)		4.1
Cavity Enamel Colour		Black
Rack Positions		6
Oven Lights		3x20W Halogen
Heating Element		
Broil Upper Heating Element		3500 W (240V)
Upper Auxiliary Element Wattage		1032W (240V)
Concealed Bake Lower Heating Element		3000 W (240V)
Convection Element Wattage		2x1300 W (240V)
Oven Accessories		
Chromed racks		2
Enameled Grill set (basin + anti splash)		1
Telescopic chromed rack		1
Meat probe		1
Dimensions Overall dim - width		20.3//" (759mm)
		29 3/4" (758mm)

FULGOR		
MILANO		
Height min/max	36 3/8" (925mm) / 38 1/2" (977mm)	
Overall dim - depth	29 3/4" (756mm)	
Power / Ratings (208/240 V, 60 Hz)		
KW/Amps rating at 120-240V, 60Hz	11kW - 45.8A	
KW/Amps rating at 120-208V, 60Hz	10kW - 48.5A	
Cable + Plug	Nema 14-50P	
INSTRUCTIONS FOR USE		
Use & Care Manual	EN, SP, FR	
Installation Manual	EN, SP, FR	