

FULGOR

MILANO









400 Series 30" Self Cleaning Single Wall Oven

F4SP30S1

BAR CODE (EAN 13)

801980101169 8



Series		400
Type		PYRO
Size		30"x30"
Colour		SS
Oven Type		Multifunction (True Euro Convection)
Temperature Regulation		Electronic
Functions		
Pyrolytic Self-Clean with automatic door latch		•
True European Convection Bake		•
Convection Broil		•
Bake		•
Broil		•
Thaw (Defrost)		•
Convection Bake (without ring element)		•
Oven Lights		•
Control Panel		
Control type		Athena XS - Electronic
Clock/Timer Display		Red LED
Commands		2 Knobs
Knobs type		MGH "U" PLASTIC
Language		English
Special Features		
Child Door Lock		
Sabbath mode		
12/24 hour clock format		
°C/°F		•
Oven Door(s)		
Oven Glass Window		Large See Through Glass
Door Cooling System		4 Pane Heat Resistant Glass
Door Hinges		Heavy Duty Steady Tilt
Handle Style		Tubular Steel
Oven Cavity		
Net Capacity (cuft)		4.3
Cavity Enamel Colour		Black
Rack Positions		6
Oven Lights		3x20W Halogen
Broil Upper Heating Element		3100 W (240V)
Upper Auxiliary Element Wattage		1032W (240V)
Concealed Bake Lower Heating Element		1400 W (240V)
Lower Auxiliary Element Wattage		600W (240V)
Convection Element Wattage		2500 W (240V)
Accessories		

FULGOR

MILANO

Chromed racks	2
Enameled Grill set (basin + anti splash)	1
Telescopic chromed rack	Optional
Dimensions/Weight - (In or Lbs)	
Overall dim - width	29 11/16" (754mm)
Overall dim - height	27-7/8" (707mm)
Overall dim - depth	24" (610mm)
Cutout - width	28 7/16" (722mm)
Cutout - height (min)	27-1/4" (692mm)
Cutout - depth (min)	23-1/4" (590mm)
Power / Ratings (208/240 V, 60 Hz)	
KW/Amps rating at 240V, 60Hz	3.7kW - 16.1Amps
KW/Amps rating at 208V, 60Hz	3.49kW - 17.1Amps
Cable + Conduit	•
INSTRUCTIONS FOR USE	
Use & Care Manual	EN, SP, FR
Installation Manual	EN, SP, FR