

Index

Single & Double Ovens **600 SERIES** 6 - 17

Single Ovens **400 SERIES** 18 - 25

Single Ovens 100 SERIES 26 - 35

Accesories & Technical Data 36 - 41



Induction Cooktops 600 SERIES 44 - 51

Radiant Cooktops 600 SERIES 52 - 59

Radiant Cooktops **300 SERIES** 60 - 69

> Gas Cooktops **400 SERIES** 70 - 79

> Gas Cooktops **300 SERIES** 80 - 87

Accesories & Technical Data 88 - 94







Brand

1949	Fulgor	is	founded	as	а	coal-stove	factory
------	--------	----	---------	----	---	------------	---------

- Fulgor first produces freestanding gas kitchens
- Meneghetti is founded as a tool -and metalpressing factory
- Fulgor's built-in cooktops are created
- Fulgor's electric cooktops first produced
- First production of Meneghetti's cooktops
- Creation of Fulgor's first glass cooktop
- First European production of Fulgor's pyrolytic ovens
- First European production of Fulgor's pyrolytic ovens for the North American market
- First production of Meneghetti's ovens
- Fulgor invents world's first dual-flame burner
- Meneghetti becomes first European cooktop manufacturer
- First production of Meneghetti's cooker hoods

Acquisition of Fulgor by Meneghetti S.p.A.

Fulgor celebrates 60 years; Fulgor-Milano is born

Meneghetti and Fulgor move forward, bringing time-honored tradition together with the latest technologies



Ovens

True **Italian design** must be as exquisite in appearance as it is in performance.

Beauty infused with intelligence; art informed by craftsmanship; form integrated with function. At Fulgor Milano, we design extraordinary appliances for everyday living – enriching **how** people live in the spaces **where** they live. Our award-winning designs are inspired by our strong passion for food, family, friends and fine living. Our innovative line of appliances and kitchen products combine the quality, reliability and affordability that families demand with a refined elegance and understated sophistication that's unmatched at any price. Sleek surfaces, clean lines and intuitive controls transform kitchens and dining areas into open, stylish spaces that draw crowds but never feel crowded.







600 Series Single & Double Ovens

A modern workhorse that marries style and innovation. With many preset cooking functions, the 600 series ovens help you prepare your meals with efficiency and ease. Child safety locks and cool touch doors ensure you and your family will be protected from high temperatures while cooking and during the self clean cycle. This series offers the fastest and most versatile self clean mode available, a dual convection system for high quality performance and an oversized oven space for big results. With 5 broil levels and a selection of accessories available to you, the 600 series ovens deliver both luxury and convenience.

SAFETY FEATURE: COOL DOOR

Rest assured, your hands are safe with us. Our cool-door technology has a proven guarantee

EXTRA LARGE CAVITY

Imagine the efficiency of being able to use multiple levels of a huge oven at once. We consider it an advantage, don't you?

TELESCOPIC RACK

Our fully retractable telescopic rack makes accessibility to your cooking more convenient

MEAT PROBE

Precise cooking performance with our meat probe, available in our single ovens and upper cavity of the double ovens



DIMENSIONS

30"x 30" single oven



30"x 30" double oven



SYMBOLS







F6SP30S1

30" Dual fan Multifunction self-clean oven

- Stainless steel
- Electronic controls with intuitive and easy access to
- the oven's numerous cooking functions
- Pyrolytic Self-Clean with automatic door latch
- Electronic temperature regulation
- 12 cooking functions including "pizza" function
- 3x20W halogen lighting
- English language

Special functions:

- Preset/Last used temperature memory
- Preheat bar (25%, 50%, 75%, 100%)
- Automatic Fast Preheat
- Keyboard Lock
- Child door lock
- Sabbath mode
- 12/24 hours clock format
- °C/F° degree unit

Delivered accessories:

- 2 chromed racks
- Enameled grill set (basin+anti-splash)
- Meat probe
- Telescopic chromed rack

F6SP30B1

30" Dual fan Multifunction Self-clean oven

- Black Colour
- Electronic controls with intuitive and easy access to
- the oven's numerous cooking functions
- Pyrolytic Self-Clean with automatic door latch
- Electronic temperature regulation
- 12 cooking functions including "pizza" function
- 3x20W halogen lighting
- English language

Special functions:

- Preset/Last used temperature memory
- Preheat bar (25%, 50%, 75%, 100%)
- Automatic Fast Preheat
- Keyboard Lock
- Child door lock
- Sabbath mode
- 12/24 hours clock format
- °C/F° degree unit

Delivered accessories:

- 2 chromed racks
- Enameled grill set (basin+anti-splash)
- Meat probe
- Telescopic chromed rack

Series 600





F6SP30W1

30" Dual fan Multifunction self-clean oven

- White Colour
- Electronic controls with intuitive and easy access to
- the oven's numerous cooking functions
- Pyrolytic Self-Clean with automatic door latch
- Electronic temperature regulation
- 12 cooking functions including "pizza" function
- 3x20W halogen lighting
- English language

Special functions:

- Preset/Last used temperature memory
- Preheat bar (25%, 50%, 75%, 100%)
- Automatic Fast Preheat
- Keyboard Lock
- Child door lock
- Sabbath mode
- 12/24 hours clock format
- °C/F° degree unit

Delivered accessories:

- 2 chromed racks
- Enameled grill set (basin+anti-splash)
- Meat probe
- Telescopic chromed rack





Upper Oven
Lower Oven

F6DP30S1

30" Dual fan Multifunction self-clean Double oven

Stainless steel

Electronic controls with intuitive and easy access to the oven's numerous cooking functions

- Pyrolytic Self-Clean with automatic door latch
- Electronic temperature regulation
- 12 cooking functions including "pizza" function
- 3x20W halogen lighting for each cavity
- English language

Special functions:

- Preset/Last used temperature memory
- Preheat bar (25%, 50%, 75%, 100%)
- Automatic Fast Preheat
- Keyboard Lock
- Child door lock
- Sabbath mode
- 12/24 hours clock format
- °C/F° degree unit

Delivered upper oven accessories:

- 2 chromed racks
- Enameled grill set(basin+anti-splash)
- Meat probe
- Telescopic chromed rack

Delivered lower oven accessories:

- 2 chromed racks
- Enameled grill set(basin+anti-splash)
- Telescopic chromed rack





F6DP30B1

30" Dual fan Multifunction self-clean Double oven

- Black Colour
- Electronic controls with intuitive and easy access to
- the oven's numerous cooking functions
- Pyrolytic Self-Clean with automatic door latch
- Electronic temperature regulation
- 12 cooking functions including "pizza" function
- 3x20W halogen lighting for each cavity
- English language

Special functions:

- Preset/Last used temperature memory
- Preheat bar (25%, 50%, 75%, 100%)
- Automatic Fast Preheat
- Keyboard Lock
- Child door lock
- Sabbath mode
- 12/24 hours clock format
- °C/F° degree unit

Delivered upper oven accessories:

- 2 chromed racks
- Enameled grill set(basin+anti-splash)
- Meat probe
- Telescopic chromed rack

Delivered lower oven accessories:

- 2 chromed racks
- Enameled grill set(basin+anti-splash)
- Telescopic chromed rack



			<u> 111 </u>	Oven
I I I	<u>, </u>		<u> </u>	Lower Oven

F6DP30W1

30" Dual fan Multifunction self-clean Double oven

White Colour

Electronic controls with intuitive and easy access to the oven's numerous cooking functions

- Pyrolytic Self-Clean with automatic door latch
- Electronic temperature regulation
- 12 cooking functions including "pizza" function
- 3x20W halogen lighting for each cavity
- English language

Special functions:

- Preset/Last used temperature memory
- Preheat bar (25%, 50%, 75%, 100%)
- Automatic Fast Preheat
- Keyboard Lock
- Child door lock
- Sabbath mode
- 12/24 hours clock format
- °C/F° degree unit

Delivered upper oven accessories:

- 2 chromed racks
- Enameled grill set(basin+anti-splash)
- Meat probe
- Telescopic chromed rack

Delivered lower oven accessories:

- 2 chromed racks
- Enameled grill set(basin+anti-splash)
- Telescopic chromed rack





400 Series Single Ovens

A sleek European design and flush installation, the 400 series oven shares the same body and soul of the 600 series oven, offering many of the same professional features while providing tremendous value. Available only in a single oven configuration, this series offers an oversized oven capacity, multi pass broil, European convection, concealed bake elements and 8 baking functions; all of which are controlled by an easy to use and extremely reliable control system.

The Athena XS control gives the home chef complete control via easy to use and intuitive controls making this oven a great choice as a primary or secondary oven for a variety of kitchen designs and applications.

SAFETY FEATURE: COOL DOOR

Rest assured, your hands are safe with us. Our cool-door technology has a proven guarantee

EXTRA LARGE CAVITY

Imagine the efficiency of being able to use multiple levels of a huge oven at once. We consider it an advantage, don't you?

TELESCOPIC RACK

Our fully retractable telescopic rack enhances your cooking experience (100%)



DIMENSIONS

30"x 30" single oven



SYMBOLS





True European Convection Bake

Convection Broil







Thaw (Defrost)



Convection bake (without ring element)



Oven Lights









F4SP30S1

30" Multifunction self-clean oven

- Stainless steel
- Electronic controls with intuitive and easy access to
- the oven's numerous cooking functions
- Pyrolytic Self-Clean
- Electronic temperature regulation
- 8 cooking functions
- 3x20W halogen lighting
- English language

Special functions:

- 12 hours clock format (AM/PM)
- °C/F° degree unit
- Preheat indication

Delivered accessories:

- 2 chromed racks
- Enameled grill set (basin+anti-splash)

Optional accessories:

Telescopic chromed rack

F4SP30B1

30" Multifunction self-clean oven

- Black Colour
- Electronic controls with intuitive and easy access to
- the oven's numerous cooking functions
- Pyrolytic Self-Clean
- Electronic temperature regulation
- 8 cooking functions
- 3x20W halogen lighting
- English language

Special functions:

- 12 hours clock format (AM/PM)
- °C/F° degree unit
- Preheat indication

Delivered accessories:

- 2 chromed racks
- Enameled grill set (basin+anti-splash)

Optional accessories:

Telescopic chromed rack











F4SP30W1

30" Multifunction self-clean oven

- White Colour
- Electronic controls with intuitive and easy access to
- the oven's numerous cooking functions
- Pyrolytic Self-Clean
- Electronic temperature regulation
- 8 cooking functions
- 3x20W halogen lighting
- English language

Special functions:

- 12 hours clock format (AM/PM)
- °C/F° degree unit
- Preheat indication

Delivered accessories:

- 2 chromed racks
- Enameled grill set (basin+anti-splash)

Optional accessories:

Telescopic chromed rack





100 Series Single Ovens

A standard-setting series with first-class performance. Many preset cooking functions help you prepare your meals with efficiency and ease. The fastest and most versatile self-clean mode available, featuring automatic door-latch system.

Child safety locks and cool-touch doors protect you and your family from high temperatures while cooking and during the self-clean cycle. 5 broil levels. Smaller cavity dimensions fit in any kitchen and reduce energy consumption while providing ample space for all your cooking needs.

A selection of accessories is available for your convenience.

HALOGEN LIGHTS

Two 20-watt halogen bulbs provide plenty of light for easy viewing

CONCEALED BAKE ELEMENTS

The concealed heating element and large broiler make it possible to cook and save energy at the same time

NEW ITALIAN DESIGN

Combining straightforwardness and ease of use with a clean Italian design, our control panel does not require an engineer to operate



DIMENSIONS

30"x 24" single oven



24"x 24" single oven



SYMBOLS



V



Convection Broil

Bake









(Defrost)



Dehydrate





Convection bake (without ring element)

Pizza (Lower Convection)



Oven Lights

Convection Roast









F1SP30S2

30" Multifunction self-clean oven

- Stainless colour
- Electronic controls
- Rounded handle
- Pyrolytic Self-Clean with automatic door latch
- Electronic temperature regulation
- 7 cooking functions
- 2X20W halogen lighting
- English language

Special functions:

- Manual fast pre-heat
- Child door lock
- Sabbath mode
- 12/24 hours clock format
- °C/°F degree unit

Delivered accessories:

- 2 chromed racks
- Enameled grill set (basin+anti-splash)

Optional accessories:

Telescopic chromed rack

F1SP30S1

30" Multifunction self-clean oven

- Stainless colour
- Electronic controls
- Pyrolytic Self-Clean
- Electronic temperature regulation
- 8 cooking functions
- 2X20W halogen lighting
- English language

Special functions:

- 12 hours clock format (AM/PM)
- °C/F° degree unit
- Preheat indication

Delivered accessories:

- 2 chromed racks
- Enameled grill set (basin+anti-splash)

Optional accessories:

Telescopic chromed rack

Series 100









F1SP24S1

24" Multifunction self-clean oven

- Electronic controls
- Pyrolytic Self-Clean
- Electronic temperature regulation
- 8 cooking functions
- 1X20W halogen lighting
- English language

Special functions:

- 12 hours clock format (AM/PM)
- °C/F° degree unit
- Preheat indication

Delivered accessories:

- 2 chromed racks
- Enameled grill set (basin+anti-splash)

Optional accessories:

Telescopic chromed rack

F1SM30S1

30" Stainless steel Convection oven

- Time programmer
- Thermostat temperature regulation
- 8 cooking functions
- 2X20W halogen lighting
- English language

Delivered accessories:

- 2 chromed racks
- Enameled broil pan only (Grill optional)

Series 100




Series 100





F1SM24S1

24" Stainless steel Convection oven

- Time programmer
- Thermostat temperature regulation
- 8 cooking functions
- 1X20W halogen lighting
- English language

Delivered accessories:

- 2 chromed racks
- Enameled broil pan only (Grill optional)

Accesories & Technical Data Single & Double Ovens

Useful accessories will help you customize your appliance while giving you ease, efficiency and successful results in your cooking.

The telescopic rack is an indispensable addition to every modern oven.

OVENS ACCESSORIES

37

TELESCOPIC RACKS

FMTR124 Telescopic rack kit "100" Series 24" Stainless Steel/Chrome

FMTR130 Telescopic rack kit "100" Series 30" Stainless Steel/Chrome

FMTR630 Telescopic rack kit "400" and "600" Series

30" Stainless Steel/Chrome





MODEL	F6SP30S1	F6SP30B1	F6SP30W1	
Гуре	PYRO	PYRO	PYRO	
ize	30"×30"	30"x30"	30"x30"	
Iolour	SS	BLACK	WHITE	
tainless Steel Aestethics	Embossed window profile with bended edges			
Dven Type	Multifunction 2 Fans (True Euro Conv.)	Multifunction 2 Fans (True Euro Conv.)	Multifunction 2 Fans (True Euro Conv	
Temperature Regulation	Electronic	Electronic	Electronic	
Control Panel				
Control type	HAWK3TC - Electronic	HAWK3TC - Electronic	HAWK3TC - Electronic	
Ilock/Timer Display	Blue Backlight	Blue Backlight	Blue Backlight	
emperature Display	Red LED	Red LED	Red LED	
unction Display	Red LED	Red LED	Red LED	
Iommands	2 Knobs / 6 Touch Keys	2 Knobs / 6 Touch Keys	2 Knobs / 6 Touch Keys	
Knobs type	MGH "U" PLASTIC	MGH "U" PLASTIC	MGH "U" PLASTIC	
anguage	English	English	English	
pecial Features				
reset/Last used temperature memory	X	X	X	
Preheat bar (25%, 50%, 75%, 100%)	X	X	Х Х	
utomatic Fast Preheat	× ×	× ×	X	
Thild Door Lock	×	^ X	× X	
	× ×	^ X	Х	
Commands Lock	X	X X	X X	
abbath mode				
2/24 hours clock format	X	X	X	
C/°F degree unit	Х	X	Х	
Oven Door(s)				
Oven Glass Window	Large See Through Glass	Large See Through Glass	Large See Through Glass	
Door Cooling System	4 Pane Heat Resistant Glass	4 Pane Heat Resistant Glass	4 Pane Heat Resistant Glass	
Door Hinges	Heavy Duty Steady Tilt	Heavy Duty Steady Tilt	Heavy Duty Steady Tilt	
landle style	Stainless Steel Tube d25mm, Plastic terminals	Stainless Steel Tube d25mm, Plastic terminals	Stainless Steel Tube d25mm, Plastic term	
Oven Cavity				
let Capacity (cbft)	4.1	4.1	4.1	
Cavity Enameling Colour	Grey	Grey	Grey	
Rack Positions	6	6	6	
Oven Lights	3x20W Halogen	3x20W Halogen	3x20W Halogen	
Broil Upper Heating Element	3500 W (240V)	3500 W (240V)	3500 W (240V)	
Jpper Auxiliary Element Wattage	1032W (240V)	1032W (240V)	1032W (240V)	
Concealed Bake Lower Heating Element	3000 W (240V)	3000 W (240V)	3000 W (240V)	
Convection Element Wattage	2x1300 W (240V)	2x1300 W (240V)	2x1300 W (240V)	
Oven Accessories				
hromed racks	2	2	2	
Enameled Grill set (basin + anti splash)	1	1	1	
elescopic chromed rack	1	1	1	
Aeat probe	1	1	1	
Dimensions/Weight - (In or Lbs)	1 	I	1	
•	20 11/16" (75/mm)	20 11/16" /7E /mm)	20 11/16" (75 4	
Overall dim - width	29 11/16" (754mm)	29 11/16" (754mm)	29 11/16" (754mm)	
Overall dim - height	27-7/8" (707mm)	27-7/8" (707mm)	27-7/8" (707mm)	
Overall dim - depth	24" (610mm)	24" (610mm)	24" (610mm)	
utout - width	28 7/16" (722mm)	28 7/16" (722mm)	28 7/16" (722mm)	
utout - height (min)	27-1/4" (692mm)	27-1/4" (692mm)	27-1/4" (692mm)	
Cutout - depth (min)	23-1/4" (590mm)	23-1/4" (590mm)	23-1/4" (590mm)	
ower / Ratings (208/240 V, 60 Hz)				
W/Amps rating at 240V, 60Hz	3.84kW - 16.9Amps	3.84kW - 16.9Amps	3.84kW - 16.9Amps	
W/Amps rating at 208V, 60Hz	3.54kW - 17.5Amps	3.54kW - 17.5Amps	3.54kW - 17.5Amps	
Cable + Conduit	Х	Х	Х	
nstructions for use				
Instructions for use Use & Care Manual	EN, SP, FR	EN, SP, FR	EN, SP, FR	





MODEL	F6DP30S1	F6DP30SB1	F6DP30W1	
ype	PYRO	PYRO	PYRO	
ize	30"×30"	30"x30"	30"×30"	
olour	SS	BLACK	WHITE	
tainless Steel Aestethics	Embossed window profile with bended edges			
Oven Type	Both Multifunction 2 Fans (True Euro Conv.)	Both Multifunction 2 Fans (True Euro Conv.)	Both Multifunction 2 Fans (True Euro Conv	
emperature Regulation	Electronic	Electronic	Electronic	
Control Panel			-	
Control type	HAWK3TC - Electronic	HAWK3TC - Electronic	HAWK3TC - Electronic	
lock/Timer Display	Blue Backlight	Blue Backlight	Blue Backlight	
emperature Display	Red LED	Red LED	Red LED	
unction Display	Red LED	Red LED	Red LED	
iommands	2 Knobs / 6 Touch Keys	2 Knobs / 6 Touch Keys	2 Knobs / 6 Touch Keys	
inobs type	MGH "U" PLASTIC	MGH "U" PLASTIC	MGH "U" PLASTIC	
anguage	English	English	English	
pecial Features	English	English	English	
reset/Last used temperature memory	X	X	X	
reheat bar (25%, 50%, 75%, 100%)	×	×	X	
utomatic Fast Preheat	× ×	× ×	Х Х	
hild Door Lock	^ X	× ×	X X	
	×		X	
ommands Lock abbath mode	× ×	X	Х Х	
		X		
2/24 hours clock format	X	X	X	
Z/°F degree unit	X	X	X	
Oven Door(s)				
Iven Glass Window	Large See Through Glass	Large See Through Glass	Large See Through Glass	
Door Cooling System	4 Pane Heat Resistant Glass	4 Pane Heat Resistant Glass	4 Pane Heat Resistant Glass	
Door Hinges	Heavy Duty Steady Tilt	Heavy Duty Steady Tilt	Heavy Duty Steady Tilt	
landle style	Stainless Steel Tube d25mm, Plastic terminals	Stainless Steel Tube d25mm, Plastic terminals	Stainless Steel Tube d25mm, Plastic termina	
Oven Cavity				
let Capacity (cbft)	4.1	4.1	4.1	
avity Enameling Colour	Grey	Grey	Grey	
ack Positions	6	6	6	
)ven Lights	3x20W Halogen	3x20W Halogen	3x20W Halogen	
roil Upper Heating Element	3500 W (240V)	3500 W (240V)	3500 W (240V)	
Ipper Auxiliary Element Wattage	1032W (240V)	1032W (240V)	1032W (240V)	
oncealed Bake Lower Heating Element	3000 W (240V)	3000 W (240V)	3000 W (240V)	
onvection Element Wattage	2x1300 W (240V)	2x1300 W (240V)	2x1300 W (240V)	
Oven Accessories				
hromed racks	2 per cavity	2 per cavity	2 per cavity	
nameled Grill set (basin + anti splash)	1 per cavity	1 per cavity	1 per cavity	
elescopic chromed rack	1 per cavity	1 per cavity	1 per cavity	
1eat probe	Upper Oven Only	Upper Oven Only	Upper Oven Only	
)imensions/Weight - (In or Lbs)				
)verall dim - width	29 11/16" (754mm)	29 11/16" (754mm)	29 11/16" (754mm)	
verall dim - height	50 13/16" (1290mm)	50 13/16" (1290mm)	50 13/16" (1290mm)	
verall dim - depth	24" (610mm)	24" (610mm)	24" (610mm)	
utout - width	28 7/16" (722mm)	28 7/16" (722mm)	28 7/16" (722mm)	
utout - height (min)	49 3/4" (1264mm)	49 3/4" (1264mm)	49 3/4" (1264mm)	
utout - depth (min)	23 1/4" (590mm)	23 1/4" (590mm)	23 1/4" (590mm)	
ower / Ratings (208/240 V, 60 Hz)				
W/Amps rating at 240V, 60Hz	7.68kW - 33.8Amps	7.68kW - 33.8Amps	7.68kW - 33.8Amps	
W/Amps rating at 208V, 60Hz	6.48kW - 32.4Amps	6.48kW - 32.4Amps	6.48kW - 32.4Amps	
able + Conduit	X	X	X	
	Λ	A	Λ	
nstructions for use Jse & Care Manual	EN, SP, FR	EN, SP, FR	EN, SP, FR	





MODEL	F4SP30S1	F4SP30B1	F4SP30W1	
Туре	PYRO	PYRO	PYRO	
Size	30"x30"	30"×30"	30"×30"	
Colour	SS	BLACK	WHITE	
)ven Type	Multifunction (True Euro Conv.)	Multifunction (True Euro Conv.)	Multifunction (True Euro Conv.)	
emperature Regulation	Electronic	Electronic	Electronic	
ontrol Panel				
ontrol type	Athena XS - Electronic	Athena XS - Electronic	Athena XS - Electronic	
lock/Timer Display	Red LED	Red LED	Red LED	
ommands	2 Knobs	2 Knobs	2 Knobs	
nobs type	MGH "U" PLASTIC	MGH "U" PLASTIC	MGH "U" PLASTIC	
anguage	English	English	English	
pecial Features			5	
lanual Fast Preheat				
hild Door Lock				
abbath mode				
2/24 hours clock format		-		
C/F degree unit	Х	Х	Х	
ven Door(s)	N.	TA AND A	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	
ven Glass Window	Large See Through Glass	Large See Through Glass	Large See Through Glass	
oor Cooling System	4 Pane Heat Resistant Glass	4 Pane Heat Resistant Glass		
oor Hinges	Heavy Duty Steady Tilt	Heavy Duty Steady Tilt	4 Pane Heat Resistant Glass Heavy Duty Steady Tilt	
andle style	Tubular Steel	Tubular Steel	Tubular Steel	
ven Cavity				
et Capacity (cbft)	4.3	4.3	4.3	
avity Enameling Colour	Grey	Grey	Grey	
ack Positions	6	6	6	
ven Lights	3x20W Halogen	3x20W Halogen	3x20W Halogen	
roil Upper Heating Element	3100 W (240V)	3100 W (240V)	3100 W (240V)	
pper Auxiliary Element Wattage	1032W (240V)	1032W (240V)	1032W (240V)	
oncealed Bake Lower Heating Element	1400 W (240V)	1400 W (240V)	1400 W (240V)	
ower Auxiliary Element Wattage	600W (240V)	600W (240V)	600W (240V)	
onvection Element Wattage	2500 W (240V)	2500 W (240V)	2500 W (240V)	
ven Accessories		2	2	
hromed racks	2	2	2	
nameled Grill set (basin + anti splash)	1	1	1	
elescopic chromed rack	Optional	Optional	Optional	
imensions/Weight - (In or Lbs)		2014/07/251	20.44/4/5//75/	
verall dim - width	29 11/16" (754mm)	29 11/16" (754mm)	29 11/16" (754mm)	
verall dim - height	27-7/8" (707mm)	27-7/8" (707mm)	27-7/8" (707mm)	
verall dim - depth	24" (610mm)	24" (610mm)	24" (610mm)	
utout - width	28 7/16" (722mm)	28 7/16" (722mm)	28 7/16" (722mm)	
utout - height (min)	27-1/4" (692mm)	27-1/4" (692mm)	27-1/4" (692mm)	
utout - depth (min)	23-1/4" (590mm)	23-1/4" (590mm)	23-1/4" (590mm)	
ower / Ratings (208/240 V, 60 Hz)				
W/Amps rating at 240V, 60Hz	3.7kW - 16.1Amps	3.7kW - 16.1Amps	3.7kW - 16.1Amps	
W/Amps rating at 208V, 60Hz	3.49kW - 17.1Amps	3.49kW - 17.1Amps	3.49kW - 17.1Amps	
able + Conduit	X	X	X	
nstructions for use				
se & Care Manual	EN, SP, FR	EN, SP, FR	EN, SP, FR	
nstallation Manual	EN, SP, FR	EN, SP, FR	EN, SP, FR	

 -	-	 -

MODEL	F1SP30S2	F1SP30S1	F1SP24S1	F1SM30S1	F1SM24S1
Туре	PYRO	PYRO	PYRO	NORMAL	NORMAL
Size	30"x24"	30"x24"	24"	30"x24"	24"
Colour	SS	SS	SS	SS	SS
Oven Type	Multifunction (True Euro Conv.)	Multifunction (True Euro Conv.)	Multifunction (True Euro Conv.)	Convection	Convection
Temperature Regulation	Electronic	Electronic	Electronic	Thermostat	Thermostat
Control Panel					
Control type	HAWK2 - Electronic	Athena XS - Electronic	Athena XS - Electronic	Time Programmer	Time Programmer
Clock/Timer Display	Blue/Red LED	Red LED	Red LED	Red Led	Red Led
Commands	2 Knobs / 8 Buttons	2 Knobs	2 Knobs	2 Knobs / 6 Buttons	2 Knobs / 6 Buttons
Knobs type	MGH "U" PLASTIC	MGH "U" PLASTIC	MGH "U" PLASTIC	MGH "U" PLASTIC	MGH "U" PLASTIC
Language	English	English	English	English	English
Special Features					
Manual Fast Preheat	X				
Child Door Lock	Х				
Sabbath mode	Х				
12/24 hours clock format	Х				
°C/°F degree unit	X	Х	Х		
Oven Door(s)					
Oven Glass Window	Large See Through Glass	Large See Through Glass	Large See Through Glass	Large See Through Glass	Large See Through Glass
Door Cooling System	4 Pane Heat Resistant Glass	4 Pane Heat Resistant Glass	4 Pane Heat Resistant Glass	3 Pane Heat Resistant Glass	3 Pane Heat Resistant Glass
Door Hinges	Heavy Duty Steady Tilt	Heavy Duty Steady Tilt	Heavy Duty Steady Tilt	Heavy Duty Steady Tilt	Heavy Duty Steady Tilt
Handle style	Rounded Stainless Steel	Tubular Steel	Rounded Stainless Steel	Tubular Steel	Tubular Steel
Oven Cavity	nounded stanness steel				
Net Capacity (cbft)	2.78	2.78	2.2	2.78	2.2
Cavity Enameling Colour	Grey	Grey	Grey	Grey	Grey
Rack Positions	4	4	4	4	4
Oven Lights	2x20W Halogen	2x20W Halogen	1x20W Halogen	2x20W Halogen	1x20W Halogen
Broil Upper Heating Element	3500 W (240V)	3100 W (240V)	2000 W (240V)	3100 W (240V)	2000W (240V)
Upper Auxiliary Element Wattage	1032W (240V)	1032W (240V)	1000W (240V)	1032W (240V)	1000W (240V)
Concealed Bake Lower Heating Element		1400 W (240V)	1200W (240V)	2100 W (240V)	1200W (240V)
Lower Auxiliary Element Wattage	5000 (2407)	600W (240V)	400W (240V)	2100 11 (2401)	120000 (2400)
Convection Element Wattage	2500 W (240V)	2500 W (240V)	2500 W (240V)		
Oven Accessories	2300 11 (2401)	2300 11 (2401)	2300 W (240V)		
Chromed racks	2	2	2	2	2
Enameled Grill set (basin + anti splash)	1	1	1	1 (basin only)	1 (basin only)
Telescopic chromed rack	I	Optional	Optional	r (Dasiri Orliy)	T (Dasii T Offiy)
Dimensions/Weight - (In or Lbs)		Optional	Optional		
Overall dim - width	29 3/8" (745mm)		23 7/16" (595mm)	29 3/8" (745mm)	23 7/16" (595mm)
Overall dim - height	23 3/16" (589mm)	23 3/16" (589mm)	23 3/16" (589mm)	23 3/16" (589mm)	23 3/16" (589mm)
Overall dim - depth	22 1/16" (560mm)	22 1/16" (560mm)	22 1/16" (560mm)	22 1/16" (560mm)	22 1/16" (560mm)
Cutout - width	22 1718 (3001111) 28" (710mm)	22 1716 (3001111) 28" (710mm)	22 1/16" (560mm)	22 1/10 (3001111) 28" (710mm)	22 1/16" (560mm)
	23" (585mm)	23" (585mm)	22 1716 (560mm) 23" (585mm)	23" (585mm)	
Cutout - height (min) Cutout - depth (min)	23 (585mm) 24" (610mm)	23 (385mm) 24" (610mm)	23 (585mm) 24" (610mm)	23 (585mm) 24" (610mm)	23" (585mm) 24" (610mm)
Power / Ratings (208/240 V, 60 Hz)	27 (01011111)	27 (0101111)		27 (0101111)	27 (01011111)
KW/Amps rating at 240V, 60Hz	3.625kW - 15.6Amps	 3.625kW - 15.6Amps	2.5kW - 10.424mpc	3.625kW - 15.6Amps	3050W/127Amps 20050V
		3.529kW - 15.0Amps	2.5kW - 10.42Amps 2.345kW - 11.3Amps		3050W/12,7Amps approx.
KW/Amps rating at 208V, 60Hz Cable + Conduit	3.529kW - 17.4Amps X	3.529KW - 17.4Amps X	Z.345KW - TT.3Amps X	2.720kW - 11.4Amps X	2300W/9,5 Amps approx. X
	Λ	^	Λ	~	^
Instructions for use					
Use & Care Manual	EN, SP, FR	EN, SP, FR	EN, SP, FR	EN, SP, FR	EN, SP, FR
Installation Manual	EN, SP, FR	EN, SP, FR	EN, SP, FR	EN, SP, FR	EN, SP, FR



Cooktops



Fulgor Milano cooktops embody Italian elegance and design while offering the quality and durability expected from one of Europe's leading manufacturers of built in cooking appliances.

Nothing is compromised in the performance of our products. Born from a culture of cooking that is world renowned, our customers should not expect less.

You will be the envy of your guests with your beautiful Italian appliance, which may inspire you to take your culinary skills to new elevations.

The shallow design of our cook tops allow kitchen designers to optimize space, providing the greatest flexibility possible for a variety of installation possibilities.

With a Fulgor Milano cooktop, your dream kitchen will become a reality.



600 Series Induction Cooktops

Our 600 series induction cooktops follow the same design criteria of all our Fulgor-Milano products; style, function, and performance are at the heart of this product.

Like our radiant touch cooktops, our induction units are finished with a subtle yet elegant aluminum trim that exudes luxury while offering all of the features you expect from a premium cooking appliance. Our induction cooktops offer the power and control of a gas cooktop with the speed and cleanability of a radiant cooktop, giving you the best of both worlds. From tempering fine chocolate, braising a classic osso bucco, or bringing a 15 quart stock pot to boil in minutes, the possibilities are endless with our induction technology. Induction Cooktops 600 Ser

FRAME

Aluminum frame stainless steel color protects the glass edges from damage

ELECTRONIC CONTROL

State-of-the-art "Peacock" control. LED displays cooking level. Booster function and low-power settings for accuracy



INDUCTION

Heating only the area beneath the pot means cooking safely without compromise. The exact amount of energy needed to heat the pan--no more, no less!



PERFORMANCES OF INDUCTION COOKING

High efficiency

Induction is the most efficient technology available today for cooking. The heat is transferred directly to the iron component in the bottom of the cooking vessel, without loss of energy

Reduced heating times

Induction is 30% to 50% faster compared with other existing cooking technology

Low surface temperature

The glass surface is heated from contact with cooking vessels. Because of this, surface temperatures are lower than those of traditional glass-ceramic cooktops. Glass is a non-stick surface, making cleaning easy

Pan detection

The system detects the presence of cookware over a cooking zone, stopping automatically and cooling down mere seconds after a pan is removed. It can even distinguish between types of pans

Safety

The system detects only vessels having minimum pan diameter; it does not detect small items like utensils that may accidentally be left on the cooktop.

Control lock prevents unintentional activation

HOW DOES INDUCTION COOKING WORK?

Every cooking zone consists of a copper coil (inductor) driven by an electronic system that can generate a high-frequency current in order to induce an electromagnetic field. Some ferrite (material with a very high magnetic permeability) elements located under the inductor form a loop of magnetic flux (red lines in the picture) with the bottom of the cooking

vessel (it must be made with ferro-magnetic material). The lines of force of the electromagnetic field induce in the bottom of the pot strong eddy currents which generate a large amount of heat



DIMENSIONS







Series 600



Available in Canada Only

F6IT36S1

36" Induction cooktop with aluminum frame in stainless steel color and glass ceramic

- Slide touch control for power setting
- "Peacock Tail" Bar for power indication
- 5 Digital display for power level indication
- Low temperature electronic control for delicate cooking
- Command Lock
- Booster/Fast boil function
- Hot Surface indication and residual heat indication
- Timer display with 5+1 timers functions and acoustic buzzer
- Failure Codes indication

Front Left Zone

- Size 6"
- Power 1200W
- Booster 1400W

Rear Left Zone

- Size 8″
- Power 2200W
- Booster 3000W

Central Zone (double)

- Size 11"/7"
- Power 2650W/1800W
- Booster 3600W/2800W

Rear Right Zone

- Size 8″
- Power 2200W
- Booster 3000W

Front Right Zone

- Size 6″
- Power 1200W
- Booster 1400W

Special features:

- Pan Detection System
- Special Big Double zone
- Cooling fan system





Available in Canada Only

F6IT30S1

30" Induction cooktop with aluminum frame in stainless steel color and glass ceramic

- Slide touch control for power setting
- "Peacock Tail" Bar for power indication
- 4 Digital display for power level indication
- Low temperature electronic control for delicate cooking
- Command Lock
- Booster/Fast boil function
- Hot Surface indication and residual heat indication
- Timer display with 4+1 timers functions and acoustic buzzer
- Failure Codes indication

Front Left Zone

- Size 6"
- Power 1200W
- Booster 1400W
- Rear Left Zone
- Size 8″
- Power 2200W
- Booster 3000W

Rear Right Zone

- Size 7″
- Power 1800W
- Booster 2800W
- Front Right Zone
- Size 6"
- Power 1200W
- Booster 1400W

Special features:

- Pan Detection System
- Cooling fan system







600 Series Radiant Touch Cooktops

Beautiful intuitive controls designed with elegance and precision. Radiant touch cooktops deliver quick and reliable performance with maximum flexibility. Touch controls with patented Peacock control sliding bar for power-level selection and fast boil with automatic power reduction. Radiant Touch Cooktops 600 Ser

FRAME

Aluminum frame stainless steel color: Sophisticated and functional!



ELECTRONIC CONTROL

Fine-tuning of the lower temperatures plus timer function is standard with our "Peacock" tail control. Slide touch bar for continuous setting



HEATING ELEMENT

Trademark FulLight[®] radiant heating elements provide quick, reliable and evenly distributed heat for more consistent cooking.

Our premium triple burner, offered in the 36" and 30" cooktop, ensures complete flexibility



55

DIMENSIONS



24" cooktop







F6RT36S1

36" Electric radiant cooktop with aluminum frame in stainless steel color and glass ceramic

- Slide touch control for power setting
- "Peacock Tail" Bar for power indication
- 5 Digital display for power level indication
- Low temperature electronic control for delicate cooking
- Command Lock
- Automatic Fast Boil function
- Hot Surface indication and residual heat indication
- Timer display with 5+1 timers functions and acoustic buzzer
- Failure Codes indication

Front Left Zone

- Size 7″
- Power 1800W
- **Bridge Element**
- Power 800W

Rear Left Zone

- Size 8″
- Power 1800W

Central Zone

- Size 9" / 7" / 5"
- Power 2500W / 1600W / 800W

Rear Right Zone

- Size 7″
- Power 1800W
- Front Right Zone ■ Size 6″
- Power 1200W





F6RT30S1

30" Electric radiant cooktop with aluminum frame in stainless steel color and glass ceramic

- "Peacock Tail" Bar for power indication
- 4 Digital display for power level indication
- Low temperature electronic control for delicate cooking
- Command Lock
- Automatic Fast Boil function
- Hot Surface indication and residual heat indication
- Timer display with 4+1 timers functions and acoustic buzzer
- Failure Codes indication

Front Left Zone

- Size 6″
- Power 1200W
- **Rear Left Zone**
- 9″/7″/5″
- Power 2500W / 1600W / 800W

Rear Right Zone

- Size 8" / 5"
- Power 2200W / 800W

Front Right Zone

- Size 6″
- Power 1200W





F6RT24S1

24" Electric radiant cooktop with aluminum frame in stainless steel color and glass ceramic, 600 Series

- 3 Digital display for power level indication
- Low temperature electronic control for delicate cooking
- Command Lock
- Automatic Fast Boil function
- Hot Surface indication and residual heat indication
- Timer display with 1 timer functions and acoustic buzzer
- Failure Codes indication

Front Left Zone

- Size 5" 1/2
- Power 1200W
- **Rear Left Zone**
- 8″/ 5″
- Power 2200W / 800W
- **Rear Right Zone**
- Size 7"
- Power 1800W



300 Series Radiant Cooktops

Our 300 series cooktops offer the same elegant European design and family line as our radiant touch and induction cooktops but in a package that offers great value and performance to the consumer.

The manual controls are reliable and accurate and continue to be the most user friendly of all control systems available today. Even the most discerning cooks will be impressed with the functionality and performance of this mainstay. Like all Fulgor-Milano cooktops the 300 series offers a shallow profile for countless installation options. Radiant Cooktops 300 Seri

DESIGN

Maintaining style continuity throughout the line, our control knob design ensures clarity and ease of use



HEATING ELEMENT

Trademark FulLight[®] radiant heating elements provide quick, reliable and evenly distributed heat for more consistent cooking

PREMIUM GLASS

World leader in premium ceramic glass for the appliance industry, using only the finest material and superior processes



DIMENSIONS



24" cooktop



24" cooktop with frame









F3RK36B1

36" Electric radiant cooktop in glass ceramic

- 5 knobs for power level setting
- Hot Surface indicator
- Residual heat indication

Front Left Zone

Size 9" / 6"
Power 2500W / 1100W
Rear Left Zone
Size 6"
Power 1200W
Central Zone
Size 11" / 8"
Power 2700W / 1800W
Rear Right Zone
Size 7"
Power 1800W

Front Right Zone

- Size 6″
- Power 1200W





F3RK30B1

30" Electric radiant cooktop in glass ceramic

- 4 knobs for power level setting
- Hot Surface indicator
- Residual heat indication

Front Left Zone

- Size 9" / 6"
 Power 2500W / 1100W
 Rear Left Zone
 Size 6"
 Power 1200W
 Rear Right Zone
 Size 7"
 Power 1800W
- Front Right Zone
- Size 6″
- Power 1200W





F3RK24B1

24" Electric radiant cooktop in glass ceramic

- 4 knobs for power level setting
- Hot Surface indicator
- Residual heat indication

Front Left Zone ■ Size 7″

Power 1800W
Rear Left Zone
Size 5 1/2"
Power 1200W
Rear Right Zone
Size 7"
Power 1800W
Front Right Zone

- Size 5 1/2"
- Power 1200W





F3RK24S1

24" Electric radiant cooktop with aluminum frame in stainless steel color and glass ceramic

- 4 knobs for power level setting
- Hot Surface indicator
- Residual heat indication

Front Left Zone

Size 7 3/4" / 4 3/4"
Power 1900W / 800W
Rear Left Zone
Size 5 1/2"
Power 1200W
Rear Right Zone
Size 7"
Power 1800W
Front Right Zone
Size 5 1/2"


400 Series Gas Cooktops

The 400 series "Largo" cooktops utilize the most advanced technology available and combine this with a classic Italian design, resulting in a cooktop that not only performs magnificently but also looks spectacular.

A design that lends itself to countless application possibilities, the 400 series cooktops also take the consumers cooking and maintenance needs into consideration. All grates are separated in sizes that make them easy to handle and remove for cleaning. The burners are well orientated for ease of use, with unique configurations like a wok burner and fifth burner on a 30" unit, making this cook top one of the most versatile in the category.

Explore the Largo cooktop family and enjoy the possibilities; buon appetito!

Gas Cooktops 400 Seri

CLASSIC DESIGN

Italian design principles inform the style, function and performance of this series, creating a classic yet versatile cooktop



DUAL BURNER

Fulgor-Milano uses a dual-flame European-style sealed burner to deliver a wide range of heat

EUROPEAN SEALED BURNERS

Designed with only two removable parts, our sealed burners keep spills from leaking inside the cooktop

DIMENSIONS









Series 400



F4GK42S1

42" Gas cooktop with 4 burners, stainless steel

- Electric Flame Ignition and Re-ignition
- Flame out sensing
- Heavy Duty Cast Iron Grates
- On request: simmer Plate and small Pot Insert (for single burners only)
- On request: wok ring (for dual burner only)

Left Burner

Max. 18000 (BTU/h) - 5275W
Min. 450 (BTU/h) - 135W

Left Middle Burner

- Max . 4000 (BTU/h) 1175W
- Min. 1000 (BTU/h) 295W

Right Middle Burner

- Max . 9000 (BTU/h) 2640W
- Min. 1300 (BTU/h) 380W

Right Burner

- Max . 15000 (BTU/h) 4400W
- Min. 2700 (BTU/h) 790W



F4GK36S1

36" Gas cooktop with 5 burners, stainless steel

- Electric Flame Ignition and Re-ignition
- Flame out sensing
- Heavy Duty Cast Iron Grates
- On request: simmer Plate and small Pot Insert (for single burners only)
- On request: wok ring (for dual burner only)

Front Left Burner

Max. 6300 (BTU/h) - 1850W
Min. 1300 (BTU/h) - 380W

Rear Left Burner

- Max. 9000 (BTU/h) 2640W
- Min. 1300 (BTU/h) 380W

Front Middle Burner

- Max. 18000 (BTU/h) 5275W
- Min. 450 (BTU/h) 135W

Rear Right Burner

- Max. 12000 (BTU/h) 3520W
- Min. 2200 (BTU/h) 645W

Front Right Burner

- Max. 4000 (BTU/h) 1175W
- Min. 1000 (BTU/h) 295W

Gas Cooktops 400 Series





F4GK30S1

30" Gas cooktop with 5 burners, stainless steel

- Electric Flame Ignition and Re-ignition
- Flame out sensing
- Heavy Duty Cast Iron Grates
- On request: simmer Plate and small Pot Insert (for single burners only)
- On request: wok ring (for dual burner only)

Front Left Burner

Max. 18000 (BTU/h) - 5275W
Min. 450 (BTU/h) - 135W

Front Middle Burner

- Max. 4000 (BTU/h) 1175W
- Min. 1000 (BTU/h) 295W

Rear Middle Burner

- Max. 12000 (BTU/h) 3520W
- Min. 2200 (BTU/h) 645W

Rear Right Burner

- Max. 9000 (BTU/h) 2640W
- Min. 1300 (BTU/h) 380W

- Max. 6300 (BTU/h) 1850W
- Min. 1300 (BTU/h) 380W



F4GK24S1

24" Gas cooktop with 4 burners, stainless steel

- Electric Flame Ignition and Re-ignition
- Flame out sensing
- Heavy Duty Cast Iron Grates
- On request: simmer Plate and small Pot Insert (for single burners only)

Front Left Burner

Max. 18000 (BTU/h) - 5275W
Min. 450 (BTU/h) - 135W

Rear Left Burner

- Max. 6300 (BTU/h) 1850W
- Min. 1300 (BTU/h) 380W

Rear Right Burner

- Max. 12000 (BTU/h) 3520W
- Min. 2200 (BTU/h) 645W

- Max. 4000 (BTU/h) 1175W
- Min. 1000 (BTU/h) 295W



300 Series Gas Cooktops

Italian wing design for greater surface space and the flexibility to position large pots and pans diagonally on the cooktop.

Patented dual crown burners (36" models only) from 18,000 BTU/H for searing meat and locking in flavor, down to 450 BTU/H.

Sealed burners are easy to clean and to remove.

Heavy-duty cast-iron grates, automatic re-ignition with flame detection, and top mount injectors for better serviceability.

Useful accessories featured like small-pot reduction, simmer plate and wok ring. Environmentally friendly, made with over 90% recyclable components.

CAST IRON GRATES

Heavy-duty cast-iron grates are designed for you to slide pots and pans from burner to burner

DUAL BURNER

Fulgor-Milano uses a dual-flame European-style sealed burner to deliver a wide range of burner output, from 18,000 BTU/h for meat-searing and wok cooking, down to 450 BTU/h for melting chocolate and locking in flavors

EUROPEAN SEALED BURNERS

Designed with only two removable parts, our sealed burners keep spills from leaking inside the cooktop

SMALL POT REDUCTION

Uniquely designed accessory (included) allows you to use pans smaller than 4 inches on a stable, flat cooking surface, without increasing the distance from the flame



83

DIMENSIONS

36" cooktop













F3GK36S1

36" Gas cooktop with 5 burners, stainless steel

- Electric Flame Ignition and Re-ignition
- Flame out sensing
- Dual Crown Burner
- Heavy Duty Cast Iron Grates
- Delivered with small Pot Insert
- On request: wok ring and simmer Plate

Front Left Burner

Max .4000 (BTU/h) - 1175W
Min.1000 (BTU/h) - 295W

Rear Left Burner

- Max.15000 (BTU/h) 4400W
- Min.1700 (BTU/h) 500W

Central Burner

- Max.18000 (BTU/h) 5275W
- Min.450 (BTU/h) 135W

Rear Right Burner

- Max.9000 (BTU/h) 2640W
- Min.1300 (BTU/h) 380W

- Max. 9000 (BTU/h) 2640W
- Min. 1300 (BTU/h) 380W



F3GK30S1

30" Gas cooktop with 4 burners, stainless steel

- Electric Flame Ignition and Re-ignition
- Flame out sensing
- Heavy Duty Cast Iron Grates
- Delivered with small Pot Insert
- On request: wok ring and simmer Plate

Front Left Burner

Max . 15000 (BTU/h) - 4400W
Min. 1700 (BTU/h) - 500W

Rear Left Burner

- Max. 9000 (BTU/h) 2640W
- Min. 1300 (BTU/h) 380W

Rear Right Burner

- Max. 12000 (BTU/h) 3520W
- Min. 1700 (BTU/h) 500W

- Max. 6300 (BTU/h) 1850W
- Min. 1300 (BTU/h) -380W

Accesories & Technical Data Cooktops

Our useful accessories will help you customize your appliance while giving you ease, efficiency and success in your cooking.

Our gas series accessories our guaranteed to enhance your cooking experience, ensuring there is no compromise to your cooking techniques.

COOKTOPS ACCESSORIES

89





300 & 400 GAS SERIES

SMALL POT REDUCTION

Uniquely designed accessory allows you to use pans smaller than 4 inches on a stable, flat cooking surface

WOK RING

For best results with a wok, use this separate, high-BTU burner specifically for wok cooking

SIMMER PLATE

The cast-iron simmer plate provides a steady simmer temperature, evenly distributed across a stable heating surface





NODEL	F6IT36S1	F6IT30S1
ze	36"	30"
blour	Steel	Steel
eating Technology	Induction	Induction
ass Type	Glass Ceramic	Glass Ceramic
ame	Aluminum	Aluminum
ontrol type	Touch Control Peacock High	Touch Control Peacock High
pecial Features		
n Detection System	X	X
pecial Big Double zone	Х	
poling fan system	Х	Х
ontrol Features		
ide touch control for power setting	X	X
eacock Tail" Bar for power indication	Х	Х
gital display for power level indication	5	4
w power scale for delicate cooking	X	X
pmmand Lock	X	X
poster/Fast boil function	× ×	× ×
bt Surface indication	X	× ×
sidual heat indication	^ X	^ X
mer functions	1+5	1+4
mer display	X	X
coustic buzzer		
ailure Codes indication	X	Х
ront Left Zone		
ze	б"	6"
ower	1200W	1200W
poster	1400W	1400W
ear Left Zone		
ze	8"	8"
ower	2200W	2200W
boster	3000W	
entral Zone (double)		
ze	11" / 7"	
ower	2650W/1800W	
ooster	3600W/2800W	
ear Right Zone		
ze	8"	7"
wer	2200W	1800W
ooster	3000W	2800W
ont Right Zone		
ze	б"	6"
ower	1200W	1200W
oster	1400W	1400W
mensions/Weight - (In or Lbs)		
verall dim - width	36" (919mm)	30" (771mm)
verall dim - height	3 9/32" (84mm)+ conduit 15/16" (24mm)	3 9/32" (84mm)+ conduit 15/16" (24mm)
verall dim - depth	21" (538mm)	21" (538mm)
utout - width	34 1/16" (865mm) - 34 5/16" (872mm)	28 11/16" (729mm) - 28 15/16" (735mm)
itout - height (min)	3 1/16" (78mm)+ conduit 15/16" (24mm)	3 1/16" (78mm)+ conduit 15/16" (24mm)
tout - depth (min)	19 19/64" (490mm) - 19 5/8" (498mm)	19 19/64" (490mm) - 19 5/8" (498mm)
pprox ship weight	19.4Kg (43 Lbs)	16.2 Kg (36 Lbs)
ower / Ratings (208/240 V, 60 Hz)	15. mg (15 E05)	
	10 2004W 45 Amor	7 200/204 204 mpc
V/Amps rating at 240V, 60Hz	10.800kW - 45Amps	7.200kW - 30Amps
N/Amps rating at 208V, 60Hz	9.700kW - 46,6Amps	6510kW - 31,3Amps
able + Conduit	X	X
structions for use		
se & Care Manual	EN, SP, FR	EN, SP, FR







MODEL	F6RT36S1	F6RT30S1	F6RT24S1
ōize	36"	30"	24"
olour	Steel	Steel	Steel
leating technology	Radiant Heaters	Radiant Heaters	Radiant Heaters
lass Type	Glass Ceramic	Glass Ceramic	Glass Ceramic
rame	Aluminum	Aluminum	Aluminum
ontrol type	Touch Control Peacock High	Touch Control Peacock High	Touch Control Peacock Low
ontrol Features			
ide touch control for power setting	Х	Х	NO
Peacock Tail" Bar for power indication	Х	Х	NO
igital display for power level indication	5	4	3
ow power scale for delicate cooking	Х	Х	Х
ommand Lock	Х	Х	Х
utomatic Fast Boil function	Х	Х	Х
lot Surface indication	Х	Х	Х
esidual heat indication	Х	Х	Х
mer functions	1+5	1+4	1
imer display	Х	Х	Х
coustic buzzer	Х	Х	Х
ailure Codes indication	Х	X	Х
ront Left Zone			
ize	7"	б"	5"1/2
ower	1800W	1200W	1200W
ridge Element			
ower	800W		
ear Left Zone			
ize	7"	9" / 7" / 5"	8" / 5"
ower	1800W	2500W / 1600W / 800W	2200W / 800W
entral Zone	100011	2300117 1000117 00011	2200117 00011
ize	9" / 7" / 5"		
ower	2500W / 1600W / 800W		
ear Right Zone			
ize	7"	8" / 5"	7"
ower	1800W	2200W / 800W	1800W
ront Right Zone	100000	220007 00000	100000
ize	6"	6"	
ower	1200W	1200W	
Dimensions/Weight - (In or Lbs)	12000	12000	
Overall dim - width	36" (919mm)	30" (771mm)	24" (618mm)
Dverall dim - height	3 9/32" (84mm)+ conduit 15/16" (24mm)	3 9/32" (84mm)+ conduit 15/16" (24mm)	3 9/32" (84mm)+ conduit 15/16" (24mm)
verall dim - depth	21" (538mm)	21" (538mm)	21" (538mm)
1	34 1/16" (865mm) - 34 5/16" (872mm)		
utout - width (min-max)	3 1/16 (805mm) - 34 5/16 (8/2mm) 3 1/16" (78mm)+ conduit 15/16" (24mm)	28 11/16" (729mm) - 28 15/16" (735mm)	22 5/8" (574mm) - 22 13/16" (580mm) 3 1/16" (78mm) + conduit 15/16" (24mm)
ox - height utout - denth (min-max)		3 1/16" (78mm)+ conduit 15/16" (24mm)	3 1/16" (78mm)+ conduit 15/16" (24mm)
utout - depth (min-max)	19 19/64" (490mm) - 19 5/8" (498mm)	19 19/64" (490mm) - 19 5/8" (498mm)	19 1/4" (490mm) - 19 9/16" (497mm)
ower / Ratings (208/240 V, 60 Hz)	0.000144 41.25 Arrest	7100144/ 20504	E 2001/04/ 21 674
W/Amps rating at 240V, 60Hz	9.900kW - 41.25Amps	7.100kW - 29.58Amps	5.200kW - 21.67Amps
W/Amps rating at 208V, 60Hz	7.436kW - 35.75Amps	5.332kW - 25.63Amps	3.900kW - 18.75Amps
able + Conduit	X	X	Х
nstructions for use			
lse & Care Manual	EN, SP, FR	EN, SP, FR	EN, SP, FR



MODEL	F3RK36B1	F3RK30B1	F3RK24B1	F3RK24S1
Size	36"	30"	24"	24"
Colour	Black	Black	Black	Stainless Steel
Heating Technology	Radiant Heaters	Radiant Heaters	Radiant Heaters	Radiant Heaters
Glass Type	Glass Ceramic	Glass Ceramic	Glass Ceramic	Glass Ceramic
Frame	NO	NO	NO	Aluminium
Control type	Knobs	Knobs	Knobs	Knobs
Control Features				
Knobs for power level setting	5	4	4	4
Knobs type	Plastic MGH "U"	Plastic MGH "U"	Plastic MGH "U"	Plastic MGH "U"
Hot Surface indication	Х	Х	Х	Х
Residual heat indication	Х	Х	Х	Х
Front Left Zone				
Size	9" / 6"	9" / 6"	7"	7 3/4" / 4 3/4"
Power	2500W / 1100W	2500W / 1100W	1800W	1900W / 800W
Rear Left Zone				
Size	б"	6"	5 1/2"	5 1/2"
Power	1200W	1200W	1200W	1200W
Central Zone				
Size	11"/8"			
Power	2700W / 1800W			
Rear Right Zone				
Size	7"	7"	7"	7"
Power	1800W	1800W	1800W	1800W
Front Right Zone				
Size	б"	6"	5 1/2"	5 1/2"
Power	1200W	1200W	1200W	1200W
Dimensions/Weight - (In or Lbs)		_		
Overall dim - width	36" (914mm)	30 1/4" (767mm)	24" (613mm)	24" (618mm)
Overall dim - height	2 3/16" (56mm)	2 3/16" (56mm)	3 9/32" (84mm)+ conduit 15/16" (24mm)	3 9/32" (84mm)+ conduit 15/16" (24mm)
Overall dim - depth	21" (533mm)	21" (533mm)	21" (533mm)	21" (538mm)
Cutout - width (min-max)	34 1/16" (865mm) - 34 5/16" (872mm)	28 11/16" (729mm) - 28 15/16" (735mm)	22 5/8" (574mm) - 22 13/16" (580mm)	22 5/8" (574mm) - 22 13/16" (580mm)
Box - height	2" (50,8mm) + conduit 15/16" (24mm)	2" (50,8mm) + conduit 15/16" (24mm)	3 1/16" (78mm)+ conduit 15/16" (24mm)	3 1/16" (78mm)+ conduit 15/16" (24mm)
Cutout - depth (min-max)	19 1/4" (490mm) - 19 9/16" (497mm)	19 1/4" (490mm) - 19 9/16" (497mm)	19 1/4" (490mm) - 19 9/16" (497mm)	19 1/4" (490mm) - 19 9/16" (497mm)
Approx ship weight	17.5 Kg (38.6Lbs)	13.5 Kg (30Lbs)	13.5 Kg (30Lbs)	13.5 Kg (30Lbs)
Power / Ratings (208/240 V, 60 Hz)				
KW/Amps rating at 240V, 60Hz	9.400kW - 39.17Amps	6.700kW - 27.9Amps	6.000kW - 25.00Amps	6.100kW - 25.42Amps
KW/Amps rating at 208V, 60Hz	7.060kW - 33.94Amps	5.032kW - 24.19Amps	4.507kW - 21.67Amps	4.582kW - 22.03Amps
Cable + Conduit	Х	Х	Х	Х
Instructions for use				
Use & Care Manual	EN, SP, FR	EN, SP, FR	EN, SP, FR	EN, SP, FR
Installation Manual	EN, SP, FR	EN, SP, FR	EN, SP, FR	EN, SP, FR



MODEL	F4GK42S1	F4GK36S1	F4GK30S1	F4GK24S1
ize	42"	36"	30"	24"
Iolour	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Heating Technology	Gas	Gas	Gas	Gas
Gas Type	NG or LP	NG or LP	NG or LP	NG or LP
P. Conversion Kit	Х	Х	Х	Х
op Mount Injectors	Х	Х	Х	Х
Knobs	Plastic MGH "U" - Frontal			
Cooktop Features				
Design	Largo	Largo	Largo	Largo
Electric Flame Ignition and Re-ignition	Х	Х	Х	Х
lame out sensing	Х	Х	Х	Х
Dual Crown Burner	Х	Х	Х	Х
Simmer Plate	Optional	Optional	Optional	Optional
Small Pot Insert	Optional (for single burners only)			
Vok Ring	Optional (for dual burner only)	Optional (for dual burner only)	Optional (for dual burner only)	Not available
leavy Duty Cast Iron Grates	4	3	2	4
lumber of Burners	4	5	5	4
Burner 1	Left Burner	Front Left Burner	Front Left Burner	Front Left Burner
Power (Max)	18000 (BTU/h) - 5275W	6300 (BTU/h) - 1850W	18000 (BTU/h) - 5275W	18000 (BTU/h) - 5275W
ower (Min)	450 (BTU/h) - 135W	1300 (BTU/h) -380W	450 (BTU/h) - 135W	450 (BTU/h) - 135W
Surner 2		Rear Left Burner	Rear Left Burner	Rear Left Burner
'ower (Max)		9000 (BTU/h) - 2640W		6300 (BTU/h) - 1850W
ower (Min)		1300 (BTU/h) - 380W		1300 (BTU/h) -380W
Surner 3	Left Middle Burner	Front Middle Burner	Front Middle Burner	Front Middle Burner
ower (Max)	4000 (BTU/h) - 1175W	18000 (BTU/h) - 5275W	4000 (BTU/h) - 1175W	
ower (Min)	1000 (BTU/h) - 295W	450 (BTU/h) - 135W	1000 (BTU/h) - 295W	
Burner 4	Right Middle Burner	Rear Middle Burner	Rear Middle Burner	Rear Middle Burner
'ower (Max)	9000 (BTU/h) - 2640W		12000 (BTU/h) - 3520W	
Power (Min)	1300 (BTU/h) - 380W		2200 (BTU/h) - 645W	
Surner 5		Rear Right Burner	Rear Right Burner	Rear Right Burner
'ower (Max)		12000 (BTU/h) - 3520W	9000 (BTU/h) - 2640W	12000 (BTU/h) - 3520W
'ower (Min)		2200 (BTU/h) - 645W	1300 (BTU/h) - 380W	2200 (BTU/h) - 645W
Burner 6	Right Burner	Front Right Burner	Front Right Burner	Front Right Burner
Power (Max)	15000 (BTU/h) - 4400W	4000 (BTU/h) - 1175W	6300 (BTU/h) - 1850W	4000 (BTU/h) - 1175W
Power (Min)	2700 (BTU/h) - 790W	1000 (BTU/h) - 295W	1300 (BTU/h) -380W	1000 (BTU/h) - 295W
Dimensions/Weight - (In or Lbs)				
Overall dim - width	1119mm	909mm	760mm	620mm
Overall dim - height	74mm	74mm	74mm	74mm
Overall dim - depth	425mm	510mm	510mm	510mm
Lutout - width (min-max)	1096mm-1099mm	886mm - 889mm	737mm - 740mm	597mm-600mm
utout - height	T.B.D.	T.B.D.	T.B.D.	T.B.D.
Cutout - depth (min-max)	404,5mm - 407,5mm	489,5mm - 492,5mm	489,5mm - 492,5mm	489,5mm - 492,5mm
Power / Ratings				
lectrical rating	120V, 60Hz	120V, 60Hz	120V, 60Hz	120V, 60Hz
/lax Power (BTU/HR)	46000 (BTU/h) - 13475W	52300 (BTU/h) - 15320W	49300 (BTU/h) - 14440W	40300 (BTU/h) - 11800W
Eable	X	X	Χ	Х
nstructions for use	~	^/	~	N
Jse & Care Manual	EN, SP, FR	EN, SP, FR	EN, SP, FR	EN, SP, FR





MODEL	F3GK36S1	F3GK30S1
Size	36"	30"
Colour	Stainless Steel	Stainless Steel
Heating Technology	Gas	Gas
Gas Type	NG or LP	NG or LP
L.P. Conversion Kit	Х	Х
Top Mount Injectors	X	X
Knobs	Plastic MGH "U" - Lateral	Plastic MGH "U" - Lateral
Cooktop Features		
Design	Lateral Wing	Lateral Wing
Electric Flame Ignition and		
Re-ignition	X	X
Flame out sensing	Х	Х
Dual Crown Burner	Х	
Simmer Plate	Optional	Optional
Small Pot Insert	Х	Χ
Wok Ring	Optional	Optional
Heavy Duty Cast Iron Grates	3	2
Number of Burners	5	4
Burner 1	Front Left Burner	Front Left Burner
Power (Max)	4000 (BTU/h) - 1175W	15000 (BTU/h) - 4400W
Power (Min)	1000 (BTU/h) - 295W	1700 (BTU/h) - 500W
Burner 2	Rear Left Burner	Rear Left Burner
Power (Max)	15000 (BTU/h) - 4400W	9000 (BTU/h) - 2640W
Power (Min)	1700 (BTU/h) - 500W	1300 (BTU/h) - 380W
Burner 3	Central Burner	Central Burner
Power (Max)	18000 (BTU/h) - 5275W	
Power (Min)	450 (BTU/h) - 135W	
Burner 4	Rear Right Burner	Rear Right Burner
Power (Max)	9000 (BTU/h) - 2640W	12000 (BTU/h) - 3520W
Power (Min)	1300 (BTU/h) - 380W	1700 (BTU/h) - 500W
Burner 5	Front Right Burner	Front Right Burner
Power (Max)	9000 (BTU/h) - 2640W	6300 (BTU/h) - 1850W
Power (Min)	1300 (BTU/h) - 380W	1300 (BTU/h) -380W
Burner 6		
Power (Max)		
Power (Min)		
Dimensions/Weight - (In or Lbs)		
Overall dim - width	36" (915mm)	
Overall dim - height	3 1/8" (80mm)	30 (7021111) 3 1/8" (80mm)
Overall dim - depth	21" (533mm)	21" (533mm)
Cutout - width (min-max)	34 1/2" (876mm) - 35" (889mm)	28 1/2" (724mm) - 29" (737mm)
Cutout - height	5 1/4" (134mm)	5 1/4" (134mm)
Cutout - depth (min-max)	19" (483mm) - 19 5/8" (498mm)	19" (483mm) - 19 5/8" (498mm)
Power / Ratings	1201/ 001	1007 501
Electrical rating	120V, 60Hz	120V, 60Hz
Max Power (BTU/HR)	55000 (BTU/h) - 16110W	42300 (BTU/h) - 12390W
Cable	Х	X
Instructions for use		-
Use & Care Manual	EN, SP, FR	EN, SP, FR
Installation Manual	EN, SP, FR	EN, SP, FR



Meneghetti S.p.a. reserves the right to make updates to the information and products or discontinue models contained in this catalogue without notice

catalogue coordinators Marketing Fulgor

FULGOR MILANO®

Meneghetti S.p.a. Via Borgo Lunardon, 8 • 36027 Rosà (Vicenza) - Italy http://www.fulgor-milano.us • e-mail: info@fulgor-milano.us