
FULGOR

MILANO



			1 SHADED AREA:		
OPENING WIDTH	A & C	В			
Range 30"	30" (762)		The surface of the entire back wall above the range and below the hood must be covered with a noncombustible material.		
Range 36"	36" (914)	7" (178)			
Range 48"	48" (1220)	7" (178)	*Consult local code for exact location requirements.		

Note: Clearances from non-combustible materials are not part of the ANSI Z21.1 scope and not certified. Clearances to non-combustible materials must conform with local codes or, in the absence of local codes, with the National Fuel Gas Code, ANSI Z223.1/NFPA 54.

Minimum clearances:

Above cooking surface (above 36" [91.4 cm])


- Sides 6" (15.2 cm)
- Within 6" (15.2 cm) side clearance, wall cabinets no deeper than 13" (33.0 cm) must be minimum 18" (45.7 cm) above cooking surface
- Wall cabinets directly above product must be a minimum of 48" (122 cm) above cooking surface.
- Rear 0" with 9 "backguard; 0" with non-combustible rear wall.


Below cooking surface (36" [91.4 cm] and below)

• Install with zero clearance between adjacent combustible construction below the cooking surface and the back and sides of the appliance

ADDITIONAL CLEARANCES:

For island installation, maintain 2-½ in. minimum from cutout to back edge of countertop and 3 in. minimum from cutout to side edges of countertop (see top view). For installation in a stepped island, 12" (30.5 cm) minimum clearance is required from the back or sides of the range to a combustible riser. The island installation is not part of the ANSI 221.1 scope and not certied.





PACKAGING 30"	lb / inch	Kg / mm	
GROSS WEIGHT	326 lb	148 Kg	
	W	33"	840
DIMENSION	Н	45-3/4"	1162
	D	32-1/4"	820

PACKAGING 36"	lb / inch	Kg / mm	
GROSS WEIGHT	382 lb	173 Kg	
	W	39"	990
DIMENSION	Н	45-3/4"	1162
	D	32-1/4"	820

PACKAGING 48"	lb / inch	Kg / mm	
GROSS WEIGHT		512 lb	232 Kg
	W	51-1/2"	990
DIMENSION	Н	46-1/8"	1173
	D	32-1/4"	820

