

FULGOR

MILANO

600 Series 48" Dual Fuel Range

F6PDF486GS1



Series

Size
Main Colour
Logo
Stainless Steel Aesthetics

600
DUAL FUEL
48"
SS
•
Professional

Cooktop

Type

Cooking Surface
Gas Type
Knobs

GAS
Black Enameled
NG (5") or LP (10")
•

Gas Cooktop Features

Electric Flame Ignition and Re-ignition
Flame out sensing
Top Mount Injectors
L.P. Conversion Kit
Dual Flame Brass Burner
Flat Griddle
Heavy Duty Cast Iron Grates
Pressure Regulator

•
•
•
•
•
•
3
•

Cooking Zones

6+Griddle

Front Left

Dual Flame Burner

Power (Max/ Min) Natural Gas
Power (Max/ Min) Propane

20000 (BTU/h) - 5850W / 750 (BTU/h) - 220W
15000 (BTU/h) - 4400W / 750 (BTU/h) - 220W

Rear Left

Dual Flame Burner

Power (Max/ Min) Natural Gas
Power (Max/ Min) Propane

18000 (BTU/h) - 5300W / 750 (BTU/h) - 220W
15000 (BTU/h) - 4400W / 750 (BTU/h) - 220W

Central Middle "Left"

Griddle Burner

Power (Max/ Min) Natural Gas
Power (Max/ Min) Propane

11500 (BTU/h) - 3370W / 2000 (BTU/h) - 590W
11500 (BTU/h) - 3370W / 2000 (BTU/h) - 590W

Front Middle "Right"

Dual Flame Burner

Power (Max/ Min) Natural Gas
Power (Max/ Min) Propane

18000 (BTU/h) - 5300W / 750 (BTU/h) - 220W
15000 (BTU/h) - 4400W / 750 (BTU/h) - 220W

Rear Middle "Right"

Dual Flame Burner

Power (Max/ Min) Natural Gas
Power (Max/ Min) Propane

18000 (BTU/h) - 5300W / 750 (BTU/h) - 220W
15000 (BTU/h) - 4400W / 750 (BTU/h) - 220W

Front Right

Dual Flame Burner

Power (Max/ Min) Natural Gas
Power (Max/ Min) Propane

20000 (BTU/h) - 5850W / 750 (BTU/h) - 220W
15000 (BTU/h) - 4400W / 750 (BTU/h) - 220W

Rear Right














Dual Flame Burner

Power (Max/ Min) Natural Gas
Power (Max/ Min) Propane

18000 (BTU/h) - 5300W / 750 (BTU/h) - 220W
15000 (BTU/h) - 4400W / 750 (BTU/h) - 220W

FULGOR

MILANO

Oven		18"	30"
Type		ELECTRIC PIRO	ELECTRIC PIRO
Oven Type		Multifunction 1 Fan	Multifunction 2 Fans
Temperature Regulation		Electronic (max temp. 550°F/290°C)	
Functions			
Pyrolitic Self-Clean with automatic door latch		•	•
True European Convection Bake (Multi level)		•	•
Convection Broil		•	•
Convection Roast		•	•
Pizza (Lower Convection)		•	•
Bake		•	•
Broil		•	•
Dehydrate		•	•
Thaw (Defrost)		•	•
Proof (Warm)		•	•
Keep warm (Warm Plus)		•	•
Oven Lights		•	•
Fast Preheat		•	•
Control Panel			
Control type		HAWK3TC - Electronic	
Clock Display		White LED	
Temperature Display		White LED	
Function Display		White LED	
Commands		8 Heavy Duty Knobs / 6 Touch Keys	
Language		English	
Electric Oven Features			
Preset/Last used temperature memory		•	
Preheat bar (25%, 50%, 75%, 100%)		•	
Automatic Fast Preheat		•	
Child Door Lock		•	
Commands Lock		•	
Sabbath mode		•	
12/24 hour clock format		•	
°C/°F		•	
Oven Door(s)			
Oven Glass Window		Deep Embossed Window	
Door Cooling System		4 Pane Heat Resistant Glass	
Soft closing system		•	
Door Hinges		Heavy Duty Steady Tilt	
Handle Style		Stainless Steel Tube d30mm, Metal terminals	
Oven Cavity			
Gross Capacity (cuft)		2.7	4.4
Usable Capacity (cuft)		2.4	4.1
Cavity Enamel Colour		Black	Black
Rack Positions		6	6
Oven Lights		2x20W Halogen	3x20W Halogen
Heating Element			
Broil Upper Heating Element		2100 W (240V)	3500 W (240V)
Upper Auxiliary Element Wattage		700W (240V)	1032W (240V)
Concealed Bake Lower Heating Element		1750 W (240V)	3000 W (240V)
Convection Element Wattage		1x2500W (240V)	2x1300 W (240V)
Oven Accessories			

FULGOR

MILANO

Chromed racks	2	2
Enameled Grill set (basin + anti splash)		1
Telescopic chromed rack	1	1
Meat probe	not present	1

Dimensions

Overall dim - width	47 3/4" (1216mm)
Height min/max	36 3/8" (923mm) / 38 1/4" (972mm)
Overall dim - depth	29 3/4" (756mm)

Power / Ratings (208/240 V, 60 Hz)

KW/Amps rating at 120-240V, 60Hz	6.08kW - 26.7A
KW/Amps rating at 120-208V, 60Hz	5.73kW - 28.3A
Cable + Plug	Nema 14-50P

INSTRUCTIONS FOR USE

Use & Care Manual	EN, SP, FR
Installation Manual	EN, SP, FR