

600 Series 36" Induction Range

F6PIR365S1



	600
Series	
	FULL ELECTRIC
Size	36"
Main Colour	SS
Logo	•
Stainless Steel Aestethics	Professional
Cooktop	
Туре	INDUCTION
Cooking Surface	Ceramic Glass
Knobs	•
Induction Special Features	
Pot Detection System	•
Child lock function	•
Cooling for avetom	•

Cooling fan system	•
Failure Codes indication	•
Induction Control Features	
Knob for power setting (illuminated)	•
Power levels	1 to 9
Digital display for power level indication	•
Melting Function 113°F / 45°C (inside the pot 108°F / 42°C)	•
Warming Function 158°F / 70°C (inside the pot 149°F / 65°C)	•
Booster/Fast boil function for each zone	•
Heat up time automatic	•
Residual heat indication	•
Cooking Zones	5
Front Left	Inductor 9" (230mm)
Power L9	2300W
Booster	3700W
Rear Left	Inductor 7" (180mm)
Power L9	1850W
Booster	3000W
Middle dual circuit	Inductor 11" (280mm)
Power L9	3000W
Booster	5500W
Middle single circuit	Inductor 7" (180mm)
Power L9	1850W
Booster	2600W
Front Right	Inductor 9" (230mm)
Power L9	2300W
Booster	3700W
Rear Right	Inductor 7" (180mm)
Power L9	1850W
Booster	3000W



Oven

Child Door Lock

°C/°F

Door Hinges

Handle Style

Туре		ELECTRIC PIRO
Oven Type		Multifunction 2 Fans (True Euro Convection)
Temperature Regulation		Electronic (max temp. 550°F/290°C)
Functions		
Pyrolitic Self-Clean with automatic door latch		•
True European Convection Bake (Multi level)	$\langle \cdot \rangle \langle \cdot \rangle$	•
Convection Broil	X	•
Convection Roast	X	•
Pizza (Lower Convection)	L	•
Bake		•
Broil	***	•
Dehydrate	\checkmark	•
Thaw (Defrost)	Y	•
Proof (Warm)	<u></u>	•
Keep warm (Warm Plus)	<u> </u>	•
Oven Lights	- Ò -	•
Fast Preheat		•
Control Panel		
Control type		HAWK3TC - Electronic
Clock Display		White LED
Temperature Display		White LED
Function Display Commands		White LED 6 Heavy Duty Knobs (6 Touch Keys
Language		6 Heavy Duty Knobs / 6 Touch Keys English
Electric Oven Features		
Preset/Last used temperature memory		•
Preheat bar (25%, 50%, 75%, 100%)		•
Automatic Fast Preheat		•
Child Dear Leak		-

Commands Lock Sabbath mode 12/24 hour clock format Oven Door(s) Oven Glass Window Deep Embossed Window 4 Pane Heat Resistant Glass Door Cooling System Soft closing system Heavy Duty Steady Tilt Stainless Steel Tube d30mm, Pro Style Oven Cavity Gross Capacity (cuft) 5.7 Usable Capacity (cuft) 4.9 Rlack

Cavity Enamel Colour	Black
Rack Positions	6
Oven Lights	3x20W Halogen
Heating Element	
Broil Upper Heating Element	3500 W (240V)
Upper Auxiliary Element Wattage	1032W (240V)
Concealed Bake Lower Heating Element	3000 W (240V)
Convection Element Wattage	2x1300 W (240V)
Oven Accessories	
Chromed racks	2
Enameled Grill set (basin + anti splash)	1
Telescopic chromed rack	1
Meat probe	1
Dimensions	
Overall dim - width	35 3/4" (910mm)

FULGOR		
	MILANO	
(36 3/8" (925mm) / 38 1/2" (977mm)	
epth	29 3/4" (756mm)	
ings $(208/240 \text{ V} 60 \text{ Hz})$		

Height min/max	36 3/8" (925mm) / 38 1/2" (977mm)
Overall dim - depth	29 3/4" (756mm)
Power / Ratings (208/240 V, 60 Hz)	
KW/Amps rating at 120-240V, 60Hz	14.6KW - 61A
KW/Amps rating at 120-208V, 60Hz	13.3kW - 63A
Cable + Plug	Nema 14-50P
INSTRUCTIONS FOR USE	
Use & Care Manual	EN, SP, FR
Installation Manual	EN, SP, FR