30" PROFESSIONAL COMBI STEAM OVEN

F6PSCO30S1





Steam Cooking



Steam Limescale Filter



True Convection



Automatic Cooking



Meat Probe



Cool Touch Door



Multi-level cooking

SPECIFICATIONS

FEATURES

Steam Generator

3 in 1 Oven: Steam, Convection, and Combi-steam Stainless Interior with broiler Quick Access Menu Automatic Programs Meat Probe 240 Volt Connection

PERFORMANCE

12 Functions
Automatic Cooking
Pre-selected and customizable recipes
(weight, temperature, cooking time)
Steam System
Combined Cooking Functions
Steam Recovery Cycle
CLEAN, assisted cleaning cycle for
oven interior and steam circuit




This product meets ADA (Americans with Disabilities Act) requirements.

Please check with your local municipality's codes and stipulations for additional details to ensure compliance.

fulgor-milano.us FULGOR MILANO

PROFESSIONAL COMBI SPEED OVEN





CODE ID	30" SOFIA PRO STEAM OVEN - F6PSCO30S1	
Туре	Steam + f	an assisted
Finish		ess steel
Temperature Regulation	Electronic	
FUNCTIONS	LIGGROUNG	
		/ <u>^</u>
Microwave / Steam cook	-/•	
Steam reheat	•	
Microwave / Steam convection	•	
Steam clean / circuit	•	
5 minute steam	•	
Convection bake	•	
Convection roast	•	
Convection broil	•	
Broil	•	
Eco convection bake	•	
Recipes	•	
Oven Lights	•	
CONTROL PANEL		
Control type	MODULAR - Electronic	
Display	TFT 3.5"	
Menu Recipes	11100	
<u>'</u>	Dual Full Tauch Marks and	
Commands	Dual Full Touch Keyboard	
Language	4	
SPECIAL FEATURES		
Manual Fast Preheat	•	
Meat Probe	•	
12/24 hour clock format	•	
°C/°F	•	
OVEN DOOR(S)		
Cool door	•	
OVEN CAPACITY		
Gross Capacity (cuft)	1.2	
Usable Capacity (cuft)	1.0	
Cavity Enamel Color	Stainless Steel	
Rack Positions	3	
Oven Lights	1x20W Halogen	
Broil Upper Heating Element	1500W (240V)	
Steamer Steamer Western	1500W (240V) 300W (240V)	
Lower Element Wattage Convection Element Wattage	2300W (240V)	
ACCESSORIES	23007	(2400)
Chrome racks	1	
Stainless Steel Tray	•	
Telescopic chrome rack	-	
SIZE		
Overall dim - width	29 - 7/8"	758 mm
Overall dim - height	18 - 5/8"	473 mm
Overall dim - depth	21"	533 mm
Cutout - width	25 - 3/4"	654 mm
Cutout - height (min)	18"	458 mm
Cutout - depth (min)	22"	560 mm
POWER / RATINGS	0.0LM 40.7A	
KW/Amps rating at 200V, 60Hz	3.3kW - 13.7A	
KW/Amps rating at 208V, 60Hz Cable + Conduit	2.48kW - 11.9A	
INSTRUCTION FOR USE		
	EN 00 50	
Use & Care Manual / Installation Manual	EN, SP, FR	

fulgor-milano.us FULGOR MILANO