700 SERIES OVEN



## F7DSCO30S1



Steam Cooking



Steam Limescale Filter



True Convection



Automatic Cooking



Meat Probe



Cool Touch Door



Multi-level cooking

### **SPECIFICATIONS**

## **FEATURES**

3 in 1 Oven: Steam, Convection, and Combi-steam Stainless Interior with broiler Quick Access Menu Automatic Programs Meat Probe 240 Volt Connection Steam Generator

#### **PERFORMANCE**


12 Functions
Automatic Cooking
Pre-selected and customizable recipes
(weight, temperature, cooking time)
Steam System
Combined Cooking Functions
Steam Recovery Cycle
CLEAN, assisted cleaning cycle for
oven interior and steam circuit

fulgor-milano.us FULGOR MILANO

# **DISTINTO**

30" COMBI STEAM OVEN





CODE ID	30" COMBI STEAM OVEN F7DSC030S1	
		175000001
Series	700	
Finish	Stainless Steel	
CONTROL PANEL		
Programming	MODULAR - Electronic	
Control Type	Dual Full Touch Keyboard	
Automatic Cooking	•	
Auto power off		•
OVEN		
Туре	Steam Oven	
Interiors	Stainless Steel	
Pull-down Door	•	
MAIN FEATURES		
Gross Capacity (cu.ft)	1.2	
Usable Capacity (cu.ft)	1.0	
Tangential cooling ventilation	•	
Total no. of modes		12
PERFORMANCE		
Maximum cooking temperature	230°C / 446°F	
Automatic Cooking	•	
Steam 210°F / 270°F	•	
Steam Injection 210°F	•	
Steam + Fan Assisted	•	
Assisted Cleaning (CLEAN)	1500	
Power Output Grill (W)		
Oven Lights	1x20W Halogen	
Broil Upper Heating Element	1500W (240V) 1500W (240V)	
Steamer		
Lower Element Wattage Convection Element Wattage	300W (240V) 2300W (240V)	
	23UUVV (24UV)	
SAFETY		- /0
Safety Door/ no. Panes of Glass Control Lock	•/3	
ACCESSORIES		•
No. of Lights (20 W halogen)		1
Removable tank (liters / fl oz)	1.4 / 45	
No./Type of Gastronorm Trays	2 / Stainless Steel	
Grey Metal Flat/no. of Supports	2 / Statilless Steel 1 / 1	
DIMENSIONS / WEIGHT		17.1
Width in/mm	29 - 7/8"	758 mm
Height in/mm	18 - 5/8"	473 mm
Depht in/mm	21"	533 mm
Recess (LxHxP) in/mm	(25 - 3/4" x 18" x 22")	(654 x 458 x 560 mm)
POWER / RATINGS	(EO 0/4 A 10 A 22 )	(004 X 400 X 000 Hilli)
KW/Amps rating at 240V, 60Hz	3.3kW - 13.7A	
KW/Amps rating at 240V, 60Hz	2.48kW - 11.9A	
Power Cord	Cable + Conduit	
INSTRUCTIONS FOR USE		Capita i Conduit
Use & Care Manual / Installation Manual	English / French / Spanish	

fulgor-milano.us FULGOR MILANO