

# FULGOR

## MILANO

### 700 Series 36" Induction Cooktop Touch Control

**F7IT36S1**



<b>Series</b>	<b>700</b>
Size	36"
Colour	Steel
Heating Technology	Induction
Glass Type	Glass Ceramic
Frame	Aluminum
Control type	Touch Control
<b>Special Features</b>	
Pan Detection System	•
Bridge Double zone	•
Cooling fan system	•
<b>Control Features</b>	
Power Levels	1 to 9
Warming Function (158°F / 70°C)	•
Booster/Fast-boil (all zones)	•
Auto-boil and Reduce (all zones)	•
Residual Heat Indication (all zones)	•
Individual Timer for each Zone	•
Child Lock	•
Key Lock (LED)	•
Pause/recall (LED)	•
General ON/OFF Key (LED)	•
<b>Left Zone</b>	
Size	11" (280mm)
Power L9	2300W
Booster	3600W
<b>Rear Central Zone</b>	
Size	7" (180mm)
Power L9	1850W
Booster	3000W
<b>Front Central Zone</b>	
Size	5 ¾" (145mm)
Power L9	1400W
Booster	2200W
<b>Rear Right Zone (Octagonal)</b>	
Size	7 ½" x 8 ½" (190mm x 220mm)
Power L9	2000W
Booster	3600W
<b>Front Right Zone (Octagonal)</b>	
Size	7 ½" x 8 ½" (190mm x 220mm)
Power L9	2000W
Booster	3600W
<b>Dimensions/Weight - (In or Lbs)</b>	
Overall dim - width	36 3/16" (919mm)
Overall dim - height	4" (100mm)
Overall dim - depth	21 3/16" (538mm)
Cutout - width	34 5/8" (879mm) +/- 1/16" (1mm)
Cutout - height (min)	2 5/8" (67mm)+ conduit 1 1/16" (27mm)
Cutout - depth (min)	19 7/16" (494mm) +/- 1/16" (1mm)
Approx ship weight	22.9 kg (51 Lbs)

# FULGOR

## MILANO

### Power / Ratings (208/240 V, 60 Hz)

KW/Amps rating at 240V, 60Hz

10.800kW - 45A

KW/Amps rating at 208V, 60Hz

9.400kW - 45A

Cable + Conduit

•

### INSTRUCTIONS FOR USE

Use & Care Manual

EN, SP, FR

Installation Manual

EN, SP, FR