## JEP5030ST

## GE 30" Built-In Knob Control Electric Cooktop


## **DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)**

**IMPORTANT**: Requires a 5" free area between the bottom of the cooktop to any combustible material, i.e., shelving. Free area not required when installing wall oven underneath cooktop. Refer to installation instructions. Requires a 15" minimum from cooktop to adjacent overhead cabinets. Units are furnished with a 48" flexible armored cable.

**NOTE:** 30" Ribbon cooktops are approved for use over select GE 27" and GE 30" Single Wall Ovens and Warming Drawers. Refer to cooktop and wall oven/warming drawer installation instructions packed with product for current dimensional data. If installed with a GE Telescopic Downdraft System, consult both the cooktop and downdraft installation instructions packed with product before installing, Cooktop gas/electric supply may need to be re-routed to install downdraft. The countertop cutout requires 23-1/2" minimum flat countertop surface and 25" minimum total countertop depth. In addition, other clearances to front edge of the countertop must be considered. Before installing. consult installation instructions packed with product for current dimensional data.

**CUTOUT FILLER TRIM KIT:** A filler trim kit is available for use if your countertop cutout is larger than the dimension shown, up to 29-13/16" x 20-7/16". Order JXTR32B for black or JXTR32W for white, to reduce the cutout opening for installation of this cooktop. These kits may be ordered from your GE Appliances Dealer.


#### APPROXIMATE COOKING DIMENSIONS



To insure accuracy, it is best to make a template when cutting the opening in the counter

### 13" MAX. depth of unprotected overhead cabinets 1 1/2" MIN. (30") and 2" MIN. (36") Clearance from cutout to nearest vertical wall or cabinet on right side of the unit below the 15" MIN. clearance height. 30" MIN, for 30" MIN. Clearance from counterton to unprotected overhead surface 15" MIN. height from countertop to nearest cabinet (including light rails) on both sides of 2" MIN. Clearance from cutout to nearest vertical wall or cabinet on left side of the unit below the 15" MIN. clearance height.

#### **INSTALLATION ABOVE A WALL OVEN**



VOLTAGE (60HZ AC)	240V	208V
CONNECTED LOAD (MAX.)	9.6kW	7.2kW
CURRENT DRAW (MAX.)	40 Amps	34.6 Amps
RECOMMENDED CIRCUIT BREAKER	40 Amps	40 Amps

\*NOTE: Check local codes for required breaker size.



For answers to your Monogram, GE Café<sup>™</sup>, GE Profile<sup>™</sup> or GE Appliances product questions, visit our website at geappliances.com or call GE Answer Center<sup>®</sup> Service, 800.626.2000.





## JEP5030ST

# GE 30" Built-In Knob Control Electric Cooktop

### **FEATURES AND BENEFITS**

Easy Clean Surface

Power Boil on Dual-Ring Element (3,100W)

Additional Power Boil Dual-Ring Element (2,200W)

Keep Warm Setting

Control Lock


Hot Surface Indicator Lights

Fit Guarantee

Flexible Cooktop

Melt Setting

Model JEP5030STSS - Stainless steel



### **GUARANTEED FIT**

Replacing a similar cooktop from GE Appliances or another brand? GE cooktops are guaranteed for an exact fit or GE Appliances will pay up to \$100 toward modifications.

Visit geappliances.com for more info.

