


## **GE Appliances**

# JVM1640AJ/BJ/CJ/SJ/WJ – GE Spacemaker® Over-the-Range Microwave Oven

### **Dimensions (in inches)**



**Note:** Requires 120V grounded outlet. Electrical receptacle must be located in cabinet above Spacemaker microwave oven. No additional wiring, venting or cabinet rebuilding necessary in many cases. Complete detailed, easy-to-follow installation instructions and convenient full-size templates are packed with the Spacemaker microwave oven.

**Important Information:** When installing the Spacemaker microwave oven over a range, allow minimum of 2" from bottom of Spacemaker microwave oven to top of range backguard to allow for removal of light covers.

**Ventilation Options:** The Spacemaker microwave ovens are designed for adaptation to the following three types of ventilation:

- Outside exhaust (vertical as shown)
- Outside exhaust (horizontal)
- Recirculating (non-vented ductless)

**Installation Information:** This information is not intended to be used for installing unit described. Before installing, consult installation instructions packed with product/kit for current dimensional data.




For answers to your Monogram,® GE Profile™ or GE® appliance questions, visit our website at GEAppliances.com or call GE Answer Center® service, 800.626.2000.



### **GE Appliances**

## JVM1640AJ/BJ/CJ/SJ/WJ – GE Spacemaker® Over-the-Range Microwave Oven

### Optional Accessories (Available at additional cost)



**HOOD EXHAUST DUCT:** Outside ventilation requires a HOOD EXHAUST DUCT. Read the following carefully.

**EXHAUST CONNECTION:** The hood exhaust has been designed to mate with a standard 3-1/4" x 10" rectangular duct. If a round duct is required, a rectangular-to-round transition adaptor must be used. Do not use less than a 6" diameter duct

**REAR EXHAUST:** If a rear or horizontal exhaust is to be used, care should be taken to align exhaust with space between studs, or wall should be prepared at the time it is constructed by leaving enough space between the wall studs to accommodate exhaust.

**MAXIMUM DUCT LENGTH**: For satisfactory air movement, the total duct length of 3-1/4" x 10" rectangular or 6" diameter round duct should not exceed 140 equivalent feet.

**ELBOWS, TRANSITIONS, WALL AND ROOF CAPS**, etc., present additional resistance to airflow and are equivalent to a section of straight duct which is longer than their actual physical size. When calculating the total duct length, add the equivalent length of all transitions and adaptors plus the lengths of all straight duct sections. The chart below shows the approximate feet of equivalent length of some typical ducts.


Duct	<b>Equivalent Feet</b>
<b>A.</b> Rectangular-To-round Transition Adaptor	5 ft.
<b>B.</b> Wall Cap	40 ft.
<b>C.</b> 90° Elbow	10 ft.
<b>D.</b> 45° Elbow	5 ft.
<b>E.</b> 90° Elbow	25 ft.
<b>F.</b> 45° Elbow	5 ft.
<b>G.</b> Roof Cap	24 ft.





## **GE Appliances**

# JVM1640AJ/BJ//CJ/SJ/WJ – GE Spacemaker® Over-the-Range Microwave Oven



### **Features and Benefits**

- 1.6 cu. ft. capacity 1000 Watts (IEC-705 test procedure)
- Convenience cooking controls Allows cooking and reheating at the touch of a button.
- Auto/Time Defrost Automatically defrost for a specified amount of time.
- Turntable On/Off Ideal for oversized, oblong-shaped dishes.
- Removable oven rack Makes multi-dish cooking possible.
- Full-view cooktop lighting Illuminates the cooking surface below.
- Two-speed, 300-CFM venting system Quickly removes smoke and steam from the cooktop.
- Model JVM1640WJ White on white
- Model JVM1640BJ Black on black
- Model JVM1640AJ Almond on almond
- Model JVM1640CJ Bisque on bisque
- Model JVM1640SJ Stainless steel