## **LG LAUNDRY**



## DLEX5500\_/DLGX5501\_

7.4 cu. ft. Capacity Energy Star Smart Front Load Dryer with Al Sensor Dry & TurboSteam®

7.4 cu. ft. Ultra Large Capacity

Digital Dial Control with LCD Display & Touch Button Control Panel

Al Sensor Dry with Smart Pairing

TurboSteam®, SteamFresh®, and SteamSanitary® Technology

Wrinkle Care Option

LG ThinQ® Technology with ThinQ Care

FlowSense® Duct Clogging Indicator

Tempered Glass Door (Reversible)

NeveRust® Stainless Steel Drum

**ENERGY STAR® Certified** 

## AVAILABLE COLORS



GRAPHITE STEEL





Yes Yes

Yes Yes Yes Yes Yes Yes Yes

Yes

Yes Yes Yes Yes

TurboSteam@

Electric: 4 Way Venting / Gas: 3 Way Venting

Electric: 3.94 / Gas: 3.49

Painted Steel Tempered Glass Door Graphite Steel (V), White (W)



## **Proactive Smart Alerts to Keep** Your Appliances Running Smoothly

- · Preventative Alerts help you stay a step ahead of potential
- ThinQ Care issues to find proactive solutions before problems arise.

  Avoid preventable repairs and service calls with real-time diagnostics for a hassle-free experience.
  - · Integrated within LG's ThinQ app-a smart home hub for managing your smart devices and appliances.



POWER SOURCE

SUMMARY		FABRIC CARE FEATURES
Туре	Front Load Dryer	Al Sensor Dry
Vent Type	Vented	Sensor Dry
Dryer Type	Elec: DLEX5500V / DLEX5500W Gas: DLGX5501V/ DLGX5501W	Precise Temperature Control with Variable Heater
Capacity	7.4 cu. ft.	Steam
Matching Washer	WM5500HVA / WM5500HWA	CONVENIENCE FEATURES
Sensor Dry	Yes	3 Minute Installation Check
Steam	Yes	End of Cycle Signal
Color	Graphite Steel (V), White (W)	Drum Light (Door Open)
APPEARANCE		Reversible Door
LCD Display Touch Buttons	Yes Yes	FlowSense® Duct Clogging Indicator
Dial-A-Cvcle®	Yes	Wrinkle Care Option
DRYER PROGRAMS	res	Control Lock
	23	W 0
No. of Programs		Venting Option
Programs (Sensor Dry)	Normal, AI Dry, Bedding, Delicates, Towels, Quick Dry, Timed Dry, Power Dry, Perm. Press, SteamFresh™, Heavy Duty, Air Dry, Steam Sanitary™, Super Dry, Active Wear, Jeans, Blanket Refresh, Low Temp Dry, Overnight Dry, Easy Ironing, Small Load, Large Load Dry, X Large Load Dry	4 Adjustable Legs Remaining Time Display / Status Indicator(s)
		ThinQ® TECHNOLOGY
		Smart Diagnosis
		Wi-Fi
		ThinQ Care
No. of Options	11	Remote Start and Cycle Monitor
Options	Cycle Optimization, Damp Dry Signal, Wrinkle Care, Control Lock, Wi-Fi, Energy Saver, TurboSteam®, Reduce Static, Remote Start, Drum Light, Signal, Cycle Edit List	Energy Monitoring
		ENERGY
		ENERGY STAR® Certified
		CEF
		MATERIALS AND FINISHES
Temperature Settings	High, Med. High, Medium, Low,	NeveRust® Stainless Steel Drum
	Ultra Low	Cabinet
Drying Levels	Very Dry, More Dry, Normal Dry, Less Dry, Damp Dry	Door
Manual Dry Times	10 min ~ 100 min (10 min increments)	All Available Colors

Ratings	CSA Listed
Electrical Requirements	Elec: 120/240V, 60Hz, 26A Gas: 120V, 60Hz, 11.5A
Гуре	Electric, Gas
BTU Rating	Gas: 20,000
OPTIONS	
P Conversion Kit	383EEL3002D
Side Venting Kit	3911EZ9131X
Orying Rack	3750EL1001A
Pedestal	WDP6V, WDP6W
Pedestal (WxHxD)	27" x 13 5/8" x 28" (43 7/8" D with door open)
DIMENSIONS	
Product (WxHxD)	27" x 39" x 29 3/4"
Depth with Door Open	51 3/8"
Carton (WxHxD)	28 7/8" x 46 1/2" x 31 3/8"
Product Weight (lbs.)	Electric: 124.3 lbs. / Gas: 136.0 lbs.
Carton Weight (lbs.)	Electric: 136.5 lbs. / Gas: 146.6 lbs.
LIMITED WARRANTY	
Parts & Labor	1 Year
Drum	3 Years
JPC CODES	
DLEX5500V (Graphite Steel)	195174048580
DLGX5501V (Graphite Steel)	195174048894
DLEX5500W (White)	195174048603
DLGX5501W (White)	195174048900