## WM3555H\_A

# LG BUILDER

.G Life's Good

## 2.4 cu. ft. Compact All-in-One Washer & Dryer Combo

- Compact All-In-One Washer/Dryer Combination
- Ventless Condensing Drying
- 2.4 cu. ft. Capacity
- TurboWash<sup>®</sup> 360 Technology
- Steam Technology & Allergiene<sup>™</sup> Cycle
- 14 Cycles / 13 Options
- Internal Heater
- Direct Drive Motor (10-Year Limited Warranty)
- NeverRust<sup>™</sup> Stainless Steel Drum
- LG ThinQ<sup>®</sup> Technology (Wi-Fi)

### COLOR AVAILABILITY

WM3555HVA – Graphite Steel

)	WM3555HWA -	White


CAPACITY & MATCHING DRYERS	
Capacity (cu. ft.)	2.4
Matching Electric Dryer	N/A
Matching Gas Dryer	N/A
APPEARANCE	
Electronic Controls with LED Display	Yes
Hard Buttons	Yes
Touch Buttons	Yes
Dial-A-Cycle™	Yes
ENERGY & WATER	
ENERGY STAR <sup>®</sup> Qualified	No
CEE Qualified	No
Integrated Modified Energy Factor (IMEF)	2.07
Integrated Water Factor (IWF)	4.2
CYCLES	
Number of Cycles	14
Wash Cycles	Normal, Bulky/Large, Baby Wear, Perm. Press, Delicates, Quick Wash, Tub Clean, Sanitary, Heavy Duty, Drain+Spin, Wash+Dry, Allergiene™, Steam Refresh, Downloaded
OPTIONS	
Number of Options	13
Options	Steam, Wrinkle Care, Delay Wash, Remote Start, Wi-Fi, TurboWash®, Extra Rinse, Pre Wash, Control Lock, Dry, Waterless Dry, Heavy Soil, Signal



200 mina	•
WASH DETAILS	
Internal Heater	Yes
Number of Wash/Rinse Temps	5
Wash/Rinse Temps	Extra Hot, Hot, Warm, Cold, Tap Cold (All Cold Rinses)
Number of Spin Speeds	5
Spin Speeds	Extra High, High, Medium, Low, No Spin
Max RPM	1,400
Water Levels	Load Sensing
Number of Soil Levels	2
AAFA Certified	Yes
DRY DETAILS	
Ventless Condensing Drying	Yes
Automatic Dry Cycles	Normal Dry, Damp Dry, Low Temp Dry, Normal Eco Dry, Waterless Dry
Time Drying	120 min, 60 min, 30 min
Normal Drying	Yes
Turbo Drying	No
FABRIC CARE	
AI DD™	Yes
Wash Technology	TurboWash® 360
Steam Technology	Yes
Allergiene™ Cycle	Yes
Sanitary Cycle	Yes
ColdWash™ Option	No
SenseClean™ System	Yes
CONVENIENCE	
TrueBalance™ Anti-Vibration System	Yes
Dispenser Type	3-Tray (Main Wash Detergent, Liquid Fabric Softener, Prewash Detergent)
LoDecibel™ Quiet Operation	Yes

CONVENIENCE CONTINUED	
End of Cycle Signal	Yes
LoadSense	Yes
Child Lock	Yes
Auto Suds Removal	Yes
4 Adjustable Leveling Legs	Yes
Easy Loading TilTub™	Yes
ADA Compliant	No
SMART FEATURES	
Wi-Fi Enabled	Yes
ThinQ®	Yes
ThinQ Care	Yes
Voice Control	Google Assistant, Amazon Alexa
SmartDiagnosis™	Yes
Remote Start and Cycle Monitor	Yes
MOTOR AND AGITATOR	
Motor Type	Inverter Direct Drive Motor
Axis	Horizontal
MATERIALS AND FINISHES	
NeveRust™ Stainless Steel Drum	Yes
Door / Rim	Chrome
Door Cover	Glass
750000000	
TECHNICAL SPECS	
TECHNICAL SPECS Electrical Requirements	120V, 60 Hz, 15 Amps
	120V, 60 Hz, 15 Amps Electric
Electrical Requirements	· · · ·
Electrical Requirements Type	Electric
Electrical Requirements Type Power Outlet Location	Electric Within 60" of Either Side
Electrical Requirements Type Power Outlet Location Plug Type	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit)
Electrical Requirements Type Power Outlet Location Plug Type Min. / Max. Water Pressure	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit)
Electrical Requirements Type Power Outlet Location Plug Type Min. / Max. Water Pressure	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit) 20 - 120 psi
Electrical Requirements Type Power Outlet Location Plug Type Min. / Max. Water Pressure INCLUDED ACCESSORIES	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit) 20 - 120 psi
Electrical Requirements Type Power Outlet Location Plug Type Min. / Max. Water Pressure INCLUDED ACCESSORIES OPTIONAL ACCESSORIES	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit) 20 - 120 psi Drain Hose
Electrical Requirements Type Power Outlet Location Plug Type Min. / Max. Water Pressure INCLUDED ACCESSORIES OPTIONAL ACCESSORIES Pedestal LG Sidekick™ Pedestal Washer Stacking Kit	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit) 20 - 120 psi Drain Hose N/A
Electrical Requirements Type Power Outlet Location Plug Type Min. / Max. Water Pressure INCLUDED ACCESSORIES OPTIONAL ACCESSORIES Pedestal LG Sidekick™ Pedestal Washer	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit) 20 - 120 psi Drain Hose N/A N/A
Electrical Requirements Type Power Outlet Location Plug Type Min. / Max. Water Pressure INCLUDED ACCESSORIES OPTIONAL ACCESSORIES Pedestal LG Sidekick™ Pedestal Washer Stacking Kit	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit) 20 - 120 psi Drain Hose N/A N/A
Electrical Requirements Type Power Outlet Location Plug Type Min. / Max. Water Pressure INCLUDED ACCESSORIES OPTIONAL ACCESSORIES Pedestal LG Sidekick™ Pedestal Washer Stacking Kit DIMENSIONS	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit) 20 - 120 psi Drain Hose N/A N/A Not Stackable
Electrical Requirements Type Power Outlet Location Plug Type Min. / Max. Water Pressure INCLUDED ACCESSORIES OPTIONAL ACCESSORIES Pedestal LG Sidekick™ Pedestal Washer Stacking Kit DIMENSIONS Product (W x H x D) Depth with Door Open Cutout Dimensions (W x H x D)	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit) 20 - 120 psi Drain Hose N/A N/A N/A Not Stackable 24" x 33 1/2" x 22 1/4" 43 1/4" 26" x 33 <b>3/4</b> " x 26 1/4"
Electrical Requirements Type Power Outlet Location Plug Type Min. / Max. Water Pressure INCLUDED ACCESSORIES OPTIONAL ACCESSORIES Pedestal LG Sidekick™ Pedestal Washer Stacking Kit DIMENSIONS Product (W × H × D) Depth with Door Open	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit) 20 - 120 psi Drain Hose N/A N/A N/A Not Stackable 24" x 33 1/2" x 22 1/4" 43 1/4"
Electrical Requirements Type Power Outlet Location Plug Type Min. / Max. Water Pressure INCLUDED ACCESSORIES OPTIONAL ACCESSORIES Pedestal LG Sidekick™ Pedestal Washer Stacking Kit DIMENSIONS Product (W x H x D) Depth with Door Open Cutout Dimensions (W x H x D)	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit) 20 - 120 psi Drain Hose N/A N/A N/A Not Stackable 24" x 33 1/2" x 22 1/4" 43 1/4" 26" x 33 <b>3/4</b> " x 26 1/4"
Electrical Requirements Type Power Outlet Location Plug Type Min. / Max. Water Pressure INCLUDED ACCESSORIES OPTIONAL ACCESSORIES Pedestal LG Sidekick™ Pedestal Washer Stacking Kit DIMENSIONS Product (W × H × D) Depth with Door Open Cutout Dimensions (W × H × D) Carton Dimensions (W × H × D)	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit) 20 - 120 psi Drain Hose N/A N/A N/A Not Stackable 24" x 33 1/2" x 22 1/4" 24" x 33 3/4" x 26 1/4" 26" x 33 3/4" x 26 1/4"
Electrical Requirements Type Power Outlet Location Plug Type Min. / Max. Water Pressure INCLUDED ACCESSORIES OPTIONAL ACCESSORIES Pedestal LG Sidekick™ Pedestal Washer Stacking Kit DIMENSIONS Product (W × H × D) Depth with Door Open Cutout Dimensions (W × H × D) Carton Dimensions (W × H × D) Approx. Weight (Product / Carton)	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit) 20 - 120 psi Drain Hose N/A N/A N/A Not Stackable 24" x 33 1/2" x 22 1/4" 24" x 33 3/4" x 26 1/4" 26" x 33 3/4" x 26 1/4" 26" x 35" x 26" 160.9 lbs. / 169.8 lbs.
Electrical Requirements Type Power Outlet Location Plug Type Min. / Max. Water Pressure INCLUDED ACCESSORIES OPTIONAL ACCESSORIES Pedestal LG Sidekick™ Pedestal Washer Stacking Kit DIMENSIONS Product (W x H x D) Depth with Door Open Cutout Dimensions (W x H x D) Carton Dimensions (W x H x D) Carton Dimensions (W x H x D) Approx. Weight (Product / Carton) LIMITED WARRANTY	Electric Within 60" of Either Side 3-Prong (Cord Attached to Unit) 20 - 120 psi Drain Hose N/A N/A N/A Not Stackable 24" x 33 1/2" x 22 1/4" 43 1/4" 26" x 33 3/4" x 26 1/4" 26" x 35" x 26" 160.9 lbs. / 169.8 lbs.

### **DIMENSIONS / CLEARANCES**



### INSTALLATION NOTES

- To ensure sufficient clearance for water lines, the drain line and airflow, allow minimum clearances of at least 1 inch (2.5 cm) at the sides and 4 inches (10 cm) behind the washer. Be sure to allow for wall, door, or floor moldings that may increase the required clearances.
- Install the washing machine on a solid floor that is strong and rigid enough to support the weight of the washing machine, even when fully loaded, without flexing or bouncing. If the floor has too much flex, you may need to reinforce it to make it more rigid. If the floor is not solid, it may cause severe vibration and noise.
- $\bullet$  The floor under the washer must not slope more than 1 inch (2.5 cm) from front to back or side to side.

ASTHMA & ALLERGY FRIENDLY Mark is a Registered Trade Mark of the ASTHMA AND ALLERGY FOUNDATION OF AMERICA and ALLERGY STANDARDS LTD.



Business

Solutions

© 2022 LG Electronics USA, Inc. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp. All other product and brand names are trademarks or registered trademarks of their respective owners. Design, features and specifications are subject to change without notice. Non-metric weights and measurements are approximate. Some features may require Internet access. Content and services may vary by product and are subject to change without notice. 5/2